



**TUPEX PROFESSIONAL  
LIGHTING SYSTEM**  
catalogue




All products in this catalogue are designed, engineered and completely made in Italy.




# General Catalogue



ALL PRODUCTS IN THIS CATALOGUE  
ARE DESIGNED, ENGINEERED AND COMPLETELY **MADE IN ITALY**

A wide-angle photograph of a modern urban plaza at dusk. The plaza is paved with large, light-colored square tiles. Several palm trees are planted in the plaza, their trunks wrapped in vibrant, multi-colored tape (red, yellow, green, blue, and pink). The trees are illuminated from below, casting a warm glow. In the background, there are modern buildings with glass facades and intricate metalwork. One building on the left has a white, textured facade. Another building on the right has a glass facade with a pattern of small, illuminated squares. The sky is a deep blue. The overall atmosphere is modern and artistic.

...if you only could imagine,  
the right light!



We would like to transmit, through the use of our products, our special policy aimed at integrating the style of our articles with their surroundings. In other words, we want to communicate our personal idea of "Light".

Our products derive from our policy aimed at presenting increasingly competitive and better quality articles.

Our greatest wish is to accomplish this policy.

With the expanding market for themed restaurants, bars, shops and shopping centers, the need to specially cater the setting to create an atmosphere attractive to customers is a must.

Now themed environments of all kinds can finally enjoy all the benefits of an intelligent light...

**TUPex**  **Elektriska**

## ALEM 09

Allmänna leveransbestämmelser avseende elektrisk materiel för leverans och användning i Sverige, utarbetade av Elektriska Installatörsorganisationen EIO och Sveriges Elgrossister, SEG.

Leveransbestämmelsen är ej avsedd att tillämpas för leveranser av tjänster, elektriska hushållsapparater, hemelektronik, datorer eller programvaror.

### Inledande bestämmelser och definitioner

1. Om inte annat stadgas nedan, eller i övrigt avtalats mellan parterna, gäller köplagen.
2. Prisbelopp: Prisbelopp enligt lagen om allmän försäkring (1962:381).
3. Köpesumma: Angivet pris exklusive mervärdesskatt för varor som enligt det individuella avtalet skall levereras till ett projekt eller till ett leveransställe.
4. Skriftligen: Information som kan läsas och lagras.
5. Säljaren ska på lämpligt sätt, exempelvis via sin hemsida, hålla köparen informerad om leveransföretag med avvikande svarstider enligt punkt 28.

### Anbud

6. Säljarens anbud gäller en månad, om ej annat anges.
7. Avser säljarens anbud från köparens förfrågan, skall detta tydligt anges i anbudet. I annat fall gäller vad som föreskrivs i förfrågan, om inte osamtygshetens uppenbarligen föranleder annat.

### Handlingar

8. Räkningar och andra handlingar som part överlämnat fördras till dess egendom. Motparten får endast använda, reproducera eller delge tredje man sådan handling, om det förstås för det med handlingens överlämnande avsedda syftet. Härutöver kan följa skyld enligt immateriell lagstiftning eller lagen om skydd för företagshemligheter.
  9. Alla personer som befinner sig på eller levererar till en byggarbetsplats är skyldiga att bära namnplått med arbetsplatsen och arbetsgivare samt ha gällande legitimation tillgänglig, till exempel i form av kort eller ID-kort.
- Om inte annat överenskommit skall säljaren utge vite vid varje påtalat tillfälle som någon av hans anställda eller anställda hos transportörer som ansetts av säljaren bryta mot vad som föreskrivits i föregående stycke. Vite utgår med 500 SEK per person och dag.

### Meddelanden mm

10. Meddelande skall (i ex genom order- eller objektnumret) ange den person eller enhet hos mottagaren som denne uppgivit handlägga leveransen.

### Författningar mm

11. Varan skall uppfylla de krav som vid leveransen gäller enligt lagar och andra författningar samt de föreskrifter och anvisningar som föreskrivs i parternas avtal.
- Ändras sådana bestämmelser efter säljarens anbud skall avtalet ändras i den mån kostnaderna eller leveranstiden påverkas.

### Produktinformation

12. Hänvisas i parternas avtal till katalog eller annan produktinformation, skall varans överensstämmelse med den angivna produktdata. Detsamma gäller om det av osamtygsheterna i avtalet framgår att parterna avsett, att varan skall motsvara data i produktinformationen.

### Produktändringar

13. Säljaren äger, såvida detta ej medför tekniska eller ekonomiska olägenheter för köparen, rätt att leverera varan med ändrade tekniska eller ekonomiska produktändringar. Om efter avtalets ingående företagna produktändringar, äger köparen för köparens sådana olägenheter upprätt, äger köparen häva avtalet skrivit avseende ändrad varan samt vara som står i sådant samband med den ändrade varan, att den måste anses utgöra en del av.

Säljaren är skyldig att ersätta köparen uppkommen skada endast om säljaren vid avtalets ingående insatt eller bortsett att ändringen kunde vålla sådana olägenheter som ovan sägs.

Ersättningskyldigheten enligt denna punkt är begränsad till köpesumman.

### Prover

14. Prov är att betrakta som typprov, om reglement överensstämmer ej avtalats.

Om till ersättning för ersättningskyldighet eller annat ansvar i utövning av åtagande med leveransen.

Läs mer på vår hemsida : [www.tupex.se](http://www.tupex.se)



Experienced products,  
reliability and know-how

When you get a Tupex Elektriska original product,  
you don't only buy an object.

LONG LIFE WARRANTY  
**5**  
**YEARS**  
YEAR

All articles have been tested by EN 60529 european norm. More than this, mechanical tests have been carried out by European or Italian Certified Institutes and results are available on request.

Mechanical test: 1.000 Kg, 5.000 Kg and 10.000 Kg resistance are carried out by TÜV Certified Institute in Italy.

Shock resistance tests. IK rating (CEI EN 50102 norms). Results available on request.

Water resistance test (IEC 529 norm) IP protective degree rating. Results available on request.

Salt spray (saline fog) Testing and Corrosion Test are regularly carried on most of the products UNI ISO 9227. Results available on request.

Routine Tests are carried on in partnership with sub-contractors or inside Puk manufacturing area.

Eulumdat Photometrics on all products are available on request.

5 years LONG LIFE warranty is valid for all articles.

After-sale assistance by our Export Dpt.

# Legend



## FLOODLIGHTS

	101100 HYDROFLASH	page. <b>12</b>
	109000 HYDROBOOK	page. <b>19</b>
	101000 HYDROCASE	page. <b>22</b>
	101200 HYDROCITY WALL	page. <b>32</b>
	103000 HYDROSTAR	page. <b>34</b>
	104000 HYDRODAN	page. <b>46</b>
	105000 HYDROSCAPE	page. <b>49</b>
	106000 HYDROSKY	page. <b>50</b>
	107000 HYDROJET	page. <b>54</b>
	108000 HYDROLASER	page. <b>58</b>



## IN-GROUND

	201000 HYDROFLOOR	page. <b>66</b>
	202000 HYDROQUADRO	page. <b>98</b>
	205000 HYDROFLOOR VETRO	page. <b>105</b>
	203000 HYDROLINE	page. <b>108</b>
	204000 HYDROLINE VETRO	page. <b>110</b>



## UNDERWATER

	301000 HYDROSCUBA	page. <b>119</b>
	303000 HYDROPOOL	page. <b>124</b>
	305000 HYDRODIVE	page. <b>128</b>



## WALL-MOUNTING

	401100 HYDROWAVE	page. <b>134</b>
	401000 HYDROTECH	page. <b>136</b>
	401900 HYDROTECH STEEL	page. <b>152</b>
	401700 HYDROECLIPSE	page. <b>158</b>
	401600 HYDROSURF	page. <b>172</b>
	401800 HYDROFLEX	page. <b>182</b>
	402000 HYDROBRACKET	page. <b>190</b>
	403000 HYDROLINE-B	page. <b>201</b>



## WALL-MOUNTING

	404000 HYDROSPLIT	page. <b>203</b>
	405000 HYDROLED	page. <b>209</b>
	401400 HYDROMASK	page. <b>212</b>
	406000 HYDROTARGET	page. <b>216</b>
	401300 HYDRODISK	page. <b>220</b>



## WALL-RECESSED

	501000 HYDROBLADE	page. <b>226</b>
	502000 HYDROSTEP	page. <b>227</b>



## BOLLARDS

	609001 HYDROBOULEVARD	page. <b>238</b>
	608001 HYDROSURF BOLLARD	page. <b>244</b>
	601000 HYDROPHARO	page. <b>246</b>
	603000 HYDROWAY	page. <b>252</b>
	604000 HYDROLANE	page. <b>259</b>
	605000 HYDROSIDE	page. <b>262</b>
	606000 HYDROPLATE	page. <b>262</b>
	601200 HYDROSTICK	page. <b>263</b>
	601100 HYDROSWING	page. <b>264</b>



## DOWNLIGHTS

	701000 HYDROCEILING	page. <b>268</b>
	706000 HYDROTECH 03	page. <b>273</b>
	707000 HYDROTECH 03 STEEL	page. <b>276</b>
	702000 HYDROSPOT	page. <b>277</b>
	704000 ID SERIES	page. <b>279</b>
	705000 OYSTER	page. <b>280</b>



## URBAN LIGHTS

	802000 HYDROCITY	page. <b>284</b>
	803000 HYDROBOOK POLE-TOP	page. <b>298</b>
	804000 HYDROTECH POLE-TOP	page. <b>306</b>
	805000 HYDROFLASH POLE-TOP	page. <b>310</b>
	809900 POLES & ACCESSORIES	page. <b>332</b>







# Floodlights



101100 HYDROFLASH

page. **12**



109000 HYDROBOOK

page. **19**



101000 HYDROCASE

page. **22**



101200 HYDROCITY WALL

page. **32**



103000 HYDROSTAR

page. **34**



104000 HYDRODAN

page. **46**



105000 HYDROSCAPE

page. **49**



106000 HYDROSKY

page. **50**



107000 HYDROJET

page. **54**



108000 HYDROLASER

page. **58**

## 101101 HYDROFLASH MEDIUM LED

Round floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 high-power LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- NR. 5 CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 1 mt. neoprene power cable included



**1...10 V** **DALI**  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST


**Full RGB**  
AVAILABLE ON REQUEST




GRADUATED STAINLESS STEEL INSERT



AC-026 - ANTI-GLARE VISOR  
FOR HYDROFLASH MEDIUM



Ø140mm




242mm

Ø140mm

8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65 -   
2,60 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	720	90.00	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)
		30°	684	85.50	
		45°	650	81.25	
	4.000°K NEUTRAL-WHITE	10°	750	93.75	
		30°	713	89.13	
		45°	677	84.63	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE



## 101102 HYDROFLASH MEDIUM COB LED

Round floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 CREE CXA 1512 COB LED. IP65 rating.

### Energy Label **A++**


- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 CREE CXA 1512 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 1 mt. neoprene power cable included




GRADUATED STAINLESS STEEL INSERT



AC-026 - ANTI-GLARE VISOR FOR HYDROFLASH MEDIUM



Ø140mm



242mm

Ø140mm

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
18 WATT 220-240V 50-60HZ ELECTRONIC IP65 2,60 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	35°	1.530	85.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>



## 101103 HYDROFLASH MAXI LED

Round floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-G3 high-power LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 1 mt. neoprene power cable included



**1...10 V** **DALI**  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST


**Full RGB**  
AVAILABLE ON REQUEST




GRADUATED STAINLESS STEEL INSERT



AC-027 - ANTI-GLARE VISOR  
FOR HYDROFLASH MEDIUM



Ø198mm



277mm

Ø198mm

18 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
3,50 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	1.152	96.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		30°	1.095	91.25	
		45°	1.040	86.67	
	4.000°K NEUTRAL-WHITE	10°	1.200	100.00	
		30°	1.140	95.00	
		45°	1.083	90.25	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE



## 101104 HYDROFLASH MAXI COB LED

Round floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 CREE CXB 2530 COB LED. IP65 rating.

### Energy Label **A++**


- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 CREE CXB 2530 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 1 mt. neoprene power cable included




GRADUATED STAINLESS STEEL INSERT



AC-027 - ANTI-GLARE VISOR FOR HYDROFLASH MEDIUM



Ø198mm



277mm

Ø198mm

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
36 WATT 220-240V 50-60HZ ELECTRONIC IP65 3,50 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	35°	3.100	86.10	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>



## 109001 HYDROBOOK MEDIUM LED





Square floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-G3 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG9
- 1 mt. neoprene power cable included



SHORT FIXING BRACKET



12 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
2,50 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	1.152	96.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		30°	1.095	91.25	
		45°	1.040	86.67	
	4.000°K NEUTRAL-WHITE	10°	1.200	100.00	
		30°	1.140	95.00	
		45°	1.083	90.25	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ● BLUE






## 109002 HYDROBOOK MAXI LED

Square floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 20 CREE XP-G3 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- NR. 20 CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG9
- 1 mt. neoprene power cable included



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	2.880	96.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		30°	2.736	91.20	
		45°	2.600	86.67	
	4.000°K NEUTRAL-WHITE	10°	3.000	100.00	
		30°	2.850	95.00	
		45°	2.708	90.26	

30 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
2,80 KG UNIT GROSS WEIGHT

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ● BLUE -

101001 HYDROCASE MICRO LED

Square small floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 1 CREE XP-G3 LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 1W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Nickel-plated brass cable gland PG9
- 1 mt. neoprene power cable included



101002 - WITH EXTENDED FIXING BRACKET OPTION



AC022 - IP65 WALL-BASE WITH BRACKET OPTION




AC001 - HEARTH SPIKE

1 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
0.55 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	115	115.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		30°	110	110.00	
		45°	104	104.00	
	4.000°K NEUTRAL-WHITE	10°	120	120.00	
		30°	114	114.00	
		45°	109	109.00	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: 4.000°K NEUTRAL-WHITE, BLUE



## 101003 HYDROCASE MINI LED

Square small floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 3 CREE XP-G3 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 3 x 1W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Nickel-plated brass cable gland PG9
- 1 mt. neoprene power cable included




101004 - WITH EXTENDED FIXING BRACKET OPTION



AC022 - IP65 WALL-BASE WITH BRACKET OPTION



AC001 - HEARTH SPIKE



3 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
0.80 KG UNIT GROSS WEIGHT


LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	346	115.33	TEXTURED GREY
		30°	329	109.66	
		45°	312	104.00	MATT WHITE (ON REQUEST)
	4.000°K NEUTRAL-WHITE	10°	360	120.00	
		30°	342	114.00	
		45°	325	108.33	MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE

101012M HYDROCASE MINI GU10

Square small floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. GU10 LED / halogen. IP65 rating.


- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- GU10 base, MAX 50W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Nickel-plated brass cable gland PG9
- 1 meter power cable included




WITH EXTENDED FIXING BRACKET  
OPTION  
101004 - LED  
101013M - GU 10



AC001  
HEARTH SPIKE



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
50 WATT MAX 220-240V 50-60HZ IP65 0.80 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	<div><div></div> TEXTURED GREY</div> <div><div></div> MATT WHITE (ON REQUEST)</div> <div><div></div> MATT BLACK (ON REQUEST)</div>

## 101006 HYDROCASE MEDIUM LED

Square floodlight for outdoor installation on a façade/wall.

Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 1 mt. neoprene power cable included

**1...10 V** **DALI**  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST

**Full RGB**  
AVAILABLE ON REQUEST



**SHORT FIXING BRACKET**  
**BOTH INCLUDED IN THE STANDARD PACKAGE**




**MEDIUM FIXING BRACKET**

**101007 - EXTENDED FIXING BRACKET - OPTION**



**AC022 - IP65 WALL-BASE WITH BRACKET OPTION**



8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
2,00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	M 10°	720	90.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		M 30°	684	85.50	
		M 45°	650	81.25	
	4.000°K NEUTRAL-WHITE	M 10°	750	93.75	
		M 30°	713	89.13	
		M 45°	677	84.63	

101008 HYDROCASE MAXI LED

Square floodlight for outdoor installation on a façade/wall.  
Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-G3 LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 1 mt. neoprene power cable included

1...10 V

DALI

1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST

FullRGB

AVAILABLE ON REQUEST




SHORT FIXING BRACKET

BOTH INCLUDED IN THE STANDARD PACKAGE

MEDIUM FIXING BRACKET

101009 - EXTENDED FIXING BRACKET - OPTION

AC022 - IP65 WALL-BASE WITH BRACKET OPTION



12 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
5,00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	1.152	96.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		30°	1.095	91.25	
		45°	1.040	86.67	
	4.000°K NEUTRAL-WHITE	10°	1.200	100.00	
		30°	1.140	95.00	
		45°	1.083	90.25	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: 4.000°K NEUTRAL-WHITE, BLUE

## 101014 HYDROCASE MAXI-20 LED

Square floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 20 CREE XP-G3 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 20 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 1 mt. neoprene power cable included



**1...10 V** **DALI**  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST

**FullRGB**  
AVAILABLE ON REQUEST






**SHORT FIXING BRACKET**  
**BOTH INCLUDED IN THE STANDARD PACKAGE**

**MEDIUM FIXING BRACKET**

**101009 - EXTENDED FIXING BRACKET - OPTION**

**AC022 - IP65 WALL-BASE WITH BRACKET OPTION**



30 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
5,50 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	2.880	96.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		30°	2.736	91.20	
		45°	2.600	86.67	
	4.000°K NEUTRAL-WHITE	10°	3.000	100.00	
		30°	2.850	95.00	
		45°	2.708	90.26	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE





## 101016 HYDROCASE MAXI-20 PRO LED




Square floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 20 CREE XP-L LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 20 CREE "XP-L" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 1 mt. neoprene power cable included



101009 - EXTENDED FIXING BRACKET - OPTION





	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
50 WATT 220-240V 50-60HZ ELECTRONIC IP65 5.2 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	10°	4.900	98.00	TEXTURED GREY
			30°	4.650	93.00	MATT WHITE (ON REQUEST)
			45°	4.420	88.40	MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE



101010 HYDROCASE MAXI G12

Square floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in ballast 220V 50Hz, G12 35W or 70W metal halide. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT CRI 35W G12 or HIT CRI 70W G12
- Conventional ballast 230V 50Hz
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Nickel-plated brass cable gland PG11



BOTH INCLUDED IN THE STANDARD PACKAGE



244 mm

378 mm

128 mm

35 WATT | 70 WATT  
HIT-CRI – BASE G12  
230V 50HZ  
IP65  
5.20 KG UNIT GROSS WEIGHT

LIGHT SOURCE

LIGHT COLOR

LIGHT BEAM OPTIONS

COLORS OPTIONS



SEE BULB FEATURES

- 4° SUPER-NARROW (ON REQUEST)
- 10° NARROW
- 23° FLOOD (ON REQUEST)

- TEXTURED GREY
- MATT WHITE (ON REQUEST)
- MATT BLACK (ON REQUEST)




## 101201 HYDROCITY WALL 12+12 LED



Round wall mounted luminaire for outdoor installation, with downward asymmetric light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws Built-in LED driver/s, with 24 CREE XP-G3 LED. IP66 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 24 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



36 WATT  
220-240V 50-60HZ ELECTRONIC  
IP66  
6,50 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	CYCLE ROUTE PEDESTRIAN	3.456	96.00	<div> <div></div> TEXTURED GREY                 <div></div> MATT WHITE (ON REQUEST)                 <div></div> MATT BLACK (ON REQUEST)             </div>
		STREET			






**101202 HYDROCITY WALL 24+24 LED**

**NEW**

Round wall mounted luminaire for outdoor installation, with downward asymmetric light distribution. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws Built-in LED driver/s, with 48 CREE XP-G3 LED. IP66 rating.

**Energy Label A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 48 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
72 WATT 220-240V 50-60HZ ELECTRONIC IP66 6,70 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	<div>  CYCLE ROUTE PEDESTRIAN </div> <div>  STREET </div>	6.912	96.00	<div>  TEXTURED GREY </div> <div>  MATT WHITE (ON REQUEST) </div> <div>  MATT BLACK (ON REQUEST) </div>

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE

103001M HYDROSTAR MINI 01 GU5.3

Small projector for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and base, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in transformer 220-240V 50-60Hz, GU5.3 LED / halogen. IP55 rating.


- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- GU5.3 base, MAX 50W
- Built-in toroidal transformer 220-240V 50-60Hz
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.




BLACK VERSION



KEMPINSKY HOTEL, GOLD COAST CITY, ACCRA, GHANA



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
50 WATT MAX – BASE GU5.3 220-240V 50-60HZ IP55 1.65 KG UNIT GROSS WEIGHT	 GU5.3 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	<div><div></div> TEXTURED GREY</div> <div><div></div> MATT WHITE (ON REQUEST)</div> <div><div></div> MATT BLACK (ON REQUEST)</div>


## 103002M HYDROSTAR MINI 02 GU5.3


Small projector for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and base, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in transformer 220-240V 50-60Hz, GU5.3 LED / halogen. IP55 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- GU5.3 base, MAX 50W
- Built-in toroidal transformer 220-240V 50-60Hz
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.



BLACK VERSION



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
50 WATT MAX – BASE GU5.3 220-240V 50-60HZ IP55 3.15 KG UNIT GROSS WEIGHT	 GU5.3 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	<div> <div></div> TEXTURED GREY           <div></div> MATT WHITE (ON REQUEST)           <div></div> MATT BLACK (ON REQUEST)         </div>

103003M HYDROSTAR MINI 01 GU10

Small projector for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and base, tempered safety glass, moulded silicone gasket and stainless steel screws. GU10 LED / halogen. IP55 rating.



- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- GU10 base, MAX 50W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.




BLACK VERSION



AC001  
EARTH SPIKE  
ON REQUEST





	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
50 WATT MAX 220-240V 50-60HZ IP55 0.75 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	<div><div></div> TEXTURED GREY</div> <div><div></div> MATT WHITE (ON REQUEST)</div> <div><div></div> MATT BLACK (ON REQUEST)</div>

103004M HYDROSTAR MINI 02 GU10

Small projector for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and base, tempered safety glass, moulded silicone gasket and stainless steel screws. GU10 LED / halogen. IP55 rating.

- Material: high corrosion resistance ie-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- GU10 base, MAX 50W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
50 WATT MAX 220-240V 50-60HZ IP55 2.20 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	<div><div></div> TEXTURED GREY</div> <div><div></div> MATT WHITE (ON REQUEST)</div> <div><div></div> MATT BLACK (ON REQUEST)</div>

103005 HYDROSTAR MEDIUM 01 LED


Projector for outdoor installation on a façade/ wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and base, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.

1...10 V DALI  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST

FullRGB  
AVAILABLE ON REQUEST



8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
3.30 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	720	90.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		30°	684	85.50	
		45°	650	81.25	
	4.000°K NEUTRAL-WHITE	10°	750	93.75	
		30°	713	89.13	
		45°	677	84.63	


\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: 4.000°K NEUTRAL-WHITE, BLUE

## 103011 HYDROSTAR MEDIUM 02 LED

Projector for outdoor installation on a façade/ wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and base, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- NR. 5 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.



8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
3.50 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	720	90.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		30°	684	85.50	
		45°	650	81.25	
	4.000°K NEUTRAL-WHITE	10°	750	93.75	
		30°	713	89.13	
		45°	677	84.63	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE

103006S HYDROSTAR MEDIUM 01 G8.5

Projector for outdoor installation on a façade/ wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and base, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in electronic ballast 220-240V 50-60Hz, G8.5 35W metal halide. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT-TC CRI G8.5 35W
- Built-in electronic ballast 220/240V 50/60Hz
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.




AC001  
EARTH SPIKE  
ON REQUEST








MOVABLE  
35°



MOVABLE  
100°



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT 220-240V 50-60HZ ELECTRONIC IP65 3.30 KG UNIT GROSS WEIGHT	 HIT-TC CRI 35W G8.5	SEE BULB FEATURES	 45° FLOOD	 TEXTURED GREY  MATT WHITE (ON REQUEST)  MATT BLACK (ON REQUEST)



**MARSA MALAZ KEMPINSKI HOTEL**

Location: The Pearl, Doha, Qatar




**103005**  
**Hydrostar Medium 01 LED**








103007S HYDROSTAR MEDIUM 02 G8.5

Projector for outdoor installation on a façade/ wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and base, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in electronic ballast 220-240V 50-60Hz, G8.5 35W metal halide. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT-TC CRI G8.5 35W
- Built-in electronic ballast 220/240V 50/60Hz
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT 220-240V 50-60HZ ELECTRONIC IP65 3.90 KG UNIT GROSS WEIGHT	 HIT-TC CRI 35W G8.5	SEE BULB FEATURES	 45° FLOOD	 TEXTURED GREY  MATT WHITE (ON REQUEST)  MATT BLACK (ON REQUEST)

## 103009 HYDROSTAR MAXI LED

Projector for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and base, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-G3 LED. IP65 rating.


### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11

**1...10 V** **DALI**

1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST

**FullRGB**  
AVAILABLE ON REQUEST



### HYDROSTAR RANGE

12 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
5.00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	1.152	96.00	TEXTURED GREY
		30°	1.095	91.25	
		45°	1.040	86.67	MATT WHITE (ON REQUEST)
	4.000°K NEUTRAL-WHITE	10°	1.200	100.00	
		30°	1.140	95.00	
		45°	1.083	90.25	MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE

103010 HYDROSTAR MAXI G12

Projector for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and base, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in ballast 230V 50Hz, G12 35W or 70W metal halide. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- HIT CRI 35W G12 or HIT CRI 70W G12
- Conventional ballast 230V 50Hz
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.




DARK-LIGHT ATTACHMENT (ACCESSORY)










SUPERSPOT 4° REFLECTOR (OPTION)

FLOOD 23° REFLECTOR (OPTION)



35 WATT | 70 WATT  
HIT-CRI – BASE G12  
230V 50HZ  
IP65  
5.00 KG UNIT GROSS WEIGHT


LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
 HIT-CRI – BASE G12	SEE BULB FEATURES	 4° SUPER-NARROW (ON REQUEST)	 TEXTURED GREY
		 10° NARROW	 MATT WHITE (ON REQUEST)
		 23° FLOOD (ON REQUEST)	 MATT BLACK (ON REQUEST)

## 104003 HYDRODAN LED

Floodlight for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in ballast 220-240V 50-60Hz, with 48 CREE XP-E LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 48 x 2W CREE "XP-E" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
100 WATT 220-240V 50-60HZ ELECTRONIC IP65 5.20 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	M 30°	5.200	52.00	TEXTURED GREY

104004 HYDRODAN LED ASYMMETRIC

Floodlight for outdoor installation on a façade/wall. Asymmetric light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in ballast 220-240V 50-60Hz, with 30 CREE XP-E LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 30 x 2W CREE "XP-E" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
60 WATT 220-240V 50-60HZ ELECTRONIC IP65 4,70 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	120° X 70°	3.300	55.00	TEXTURED GREY



105003 HYDROSCAPE LED

Slim rectangular floodlight for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 15 CREE XP-G3 LED. IP65 rating.

Energy Label A++


- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 15 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double M20 cable gland.
- 1 mt. neoprene power cable included




1...10 V DALI  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST  
Full RGB  
AVAILABLE ON REQUEST



WATER DRAINAGE




PANCHO ARENA, FELCSUT, HUNGARY



AC003: WALL EXTENSIBLE BRACKET  
DIE-CAST ALUMINUM  
(OPTION TO BE ORDERED SEPARATELY)

22 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
3.80 KG UNIT GROSS WEIGHT



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	2.160	98.18	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		30°	2.052	93.28	
		45°	1.950	88.64	
	4.000°K NEUTRAL-WHITE	10°	2.250	102.27	
		30°	2.138	97.18	
		45°	2.031	92.32	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

## 106001 HYDROSKY MINI LED

Projector for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, base and anti-glare visor, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 3 CREE XP-E LED. IP66 rating.



### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 3 x 2W CREE "XP-E" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Anti-glare visor.
- 1 mt. neoprene power cable included



## 106002

### HYDROSKY MINI LED EARTH SPIKE



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
6 WATT 220-240V 50-60HZ ELECTRONIC IP66 1,50 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	30°	350	58.33	TEXTURED GREY

106003 HYDROSKY MEDIUM LED


Projector for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, base and anti-glare visor, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 9 CREE XP-E LED. IP66 rating.




Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- NR. 9 CREE "XP-E" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Anti-glare visor.
- 1 mt. neoprene power cable included



106004 HYDROSKY MEDIUM LED EARTH SPIKE



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
11 WATT 220-240V 50-60HZ ELECTRONIC IP66 2.20 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 30°	1.000	90.91	 TEXTURED GREY

## 106005 HYDROSKY MAXI LED

Projector for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, base and anti-glare visor, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 18 CREE XP-E LED. IP66 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 18 CREE "XP-E" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Anti-glare visor.
- 1 mt. neoprene power cable included




## 106006

### HYDROSKY MAXI LED EARTH SPIKE



AC-023  
FLANGE FOR POLE MOUNTING  
(POLE DIAMETER 120 MM)




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
21 WATT 220-240V 50-60HZ ELECTRONIC IP66 3.20 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	30°	2.400	114.28	TEXTURED GREY

106007 HYDROSKY MEGA LED




Projector for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and base, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 36 CREE XP-E LED. IP66 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 36 CREE "XP-E" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Anti-glare visor.
- 1 mt. neoprene power cable included



AC-023  
FLANGE FOR POLE MOUNTING  
(POLE DIAMETER 120 MM)

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
60 WATT 220-240V 50-60HZ ELECTRONIC IP66 5.20 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 30°	5.000	83.34	 TEXTURED GREY

## 107002 HYDROJET MICRO LED

Spike projector for outdoor installation through earth spike. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 1 CREE XB-D LED. IP66 rating.



### Energy Label **A++**




- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 2W CREE "XB-D" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included



## 107001

### HYDROJET MICRO LED MOUNTING BASE



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2 WATT 220-240V 50-60HZ ELECTRONIC IP66 0,60 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 30°	139	69.50	 TEXTURED GREY



## 107004 HYDROJET MINI LED

Spike projector for outdoor installation through earth spike. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 1 CREE CXA 1304 COB LED. IP66 rating.



### Energy Label A++




- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 6W COB CREE "CXA 1304" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included



## 107003

### HYDROJET MINI LED MOUNTING BASE



6 WATT 220-240V 50-60HZ ELECTRONIC IP66 0,70 KG UNIT GROSS WEIGHT	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
	COB LED	 3.000°K WARM-WHITE	 30°	492	82.00	 TEXTURED GREY

107006 HYDROJET MEDIUM LED



Spike projector for outdoor installation through earth spike. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 1 CREE CXA 1507 COB LED. IP66 rating.




Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 12W COB CREE "CXA 1507" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included



107005 HYDROJET MEDIUM LED MOUNTING BASE





	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
12 WATT 220-240V 50-60HZ ELECTRONIC IP66 1,40 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 30°	898	74.90	 TEXTURED GREY

## 108001 HYDROLASER MICRO LED

Skyscraper projector for outdoor installation to wall wash a building façade. Anodized extruded aluminium body, phospho-chromatised and polyester powder coated die-cast copper-free aluminium closing caps, tempered safety glass, moulded silicone gasket and stainless steel screws. 24V DC remote driver needed, with 2 CREE LED. IP67 rating.

### Energy Label **A++**

- Material: high corrosion resistance anodized extruded aluminum body, die-cast copper-free aluminum closing caps.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 2W CREE LED
- 24V DC
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.5 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
6 WATT 24V DC REMOTE DRIVER NEEDED IP66 0,80 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	5°	400	66.67	SILVER

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	MIN 1 - MAX 3
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 - MAX 5
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 9





## 108002 HYDROLASER MINI LED

Skyscraper projector for outdoor installation to wall wash a building façade. Anodized extruded aluminium body, phospho-chromatised and polyester powder coated die-cast copper-free aluminium closing caps, tempered safety glass, moulded silicone gasket and stainless steel screws. 24V DC remote driver needed, with 3 CREE LED. IP66 rating.

### Energy Label **A++**

- Material: high corrosion resistance anodized extruded aluminum body, die-cast copper-free aluminum closing caps.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 3 x 2W CREE LED
- 24V DC
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.5 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 24V DC REMOTE DRIVER NEEDED IP66 1,10 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	5°	600	60.00	SILVER



REMOTE DRIVER SELECTION						
BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES	
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	MIN 1 - MAX 2	
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 - MAX 3	
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 5	




108003    HYDROLASER MEDIUM LED

Skyscraper projector for outdoor installation to wall wash a building façade. Anodized extruded aluminium body, phospho-chromatised and polyester powder coated die-cast copper-free aluminium closing caps, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 6 CREE LED. IP66 rating.

Energy Label    A++

- Material: high corrosion resistance anodized extruded aluminum body, die-cast copper-free aluminum closing caps.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 6 x 2W CREE LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.5 mt. neoprene power cable included






	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
18 WATT 220-240V 50-60HZ ELECTRONIC IP66 1,70 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 5°	1.200	66.67	 SILVER

**108004 HYDROLASER MAXI LED**

Skyscraper projector for outdoor installation to wall wash a building façade. Anodized extruded aluminium body, phospho-chromatised and polyester powder coated die-cast copper-free aluminium closing caps, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 24 CREE LED. IP66 rating.

**Energy Label** **A++**

- Material: high corrosion resistance anodized extruded aluminum body, die-cast copper-free aluminum closing caps.
- Coating: polyester powder coating with phosphocromating pre-finish
- NR. 24 x 2W CREE LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.5 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
55 WATT 220-240V 50-60HZ ELECTRONIC IP66 4,60 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	5°	4.800	87.27	SILVER







## In Ground



201000 HYDROFLOOR

page. **66**



202000 HYDROQUADRO

page. **98**



205000 HYDROFLOOR VETRO

page. **105**



203000 HYDROLINE

page. **108**



204000 HYDROLINE VETRO



page. **110**

## 201001 HYDROFLOOR PICO LED

Round ground-recessed luminaire for outdoor installation, stainless steel AISI316 body and frame, tempered safety glass, moulded silicone gasket. With 1 CREE LED. 24V DC remote driver needed. IP67 rating.

### Energy Label **A++**

- Completely made in stainless steel AISI 316 body
- NR. 1 x 1W CREE "XP-G3" LED
- Silicone rubber gasket
- Tempered safety glass.
- Polypropilene recessing box included.
- 1 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
1 WATT 24V DC REMOTE DRIVER NEEDED IP67 0.30 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	M 25°	96	96.00	STAINLESS STEEL
		6.000°K COLD-WHITE	M 25°	100	100.00	

### REMOTE DRIVER SELECTION



BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	MIN 1 - MAX 9
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 - MAX 14
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 25
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 - MAX 42

## 201060 HYDROFLOOR PICO SOFT LED

Round ground-recessed luminaire for outdoor installation, stainless steel AISI316 body and frame, tempered frosted safety glass diffuser, moulded silicone gasket. With 6 x SMD LED. 24V DC remote driver needed. IP67 rating.

### Energy Label **A++**

- Material: stainless steel AISI 316
- NR. 6 x SMD LED
- Frosted glass
- 0.8W – 24V DC
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
0.8 WATT 24V DC REMOTE DRIVER NEEDED IP67 0.30 KG UNIT GROSS WEIGHT	SMD LED	3.000°K WARM-WHITE	75°	64	80.00	STAINLESS STEEL

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	MIN 1 - MAX 4
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 - MAX 6
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 12





## 201002 HYDROFLOOR SMALL LED

Round ground-recessed luminaire for outdoor installation, stainless steel AISI316 body and frame, tempered safety glass, moulded silicone gasket. With 3 CREE LED. 24V DC remote driver needed. IP67 rating.

### Energy Label **A++**

- Completely made in stainless steel AISI 316 body
- NR. 3 x 1W CREE "XP-G3" LED
- Silicone rubber gasket
- Tempered safety glass.
- Polypropylene recessing box included.
- 1 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
3 WATT 24V DC REMOTE DRIVER NEEDED IP67 0.60 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	25°	288	96.00	STAINLESS STEEL
		6.000°K COLD-WHITE	25°	300	100.00	

### REMOTE DRIVER SELECTION



BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	MIN 1 - MAX 4
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 - MAX 5
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 9
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 - MAX 15

## 201061 HYDROFLOOR SMALL SOFT LED

Round ground-recessed luminaire for outdoor installation, stainless steel AISI316 body and frame, tempered frosted safety glass diffuser, moulded silicone gasket. With 12 x SMD LED. Built-in LED driver 220-240V 50-60Hz. IP67 rating.

### Energy Label **A++**

- Material: stainless steel AISI 316
- NR. 12 x SMD LED
- Frosted glass
- 1.5W – 220-240V 50-60Hz
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included





	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
1.5 WATT 220-240V 50-60HZ ELECTRONIC IP67 0.60 KG UNIT GROSS WEIGHT	SMD LED	3.000°K WARM-WHITE	80°	76	50.67	STAINLESS STEEL

201003 HYDROFLOOR MICRO PERFORMANCE LED

Round ground-recessed luminaire for outdoor installation, Phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 1 CREE XP-G3 LED. IP67 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 ring.
- NR. 1 x 1W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 1.000 Kg
- Protection against impact IK09 (10 joule)
- Cable gland PG9
- Polypropilene recessing box included.
- 1 mt. neoprene power cable included



1 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
0.70 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	M 10°	115	115.00	STAINLESS STEEL
		M 30°	110	110.00	
		M 45°	104	104.00	
	4.000°K NEUTRAL-WHITE	M 10°	120	120.00	
		M 30°	114	114.00	
		M 45°	109	109.00	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

## 201005P HYDROFLOOR MICRO GU4




201004P




201005P



Round ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. G4 20W LED / halogen. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 ring.
- GU4 base, MAX 20W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 1.000 Kg
- Protection against impact IK09 (10 joule)
- Cable gland PG9
- Polypropylene recessing box included.
- 1 mt. neoprene power cable included



MAX 1.000 kg



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20 WATT MAX 12V IP67 0.70 KG UNIT GROSS WEIGHT	 GU4 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	 STAINLESS STEEL


## 201065 HYDROFLOOR MICRO STEEL 01 LED




**NEW**

Round ground-recessed drive-over luminaire for outdoor installation, top cover with one way 1x90° light emission. Body and top cover completely realized in stainless steel AISI 304, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 1 CREE XP-E2 LED. IP67 rating.

### Energy Label **A++**

- Material: stainless steel AISI 304
- NR. 1 CREE "XP-E2" LED
- Electronic transformer 220/240V 50/60Hz included
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 2000 Kg
- Polypropylene recessing box included.
- M12 cable gland
- 1 mt. neoprene power cable included




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
3 WATT 220-240V 50-60HZ ELECTRONIC IP67 1,00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 1X90°	150	50.00	 STAINLESS STEEL



## 201066 HYDROFLOOR MICRO STEEL 02 LED



Round ground-recessed drive-over luminaire for outdoor installation, top cover with two ways 2x90° light emission. Body and top cover completely realized in stainless steel AISI 304, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 2 CREE XP-E2 LED. IP67 rating.



### Energy Label **A++**


- Material: stainless steel AISI 304
- NR. 2 CREE "XP-E2" LED
- Electronic transformer 220/240V 50/60Hz included
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 2000 Kg
- Polypropilene recessing box included.
- M12 cable gland
- 1 mt. neoprene power cable included

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
5 WATT 220-240V 50-60HZ ELECTRONIC IP67 1,00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	2X90°	250	50.00	STAINLESS STEEL

## 201067 HYDROFLOOR MICRO STEEL 04 LED



Round ground-recessed drive-over luminaire for outdoor installation, top cover with two ways 4x70° light emission. Body and top cover completely realized in stainless steel AISI 304, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 4 CREE XP-E2 LED. IP67 rating.



### Energy Label **A++**



- Material: stainless steel AISI 304
- NR. 4 CREE "XP-E2" LED
- Electronic transformer 220/240V 50/60Hz included
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 2000 Kg
- Polypropilene recessing box included.
- M12 cable gland
- 1 mt. neoprene power cable included




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
6 WATT 220-240V 50-60HZ ELECTRONIC IP67 1,00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	4X70°	400	66.67	STAINLESS STEEL

201006P HYDROFLOOR MICRO 01 GU4

Round ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and protective cover, tempered safety glass, moulded silicone gasket. G4 20W LED / halogen. IP67 rating

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- GU4 base, MAX 20W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 1.000 Kg
- Protection against impact IK09 (10 joule)
- Cable gland PG9
- Polypropilene recessing box included.
- 1 mt. neoprene power cable included








	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20 WATT MAX 12V IP67 0.60 KG UNIT GROSS WEIGHT	 GU4 LED / HALOGEN	SEE BULB FEATURES		 TEXTURED-GREY

201007P HYDROFLOOR MICRO 02 GU4

Round ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and protective cover, tempered safety glass, moulded silicone gasket. G4 20W LED / halogen. IP67 rating

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- GU4 base, MAX 20W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 1.000 Kg
- Protection against impact IK09 (10 joule)
- Cable gland PG9
- Polypropilene recessing box included.
- 1 mt. neoprene power cable included








	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20 WATT MAX 12V IP67 0.60 KG UNIT GROSS WEIGHT	 GU4 LED / HALOGEN	SEE BULB FEATURES		 TEXTURED-GREY

## 201008P HYDROFLOOR MICRO 04 GU4

Round ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and protective cover, tempered safety glass, moulded silicone gasket. G4 20W LED / halogen. IP67 rating

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- GU4 base, MAX 20W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 1.000 Kg
- Protection against impact IK09 (10 joule)
- Cable gland PG9
- Polypropilene recessing box included.
- 1 mt. neoprene power cable included



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20 WATT MAX 12V IP67 0.60 KG UNIT GROSS WEIGHT	 GU4 LED / HALOGEN	SEE BULB FEATURES		 TEXTURED-GREY

## 201010P HYDROFLOOR COMPACT ROUND GU10





201009P





201010P

Round compact ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. GU10 LED / halogen. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 ring.
- GU10 base, MAX 35W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Fully frosted glass available on request.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- Double PG11 cable gland.
- Polypropilene recessing box included.
- 1 mt. neoprene power cable included



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT MAX 220-240V 50-60HZ IP67 1.30 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	 STAINLESS STEEL

201012 HYDROFLOOR MINI PERFORMANCE LED

Round ground-recessed luminaire for outdoor installation, Phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 3 CREE XP-G3 LED. IP67 rating.

Energy Label A++



- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 ring.
- NR. 3 x 1W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- M20 cable gland.
- Adjustable +/- 15 degrees.
- Polypropylene recessing box included.
- 3 mt. neoprene power cable included



**Full RGB**  
AVAILABLE ON REQUEST



BELLAGIO VILLAGE, OLIVETO LARIO, ITALY



3 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
1.25 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	346	115.33	STAINLESS STEEL
		30°	329	109.66	
		45°	312	104.00	
	4.000°K NEUTRAL-WHITE	10°	360	120.00	
		30°	342	114.00	
		45°	325	108.33	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

## 201014P HYDROFLOOR MINI ROUND GU5.3




201013P




201014P



Round ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. GU5.3 LED / halogen. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 ring.
- GU5.3 base, MAX 35W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Fully frosted glass available on request.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- Adjustable +/- 15 degrees.
- M20 cable gland.
- Polypropylene recessing box included.



201015P HYDROFLOOR COMPACT SQUARE GU5.3



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT MAX 12V IP67 1.20 KG UNIT GROSS WEIGHT	 GU5.3 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	 STAINLESS STEEL

## 201017P HYDROFLOOR MINI ROUND GU10




201016P




201017P



Round ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. GU10 LED / halogen. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 ring.
- GU10 base, MAX 35W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Fully frosted glass available on request.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- M20 cable gland.
- Polypropylene recessing box included.



201018P HYDROFLOOR COMPACT SQUARE GU10





	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT MAX 220-230V 50-60HZ IP67 1.20 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	 STAINLESS STEEL

201019P HYDROFLOOR MINI STEEL AISI 316 ROUND GU10

Round ground-recessed luminaire for outdoor installation, Stainless steel AISI 316 body and frame, tempered safety glass, moulded silicone gasket. GU10 LED / halogen. IP67 rating.

- Material: completely made in Stainless Steel AISI 316
- Stainless steel AISI 316 ring.
- GU10 base, MAX 35W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Fully frosted glass available on request.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- M20 cable gland.
- Polypropilene recessing box included.






	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT MAX 220-230V 50-60HZ IP67 1.20 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	 STAINLESS STEEL

201022P HYDROFLOOR MINI 01 GU10

Round ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and protective cover, tempered safety glass, moulded silicone gasket. GU10 LED / halogen. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- GU10 base, MAX 35W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5.000 Kg
- Protection against impact IK09 (10 joule)
- M20 cable gland.
- Polypropilene recessing box included.
- Available also in GU5.3 12V version.








	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT MAX 220-240V 50-60HZ IP67 1.20 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES		 TEXTURED-GREY

201023P HYDROFLOOR MINI 02 GU10

Round ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and protective cover, tempered safety glass, moulded silicone gasket. GU10 LED / halogen. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- GU10 base, MAX 35W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5.000 Kg
- Protection against impact IK09 (10 joule)
- M20 cable gland.
- Polypropylene recessing box included.
- Available also in GU5.3 12V version.



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT MAX 220-240V 50-60HZ IP67 1.20 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES		 TEXTURED-GREY



201024 HYDROFLOOR MEDIUM PERFORMANCE LED

Round ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP67 rating.

Energy Label A++



- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- Stainless steel AISI 304 ring.
- NR. 5 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- M20 cable gland.
- Adjustable +/- 15 degrees.
- Polypropilene recessing box included.
- 1 mt. neoprene power cable included



HYDROFLOOR MEDIUM SQUARE LED AVAILABLE ON REQUEST



1...10 V DALI  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST  
Full RGB  
AVAILABLE ON REQUEST



8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
2.20 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	720	90.00	STAINLESS STEEL
		30°	684	85.50	
		45°	650	81.25	
	4.000°K NEUTRAL-WHITE	10°	750	93.75	
		30°	713	89.13	
		45°	677	84.63	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

## 201058 HYDROFLOOR MEDIUM COMPACT PERFORMANCE LED



Round compact ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP67 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 ring.
- NR. 5 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- Double PG11 cable gland.
- Adjustable +/- 15 degrees.
- Polypropilene recessing box included.
- 1 mt. neoprene power cable included




**Full RGB**  
AVAILABLE ON REQUEST



8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
2.20 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	720	90.00	STAINLESS STEEL
		30°	684	85.50	
		45°	650	81.25	
	4.000°K NEUTRAL-WHITE	10°	750	93.75	
		30°	713	89.13	
		45°	677	84.63	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ● BLUE



**201064 HYDROFLOOR MEDIUM STEEL AISI 316 PERFORMANCE LED**



Round ground-recessed luminaire for outdoor installation, stainless steel AISI 316 body and frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP67 rating.

**Energy Label A++**

- Material: completely made in stainless steel AISI 316
- NR. 5 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel trim AISI 316
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland
- Adjustable +/- 15 degrees.
- Polypropilene housing for recess included
- 1 mt. neoprene power cable included





**COMPLETELY MADE OF STAINLESS STEEL AISI 316 GRADE**



1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST



AVAILABLE ON REQUEST



8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
2,50 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	 3.000°K WARM-WHITE	10°	1.152	96.00	STAINLESS STEEL
		30°	1.095	91.25	
		45°	1.040	86.67	
	 4.000°K NEUTRAL-WHITE	10°	1.200	100.00	
		30°	1.140	95.00	
		45°	1.083	90.25	

201026M HYDROFLOOR MEDIUM AR-111 ROUND G53



201025M





201026M



Round ground-recessed luminaire for outdoor installation, Phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built in transformer 230V 50Hz, G53 AR-111 LED / halogen. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- Stainless steel AISI 304 ring.
- G53 base, MAX 50W
- Built-in toroidal transformer 230V 50Hz.
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Fully frosted glass available on request.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- Adjustable +/- 15 degrees.
- M20 cable gland.
- Polypropylene recessing box included.



201027M HYDROFLOOR MEDIUM AR-111 SQUARE G53



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
50 WATT MAX 220-230V 50-60HZ IP67 2.50 KG UNIT GROSS WEIGHT	 G53 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	 STAINLESS STEEL

## 201029P HYDROFLOOR MEDIUM P ROUND G8.5



201028P




201029P

Round ground-recessed luminaire for outdoor installation, Phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in ballast 220-240V 50-60Hz, G8.5 20W metal halide. IP67 rating.


- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 ring.
- HIT-TC CRI G8.5 20W
- Built-in electronic ballast 220-240V 50-60Hz.
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Fully frosted glass available on request.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- Adjustable +/- 15 degrees.
- Double M20 cable gland.
- Polypropylene recessing box included.






201030P HYDROFLOOR MEDIUM P SQUARE G8.5  
AVAILABLE ON REQUEST



FLOOD 60° REFLECTOR  
(STANDARD)



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20 WATT 220-240V 50-60HZ ELECTRONIC IP67 2.60 KG UNIT GROSS WEIGHT	 HIT-TC CRI 20W G8.5	SEE BULB FEATURES	 60° FLOOD	 STAINLESS STEEL

201032P HYDROFLOOR MEDIUM P ROUND FLUO GX24D-2



201031P





201032P

Round ground-recessed luminaire for outdoor installation, Phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in ballast 230V 50Hz, Gx24d-2 18W compact fluoscent. IP67 rating.


- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 ring.
- TC-T Gx24d-2 18W
- Built-in ballast 230V 50Hz.
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Fully frosted glass available on request.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland.
- Polypropilene recessing box included.






201033P HYDROFLOOR MEDIUM P SQUARE FLUO GX24D-2 AVAILABLE ON REQUEST



Ø 190 mm



MAX 5.000 KG

	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
18 WATT MAX 230V 50HZ IP67 2.50 KG UNIT GROSS WEIGHT	 TC-T - GX24D-2	SEE BULB FEATURES	 40°	 STAINLESS STEEL

## 201034 HYDROFLOOR MAXI PERFORMANCE LED

Round ground-recessed luminaire for outdoor installation, Phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-G3 LED. IP67 rating.

### Energy Label **A++**



- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel trim AISI 304
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland
- Adjustable +/- 15 degrees.
- Polypropilene housing for recess included
- 1 mt. neoprene power cable included



1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST



AVAILABLE ON REQUEST



12 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
5.00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	1.152	96.00	STAINLESS STEEL
		30°	1.095	91.25	
		45°	1.040	86.67	
	4.000°K NEUTRAL-WHITE	10°	1.200	100.00	
		30°	1.140	95.00	
		45°	1.083	90.25	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ● BLUE

201063 HYDROFLOOR MAXI SHALLOW PERFORMANCE LED



Round compact ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-G3 LED. IP67 rating.

Energy Label A++



- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel trim AISI 304
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK09 (10 joule)
- Double M20 cable gland
- Polypropylene housing for recess included
- 1 mt. neoprene power cable included




1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST



AVAILABLE ON REQUEST



HOLE FOR RECESSING Ø 257mm



12 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
4,50 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	1.152	96.00	STAINLESS STEEL
		30°	1.095	91.25	
		45°	1.040	86.67	
	4.000°K NEUTRAL-WHITE	10°	1.200	100.00	
		30°	1.140	95.00	
		45°	1.083	90.25	

## 201039 HYDROFLOOR MAXI ROUND G12



201038



201039

Round ground-recessed luminaire for outdoor installation, Phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in ballast 230V 50Hz, G12 35W or 70W metal halide. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT CRI 35W or HIT CRI 70W
- Built-in conventional ballast 230V 50Hz
- Stainless steel trim AISI 304
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland
- Adjustable +/- 15 degrees.
- Polypropylene housing for recess included



AC004 - LIGHT GRID  
(ACCESSORY)



AC002 - DARK-LIGHT ATTACHMENT  
(ACCESSORY)



SPOT 10° REFLECTOR  
(STANDARD)




SUPERSPOT 4°  
REFLECTOR  
(OPTION)




FLOOD 23° REFLECTOR  
(OPTION)



201040 HYDROFLOOR MAXI SQUARE  
G12 AVAILABLE ON REQUEST




Ø 265 mm



MAX 5.000 kg



MOVABLE



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT   70 WATT 230V 50HZ IP67 6.00 KG UNIT GROSS WEIGHT	HIT-CRI - BASE G12	SEE BULB FEATURES	4° SUPER-NARROW (ON REQUEST)	STAINLESS STEEL
			10° NARROW	
			23° FLOOD (ON REQUEST)	

201059 HYDROFLOOR MAXI STEEL AISI 316 PERFORMANCE LED

Round compact ground-recessed luminaire for outdoor installation, stainless steel AISI 316 body and frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-G3 LED. IP67 rating.

Energy Label A++

- Material: completely made in stainless steel AISI 316
- NR. 8 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel trim AISI 316
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland
- Adjustable +/- 15 degrees.
- Polypropilene housing for recess included
- 1 mt. neoprene power cable included





1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST



AVAILABLE ON REQUEST

COMPLETELY MADE  
OF STAINLESS STEEL  
AISI 316 GRADE



12 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
5.50 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	1.152	96.00	STAINLESS STEEL
		30°	1.095	91.25	
		45°	1.040	86.67	
	4.000°K NEUTRAL-WHITE	10°	1.200	100.00	
		30°	1.140	95.00	
		45°	1.083	90.25	




## 201041 HYDROFLOOR MAXI STEEL AISI 316 ROUND G12

Round compact ground-recessed luminaire for outdoor installation, stainless steel AISI 316 body and frame, tempered safety glass, moulded silicone gasket. Built-in ballast 230V 50Hz, G12 35W or 70W metal halide. IP67 rating.

- Material: completely made in stainless steel AISI 316
- HIT CRI 35W or HIT CRI 70W
- Built-in conventional ballast 230V 50Hz
- Stainless steel trim AISI 316
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland
- Adjustable +/- 15 degrees.
- Polypropylene housing for recess included



**COMPLETELY MADE  
OF STAINLESS STEEL  
AISI 316 GRADE**



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT   70 WATT 230V 50HZ IP67 6.00 KG UNIT GROSS WEIGHT	 HIT-CRI - BASE G12	SEE BULB FEATURES	4° SUPER-NARROW (ON REQUEST)	STAINLESS STEEL
			10° NARROW	
			23° FLOOD (ON REQUEST)	

201043S HYDROFLOOR MAXI ROUND RX7S SYMMETRIC



201042S



201043S

Round ground-recessed luminaire for outdoor installation, Phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Symmetrical reflector. Built-in ballast 230V 50Hz, Rx7s 70W metal halide. IP67 rating.



- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT DE 70W Rx7s
- Built-in conventional ballast 230V 50Hz
- Stainless steel trim AISI 304
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland
- Adjustable +/- 15 degrees.
- Polypropylene housing for recess included






AC004 - LIGHT GRID FOR VISUAL COMFORT (ACCESSORY)



201044 HYDROFLOOR MAXI SQUARE RX7S AVAILABLE ON REQUEST





	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
70 WATT 230V 50HZ IP67 6,00 KG UNIT GROSS WEIGHT	 HIT-DE - BASE RX7S	SEE BULB FEATURES	 60° FLOOD	 STAINLESS STEEL




201046A HYDROFLOOR MAXI ROUND RX7S ASYMMETRIC



Round ground-recessed luminaire for outdoor installation, Phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Asymmetrical reflector. Built-in ballast 230V 50Hz, Rx7s 70W metal halide. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT DE 70W Rx7s
- Built-in conventional ballast 230V 50Hz
- Stainless steel trim AISI 304
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland
- Polypropilene housing for recess included



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
70 WATT 230V 50HZ IP67 6,00 KG UNIT GROSS WEIGHT	 HIT-DE - BASE RX7S	SEE BULB FEATURES	 ASYMMETRIC	 STAINLESS STEEL

201048 HYDROFLOOR MAXI COMPACT PERFORMANCE LED

Round compact ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 15 CREE XP-G3 LED. IP67 rating.



Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 15 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel trim AISI 304
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland
- Polypropilene housing for recess included
- 1 mt. neoprene power cable included

1...10 V DALI  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST



REDUCED RECESSED DEPTH  
ONLY 136 mm



22 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
5 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	M 10°	2.160	98.18	STAINLESS STEEL
		M 30°	2.052	93.27	
		M 45°	1.949	88.60	
	4.000°K NEUTRAL-WHITE	M 10°	2.250	102.28	
		M 30°	2.137	97.14	
		M 45°	2.030	92.27	

## 201062 HYDROFLOOR MAXI COMPACT PERFORMANCE PRO LED

Round compact ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 15 CREE XP-L LED. IP67 rating.

### Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 15 CREE "XP-L" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel trim AISI 304
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland
- Polypropylene housing for recess included
- 1 mt. neoprene power cable included


1...10 V DALI

1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST




**REDUCED RECESSED DEPTH  
ONLY 136 mm**

**+70%  
LUMEN  
OUTPUT**



HOLE FOR RECESSING Ø 310mm



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
40 WATT 220-240V 50-60HZ ELECTRONIC IP67 5 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	M 10°	3.680	92.00	STAINLESS STEEL
			M 30°	3.500	87.50	
			M 45° *	3.320	83.00	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE - \* 45° ON REQUEST

201049 HYDROFLOOR MAXI COMPACT ROUND G12

Round compact ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in ballast 230V 50Hz, G12 35W or 70W metal halide. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT CRI 35W or HIT CRI 70W
- Built-in conventional ballast 230V 50Hz
- Stainless steel trim AISI 304
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland
- Polypropilene housing for recess included



REDUCED RECESSED DEPTH ONLY 136 mm




SPOT 10° REFLECTOR (STANDARD)



SUPERSPOT 4° REFLECTOR (OPTION)






FLOOD 23° REFLECTOR (OPTION)



AC004 - LIGHT GRID (ACCESSORY)

AC002 - DARK-LIGHT ATTACHMENT (ACCESSORY)








	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT   70 WATT 230V 50HZ IP67 6.00 KG UNIT GROSS WEIGHT	 HIT-CRI - BASE G12	SEE BULB FEATURES	4° SUPER-NARROW (ON REQUEST)	STAINLESS STEEL
			10° NARROW	
			23° FLOOD (ON REQUEST)	

## 201052X HYDROFLOOR MEGA ROUND G12



Round ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in ballast 230V 50Hz, G12 150W metal halide. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT CRI 150W G12
- Built-in conventional ballast 230V 50Hz
- Stainless steel trim AISI 304
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double PG13.5 cable gland
- Adjustable +/- 15 degrees.
- Polypropylene housing for recess included




	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
150 WATT 230V 50HZ IP67 13.10 KG UNIT GROSS WEIGHT	 HIT-CRI - BASE G12	SEE BULB FEATURES	4° SUPER-NARROW (ON REQUEST)	STAINLESS STEEL
			10° NARROW	
			23° FLOOD (ON REQUEST)	

## AC005 HYDROCONNECT-02 - 2 WAYS

- Hydroconnect ip68-02  
2 Ways

IP68 - CE ▽ ⊕




### COLORS OPTIONS

■ MATT BLACK

## AC006 HYDROCONNECT-03 - 3 WAYS

- Hydroconnect ip68-03  
3 Ways

IP68 - CE ▽ ⊕



### COLORS OPTIONS

■ MATT BLACK



## 202001 HYDROQUADRO MINI PERFORMANCE LED

Square ground-recessed luminaire for outdoor installation, Phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 3 CREE XP-G3 LED. IP67 rating.








**Energy Label** **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 trim.
- NR. 3 x 1W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- M20 cable gland.
- Adjustable +/- 15 degrees.
- Polypropilene recessing box included.
- 3 mt. neoprene power cable included

**Full RGB**  
AVAILABLE ON REQUEST



3 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
1.25 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	 10°	346	115.33	 STAINLESS STEEL
		 30°	329	109.66	
		 45°	312	104.00	
	4.000°K NEUTRAL-WHITE	 10°	360	120.00	
		 30°	342	114.00	
		 45°	325	108.33	



\* OTHER LIGHT COLORS AVAILABLE ON REQUEST:  BLUE

202002P HYDROQUADRO MINI ROUND GU5.3

Square ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. GU5.3 LED / halogen. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- Stainless steel AISI 304 trim.
- GU5.3 base, MAX 35W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Fully frosted glass available on request.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- Adjustable +/- 15 degrees.
- M20 cable gland.
- Polypropilene recessing box included.





	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT MAX 12V IP67 1.20 KG UNIT GROSS WEIGHT	 GU5.3 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	 STAINLESS STEEL

202003P HYDROQUADRO MINI ROUND GU10

Square ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. GU10 LED / halogen. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- Stainless steel AISI 304 ring.
- GU10 base, MAX 35W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Fully frosted glass available on request.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- M20 cable gland.
- Polypropilene recessing box included.



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT MAX 220-230V 50-60HZ IP67 1.20 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	 STAINLESS STEEL

## 202008 HYDROQUADRO MEDIUM PERFORMANCE LED



Square ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 9 CREE XP-G3 LED. IP67 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 trim.
- NR. 9 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland.
- Adjustable +/- 15 degrees.
- Polypropylene recessing box included.
- 1 mt. neoprene power cable included




1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST



14 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
2.80 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	1.296	92.57	STAINLESS STEEL
		30°	1.231	87.93	
		45°	1.170	83.57	
	4.000°K NEUTRAL-WHITE	10°	1.350	96.43	
		30°	1.283	91.65	
		45°	1.219	87.07	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ● BLUE



**202009 HYDROQUADRO MAXI PERFORMANCE LED**



Square ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 16 CREE XP-G3 LED. IP67 rating.

**Energy Label A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 trim.
- NR. 16 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland.
- Adjustable +/- 15 degrees.
- Polypropilene recessing box included.
- 1 mt. neoprene power cable included



**1...10 V DALI**  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST



24 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
5.70 KG UNIT GROSS WEIGHT



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	2.304	96.00	STAINLESS STEEL
		30°	2.189	91.21	
		45°	2.080	86.67	
	4.000°K NEUTRAL-WHITE	10°	2.400	100.00	
		30°	2.280	95.00	
		45°	2.166	90.25	






\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

202006 HYDROQUADRO MAXI G12

Square ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in ballast 230V 50Hz, G12 35W or 70W metal halide. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT CRI 35W or HIT CRI 70W
- Built-in conventional ballast 230V 50Hz
- Stainless steel AISI 304 trim.
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland
- Adjustable +/- 15 degrees.
- Polypropylene housing for recess included



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT   70 WATT 230V 50HZ IP67 6.50 KG UNIT GROSS WEIGHT	 HIT-CRI – BASE G12	SEE BULB FEATURES	 4° SUPER-NARROW (ON REQUEST)	 STAINLESS STEEL
			 10° NARROW	
			 23° FLOOD (ON REQUEST)	

## 202010 HYDROQUADRO MAXI PERFORMANCE PRO LED



Square ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 16 CREE XP-L LED. IP67 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 trim.
- NR. 16 CREE "XP-L" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- Double M20 cable gland.
- Adjustable +/- 15 degrees.
- Polypropylene recessing box included.
- 1 mt. neoprene power cable included



1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
44 WATT 220-240V 50-60HZ ELECTRONIC IP67 5.70 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	10°	3.920	89.10	STAINLESS STEEL
			30°	3.720	84.55	
			45°	3.540	80.45	


\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE

205001 HYDROFLOOR VETRO MEDIUM SQUARE LED

Square ground-recessed trimless uplight for outdoor installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP67 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- NR. 5 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- PG9 cable gland.
- Polypropylene recessing box included.
- 1 mt. neoprene power cable included



8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
1,40 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	720	90.00	GLASS
		30°	684	85.50	
		45°	650	81.25	
	4.000°K NEUTRAL-WHITE	10°	750	93.75	
		30°	713	89.13	
		45°	677	84.63	


## 205002 HYDROFLOOR VETRO LINEAR LED

NEW










Linear ground-recessed trimless uplight for outdoor installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 6 CREE XP-G3 LED. IP67 rating.

### Energy Label A++


- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 6 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5.000 Kg
- Protection against impact IK10 (20 joule)
- PG9 cable gland.
- Polypropylene recessing box included.
- 1 mt. neoprene power cable included



10 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
1,40 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	 3.000°K WARM-WHITE	 10°	900	90.00	 GLASS
		 30°	855	85.50	
		 45°	812	81.20	
	 4.000°K NEUTRAL-WHITE	 10°	940	94.00	
		 30°	893	89.30	
		 45°	848	84.80	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST:  BLUE



## 203003 HYDROLINE 13 PERFORMANCE LED

Linear ground-recessed luminaire for outdoor installation, length 685mm, Phospho-chromatised and polyester powder coated extruded copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 13 CREE XP-G3 LED. IP67 rating.



### Energy Label **A++**

- Material: high corrosion resistance extruded copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 13 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel AISI 304 trim.
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double PG13.5 cable gland
- Stainless steel housing for recess included.
- 1 mt. neoprene power cable included.




**1...10 V** **DALI**  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST


**RGB**  
AVAILABLE ON REQUEST




WHEN INSTALLING HYDROLINE, A "DRAINAGE BED" OF AT LEAST 20 CENTIMETERS HAS TO BE OBSERVED UNDER THE STAINLESS STEEL RECESSING BOX (GRAVEL AND SAND)



Only fixture



Stainless steel box



19.5 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
7.00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	1.872	96.00	STAINLESS STEEL
		30°	1.779	91.25	
		45°	1.690	86.67	
		ASYMMETRIC WALL-WASHER	1.779	91.25	
	4.000°K NEUTRAL-WHITE	10°	1.950	100.00	
		30°	1.853	95.00	
		45°	1.760	90.25	
		ASYMMETRIC WALL-WASHER	1.853	95.00	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: **BLUE**

203004 HYDROLINE 21 PERFORMANCE LED

Linear ground-recessed luminaire for outdoor installation, length 985mm, Phospho-chromatised and polyester powder coated extruded copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 21 CREE XP-G3 LED. IP67 rating.



Energy Label A++

- Material: high corrosion resistance extruded copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 21 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel AISI 304 trim.
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Max static weight resistance 5000 Kg
- Protection against impact IK10 (20 joule)
- Double PG13.5 cable gland
- Stainless steel housing for recess included.
- 1 mt. neoprene power cable included.




1...10 V DALI  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST

RGB  
AVAILABLE ON REQUEST




WHEN INSTALLING HYDROLINE, A "DRAINAGE BED" OF AT LEAST 20 CENTIMETERS HAS TO BE OBSERVED UNDER THE STAINLESS STEEL RECESSING BOX (GRAVEL AND SAND)



31.5 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
10.00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	3.024	96.00	STAINLESS STEEL
		30°	2.873	91.25	
		45°	2.729	86.67	
		ASYMMETRIC WALL-WASHER	2.873	91.25	
	4.000°K NEUTRAL-WHITE	10°	3.150	100.00	
		30°	2.993	95.00	
		45°	2.843	90.25	
		ASYMMETRIC WALL-WASHER	2.993	95.00	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE





## 204003 HYDROLINE VETRO SLIM LED

Linear slim ground-recessed luminaire for outdoor installation, length 1.000mm, anodized extruded aluminium body, tempered frosted glass diffuser, stainless steel housing for recess. Built-in LED driver 220-240V 50-60Hz, Low power 72 Epistar SMD5050 LED. IP67 rating.

### Energy Label **A++**

- Material: high corrosion resistance extruded copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 72 x Epistar SMD5050 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Opal resin diffuser.
- Max static weight resistance 3000 Kg
- Protection against impact IK09 (10 joule)
- Stainless steel housing for recess included.
- Double 0.5 mt. neoprene power cable included, supplied with male/female quick coupling for in-line installation.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
15 WATT 220-240V 50-60HZ ELECTRONIC IP67 4.20 KG UNIT GROSS WEIGHT	SMD 5050 LED	3.000°K WARM-WHITE	90°	300	20.00	GLASS





## 204001 HYDROLINE VETRO LED

Linear ground-recessed luminaire for outdoor installation, length 1.000mm, anodized extruded aluminium body, tempered safety glass, moulded silicone gaskets, stainless steel housing for recess. 24V remote driver needed, Low power EPISTAR SMD3528 LED. IP67 rating.

### Energy Label **A++**

- Material: high corrosion resistance extruded copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel screws
- Tempered safety glass diffuser.
- Max static weight resistance 3000 Kg
- Protection against impact IK09 (10 joule)
- Stainless steel housing for recess included.
- 1 mt. neoprene power cable included.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
12 WATT 24V DC REMOTE DRIVER NEEDED IP67 5.00 KG UNIT GROSS WEIGHT	SMD 3528 LED	3.000°K WARM-WHITE	100°	480	40.00	GLASS
		4.000°K NEUTRAL-WHITE	100°	500	40.00	

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	1
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 - MAX 2
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 4
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 - MAX 7





## 204002 HYDROLINE VETRO PERFORMANCE LED









Linear ground-recessed luminaire for outdoor installation, length 1.000mm, anodized extruded aluminium body, tempered safety glass, moulded silicone gaskets, stainless steel housing for recess. 350/500mA remote driver needed, with 25 CREE XP-G3 LED. IP67 rating.

### Energy Label **A++**




- Material: high corrosion resistance extruded copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel screws
- Tempered safety glass diffuser.
- Max static weight resistance 3000 Kg
- Protection against impact IK09 (10 joule)
- Stainless steel housing for recess included.
- 1 mt. neoprene power cable included.




37 WATT  
350/500 MA REMOTE DRIVER NEEDED  
IP67  
5.10 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	 3.000°K WARM-WHITE	 10°	3.600	96.00	GLASS
		 30°	3.420	91.25	
		 45°	3.249	86.67	
		ASYMMETRIC WALL-WASHER	3.420	91.25	
	 4.000°K NEUTRAL-WHITE	 10°	3.750	100.00	
		 30°	3.563	95.00	
		 45°	3.385	90.25	
		ASYMMETRIC WALL-WASHER	3.563	95.00	

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
 TCI ITALY	122210	CONSTANT CURRENT 350 MA / 500 MA	40W - 56W	IP20	1
 TRIDONIC	87500329	CONSTANT CURRENT 500 MA	65W	IP67	1
 TRIDONIC	87500335	CONSTANT CURRENT 500 MA	150W	IP67	MIN 2 - MAX 4







# Underwater



301000 HYDROSCUBA

page. **119**



303000 HYDROPOOL

page. **124**



305000 HYDRODIVE

page. **128**



## 301001 HYDROSCUBA MICRO LED – SURFACE MOUNTED

Small underwater projector, surface mounted, completely made in stainless steel AISI 316L, silicone o-rings, 350/500mA remote driver needed, with 1 CREE XP-G3 LED. IP 68 rating.


### Energy Label **A++**

- Material: completely made in stainless steel AISI 316 L marine grade
- Stainless steel AISI 316 L marine grade trim.
- NR. 1 x 1.5W CREE "XP-G3" LED
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection system IP68 with maximum immersion depth 3 mt.
- M12 cable gland made in stainless steel AISI 316.
- 8 mt. neoprene power cable included
- Adjustable through 200°



AC 024 - SPIKE FOR HYDROSCUBA MICRO/MINI

1.5 WATT  
REMOTE DRIVER 350/500 MA NEEDED  
IP68 – 3 METERS DEPTH  
1.50 KG UNIT GROSS WEIGHT



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	144	96.00	STAINLESS STEEL
		30°	137	91.34	
		45°	130	86.67	
	4.000°K NEUTRAL-WHITE	10°	150	100.00	
		30°	143	95.34	
		45°	136	90.67	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

### REMOTE DRIVER SELECTION


BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
TCI ITALY	122086	CONSTANT CURRENT 350 MA	4W	IP20	MIN 1 - MAX 2
TCI ITALY	122204	CONSTANT CURRENT 350 MA / 500 MA	25W - 35W	IP20	MIN 1 - MAX 16
MEANWELL	LPC-20-350	CONSTANT CURRENT 350 MA	16.8W	IP67	MIN 4 - MAX 12
MEANWELL	LPC-20-700	CONSTANT CURRENT 700 MA	21W	IP67	MIN 4 - MAX 8
MEANWELL	LPF-25-48	CONSTANT CURRENT 530 MA	25W	IP67	MIN 10 - MAX 16

## 301002 HYDROSCUBA MICRO LED - RECESS

Small underwater luminaire, wall-recessed, completely made in stainless steel AISI 316L, silicone o-rings, acetal resin housing for recess. 350/500mA remote driver needed, with 1 CREE XP-G3 LED. IP 68 rating.

### Energy Label **A++**

- Material: completely made in stainless steel AISI 316 L marine grade
- Stainless steel AISI 316 L marine grade trim.
- NR. 1 x 1.5W CREE "XP-G3" LED
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection system IP68 with maximum immersion depth 3 mt.
- M12 cable gland made in stainless steel AISI 316.
- Recess housing made in acetal resin.
- Cable sheath made in PVC.
- 8 mt. neoprene power cable included



1.5 WATT  
REMOTE DRIVER 350/500 MA NEEDED  
IP68 - 3 METERS DEPTH  
1.50 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	144	96.00	STAINLESS STEEL
		30°	137	91.34	
		45°	130	86.67	
	4.000°K NEUTRAL-WHITE	10°	150	100.00	
		30°	143	95.34	
		45°	136	90.67	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
TCI ITALY	122086	CONSTANT CURRENT 350 MA	4W	IP20	MIN 1 - MAX 2
TCI ITALY	122204	CONSTANT CURRENT 350 MA / 500 MA	25W - 35W	IP20	MIN 1 - MAX 16
MEANWELL	LPC-20-350	CONSTANT CURRENT 350 MA	16.8W	IP67	MIN 4 - MAX 12
MEANWELL	LPC-20-700	CONSTANT CURRENT 700 MA	21W	IP67	MIN 4 - MAX 8
MEANWELL	LPF-25-48	CONSTANT CURRENT 530 MA	25W	IP67	MIN 10 - MAX 16

## 301003 HYDROSCUBA MINI LED – SURFACE MOUNTED

Small underwater projector, surface mounted, completely made in stainless steel AISI 316L, silicone o-rings, 350/500mA remote driver needed, with 4 CREE XP-G3 LED. IP 68 rating.


### Energy Label **A++**








- Material: completely made in stainless steel AISI 316 L marine grade
- Stainless steel AISI 316 L marine grade trim.
- NR. 4 x 1.5W CREE "XP-G3" LED
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection system IP68 with maximum immersion depth 3 mt.
- M12 cable gland made in stainless steel AISI 316.
- 8 mt. neoprene power cable included
- Adjustable through 200°



AC 024 - SPIKE FOR HYDROSCUBA MICRO/MINI






6 WATT  
REMOTE DRIVER 350/500 MA NEEDED  
IP68 – 3 METERS DEPTH  
2.00 KG UNIT GROSS WEIGHT



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	 10°	576	96.00	 STAINLESS STEEL
		 30°	548	91.34	
		 30°	521	86.84	
	4.000°K NEUTRAL-WHITE	 10°	600	100.00	
		 30°	570	95.00	
		 30°	541,50	90.25	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST:  BLUE

### REMOTE DRIVER SELECTION


BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
 TCI ITALY	122356	CONSTANT CURRENT 500 MA	12W	IP20	1
 TCI ITALY	122204	CONSTANT CURRENT 350 MA / 500 MA	25W - 35W	IP20	MIN 1 - MAX 4
 MEANWELL	LPC-20-350	CONSTANT CURRENT 350 MA	16.8W	IP67	MIN 1 - MAX 4
 MEANWELL	LPC-20-700	CONSTANT CURRENT 700 MA	21W	IP67	MIN 1 - MAX 2
 MEANWELL	LPF-25-48	CONSTANT CURRENT 530 MA	25W	IP67	MIN 3 - MAX 4

## 301004 HYDROSCUBA MINI LED – RECESS

Small underwater luminaire, wall-recessed, completely made in stainless steel AISI 316L, silicone o-rings, acetal resin housing for recess. 350/500mA remote driver needed, with 4 CREE XP-G3 LED. IP 68 rating.

### Energy Label **A++**

- Material: completely made in stainless steel AISI 316 L marine grade
- Stainless steel AISI 316 L marine grade trim.
- NR. 4 x 1.5W CREE "XP-G3" LED
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection system IP68 with maximum immersion depth 3 mt.
- M12 cable gland made in stainless steel AISI 316.
- Recess housing made in acetal resin.
- Cable sheath made in PVC.
- 8 mt. neoprene power cable included



6 WATT  
REMOTE DRIVER 350/500 MA NEEDED  
IP68 – 3 METERS DEPTH  
2.00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	576	96.00	STAINLESS STEEL
		30°	548	91.34	
		30°	521	86.84	
	4.000°K NEUTRAL-WHITE	10°	600	100.00	
		30°	570	95.00	
		30°	541,50	90.25	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ● BLUE

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
TCI ITALY	122356	CONSTANT CURRENT 500 MA	12W	IP20	1
TCI ITALY	122204	CONSTANT CURRENT 350 MA / 500 MA	25W - 35W	IP20	MIN 1 - MAX 4
MEANWELL	LPC-20-350	CONSTANT CURRENT 350 MA	16.8W	IP67	MIN 1 - MAX 4
MEANWELL	LPC-20-700	CONSTANT CURRENT 700 MA	21W	IP67	MIN 1 - MAX 2
MEANWELL	LPF-25-48	CONSTANT CURRENT 530 MA	25W	IP67	MIN 3 - MAX 4

## 301005 HYDROSCUBA MEDIUM LED – SURFACE MOUNTED

Underwater projector, surface mounted, completely made in stainless steel AISI 316L, silicone o-rings, 350/500mA remote driver needed, with 5 CREE XP-G3 LED. IP 68 rating.


### Energy Label **A++**

- Material: completely made in stainless steel AISI 316 L marine grade
- Stainless steel AISI 316 L marine grade trim.
- NR. 5 x 1.5W CREE "XP-G3" LED
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection system IP68 with maximum immersion depth 3 mt.
- M12 cable gland made in stainless steel AISI 316.
- 8 mt. neoprene power cable included
- Adjustable through 200°



AC 025 - SPIKE FOR HYDROSCUBA MEDIUM

8 WATT  
REMOTE DRIVER 350/500 MA NEEDED  
IP68 – 3 METERS DEPTH  
5.00 KG UNIT GROSS WEIGHT



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	720	90.00	STAINLESS STEEL
		30°	684	85.50	
		45°	650	81.25	
	4.000°K NEUTRAL-WHITE	10°	750	93.75	
		30°	713	89.13	
		45°	677	84.63	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ● BLUE

### REMOTE DRIVER SELECTION


BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
TCI ITALY	122356	CONSTANT CURRENT 500 MA	12W	IP20	1
TCI ITALY	122204	CONSTANT CURRENT 350 MA / 500 MA	25W - 35W	IP20	MIN 1 - MAX 3
MEANWELL	LPC-20-350	CONSTANT CURRENT 350 MA	16.8W	IP67	MIN 1 - MAX 3
MEANWELL	LPC-20-700	CONSTANT CURRENT 700 MA	21W	IP67	MIN 1 - MAX 2
MEANWELL	LPF-25-48	CONSTANT CURRENT 530 MA	25W	IP67	MIN 2 - MAX 3

**301006    HYDROSCUBA MEDIUM LED – RECESS**










Underwater luminaire, wall-recessed, completely made in stainless steel AISI 316L, silicone o-rings, acetal resin housing for recess. 350/500mA remote driver needed, with 5 CREE XP-G3 LED. IP 68 rating.

**Energy Label    A++**






- Material: completely made in stainless steel AISI 316 L marine grade
- Stainless steel AISI 316 L marine grade trim.
- NR. 5 x 1.5W CREE "XP-G3" LED
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection system IP68 with maximum immersion depth 3 mt.
- M12 cable gland made in stainless steel AISI 316.
- Recess housing made in acetal resin.
- Cable sheath made in PVC.
- 8 mt. neoprene power cable included



8 WATT  
 REMOTE DRIVER 350/500 MA NEEDED  
 IP68 – 3 METERS DEPTH  
 5.00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	 3.000°K WARM-WHITE	 10°	720	90.00	 STAINLESS STEEL
		 30°	684	85.50	
		 45°	650	81.25	
	 4.000°K NEUTRAL-WHITE	 10°	750	93.75	
		 30°	713	89.13	
		 45°	677	84.63	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST:  BLUE

REMOTE DRIVER SELECTION		MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
	TCI ITALY	122356	CONSTANT CURRENT 500 MA	12W	IP20	1
	TCI ITALY	122204	CONSTANT CURRENT 350 MA / 500 MA	25W - 35W	IP20	MIN 1 - MAX 3
	MEANWELL	LPC-20-350	CONSTANT CURRENT 350 MA	16.8W	IP67	MIN 1 - MAX 3
	MEANWELL	LPC-20-700	CONSTANT CURRENT 700 MA	21W	IP67	MIN 1 - MAX 2
	MEANWELL	LPF-25-48	CONSTANT CURRENT 530 MA	25W	IP67	MIN 2 - MAX 3

## 303001 HYDROPOL MEDIUM LED

Swimming-pool underwater luminaire, round shape, wall-recessed, completely made in stainless steel AISI 316L, polypropylene housing for recess. 24V remote driver needed, with 6 OSRAM LED. IP 68 rating.

### Energy Label **A++**


- Material: completely made in stainless steel AISI 316 L marine grade
- Stainless steel AISI 316 L marine grade trim.
- NR. 6 x 2W OSRAM LED
- Stainless steel screws
- EPDM rubber gasket
- Tempered safety glass.
- Protection system IP68 with maximum immersion depth 1 mt.
- Protection against impact IK08
- PG11 cable gland made in nickel-plated brass.
- Recess housing made in polypropylene.
- 3 mt. neoprene power cable included




AVAILABLE ON REQUEST



**THIS LUMINAIRE IS SUITABLE ONLY FOR UNDERWATER INSTALLATION**



Ø 180mm



120mm

54mm

Ø 156mm



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
12 WATT 24V DC REMOTE DRIVER NEEDED IP68 – 1 METER DEPTH 2.00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	30°	1.200	100.00	STAINLESS STEEL

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	1
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 - MAX 2
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 4
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 - MAX 7

303002 HYDROPPOOL MAXI LED


Swimming-pool underwater luminaire, round shape, wall-recessed, completely made in stainless steel AISI 316L, polypropylene housing for recess. 24V remote driver needed, with 12 OSRAM LED. IP 68 rating.

Energy Label A++




- Material: completely made in stainless steel AISI 316 L marine grade
- Stainless steel AISI 316 L marine grade trim.
- NR. 12 x 2W OSRAM LED
- Stainless steel screws
- EPDM rubber gasket
- Tempered safety glass.
- Protection system IP68 with maximum immersion depth 1 mt.
- Protection against impact IK08
- PG11 cable gland made in nickel-plated brass.
- Recess housing made in polypropylene.
- 3 mt. neoprene power cable included



THIS LUMINAIRE IS SUITABLE ONLY FOR UNDERWATER INSTALLATION



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
24 WATT 24V DC REMOTE DRIVER NEEDED IP68 – 1 METER DEPTH 2.50 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	30°	2.000	83.34	STAINLESS STEEL

REMOTE DRIVER SELECTION					
BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
 MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	1
 MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 2
 MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 - MAX 3

## 303003 HYDROPPOOL MEGA LED

Swimming-pool underwater luminaire, round shape, wall-recessed, completely made in stainless steel AISI 316 L, polypropylene housing for recess. 24V remote driver needed, with 18 OSRAM LED. IP 68 rating.

### Energy Label A++


- Material: completely made in stainless steel AISI 316 L marine grade
- Stainless steel AISI 316 L marine grade trim.
- NR. 18 x 2W OSRAM LED
- Stainless steel screws
- EPDM rubber gasket
- Tempered safety glass.
- Protection system IP68 with maximum immersion depth 1 mt.
- Protection against impact IK08
- PG11 cable gland made in nickel-plated brass.
- Recess housing made in polypropylene.
- 3 mt. neoprene power cable included



AVAILABLE ON REQUEST




THIS LUMINAIRE IS SUITABLE ONLY FOR UNDERWATER INSTALLATION



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
36 WATT 24V DC REMOTE DRIVER NEEDED IP68 – 1 METER DEPTH 3.80 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	30°	2.900	80.56	STAINLESS STEEL

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	1
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 - MAX 2



## 305001 HYDRODIVE MINI LED




Underwater projector, surface mounted, completely made in stainless steel AISI 316L, silicone gasket, 24V DC remote driver needed, with 1 x COB LED. IP 68 rating.

### Energy Label **A++**

- Material: completely made in stainless steel AISI 316 L marine grade
- NR. 1x8W COB LED
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection system IP68 with maximum immersion depth 1 mt.
- PG11 Cable gland made copper with nickel-coated
- 3 mt. neoprene power cable included

**Full RGB**  
AVAILABLE ON REQUEST

**! THIS LUMINAIRE IS SUITABLE ONLY FOR UNDERWATER INSTALLATION**



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
8 WATT 24V DC DRIVER NEEDED IP68 – 1 METERS DEPTH 1,10 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	30°	607	75.87	STAINLESS STEEL

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	MIN 1 – MAX 2
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 – MAX 3
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 – MAX 6

305002 HYDRODIVE MEDIUM LED **NEW**


Underwater projector, surface mounted, completely made in stainless steel AISI 316L, silicone gasket, 24V DC remote driver needed, with 1 x COB LED. IP 68 rating.

Energy Label **A++**

- Material: completely made in stainless steel AISI 316 L marine grade
- NR. 1x16W COB LED
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection system IP68 with maximum immersion depth 1 mt.
- PG11 Cable gland made copper with nickel-coated
- 3 mt. neoprene power cable included

**Full RGB**  
AVAILABLE ON REQUEST

**! THIS LUMINAIRE IS SUITABLE ONLY FOR UNDERWATER INSTALLATION**



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
16 WATT 24V DC DRIVER NEEDED IP68 – 1 METERS DEPTH 1,60 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	30°	1.183	73.94	STAINLESS STEEL

REMOTE DRIVER SELECTION					
BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	1
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 3

## 305003 HYDRODIVE MAXI LED

NEW


Underwater projector, surface mounted, completely made in stainless steel AISI 316L, silicone gasket, 24V DC remote driver needed, with 1 x COB LED. IP 68 rating.

### Energy Label A++

- Material: completely made in stainless steel AISI 316 L marine grade
- NR. 1x20W COB LED
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection system IP68 with maximum immersion depth 1 mt.
- PG11 Cable gland made copper with nickel-coated
- 3 mt. neoprene power cable included

**Full RGB**  
AVAILABLE ON REQUEST

**! THIS LUMINAIRE IS SUITABLE ONLY FOR UNDERWATER INSTALLATION**



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
20 WATT 24V DC DRIVER NEEDED IP68 – 1 METERS DEPTH 2,00 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	30°	1.478	73.90	STAINLESS STEEL

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	1
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 2
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 - MAX 4







# Wall Mounting



401100 HYDROWAVE

page. **134**



401000 HYDROTECH

page. **136**



401900 HYDROTECH STEEL

page. **152**



401700 HYDROECLIPSE

page. **158**



401600 HYDROSURF

page. **172**



401800 HYDROFLEX

page. **182**



402000 HYDROBRACKET

page. **190**



403000 HYDROLINE-B

page. **201**



404000 HYDROSPLIT

page. **203**



405000 HYDROLED

page. **209**



401400 HYDROMASK

page. **212**



406000 HYDROTARGET

page. **216**



401300 HYDRODISK

page. **220**




## 401101 HYDROWAVE LED


Surface mounted luminaire for outdoor installation on window sill, with asymmetric 8°x170° "window-washer" light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 1 CREE LED. IP65 rating.

### Energy Label **A++**


- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 3W CREE "XP-G" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass
- 1 mt. neoprene power cable included



170°  
SINGLE INSTALLATION,  
IN THE MIDDLE:  
SUGGESTED FOR  
SMALL / MEDIUM  
SIZE WINDOWS




170°  
DOUBLE INSTALLATION,  
ON BOTH SIDES:  
SUGGESTED IN CASE  
OF HIGH LIGHTING  
PERFORMANCE NEEDED



170°  
DOUBLE INSTALLATION,  
IN THE MIDDLE:  
SUGGESTED FOR  
BIG SIZE WINDOWS.



SIDE KNOCKOUT FOR CABLE




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
6 WATT 220-240V 50-60HZ ELECTRONIC IP65 0,65 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	8° X 170°	350	58.00	TEXTURED GREY




401001L HYDROTECH MINI 02 ROUND GU10

Round up&down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. GU10 LED / halogen. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Double GU10 base, MAX 50W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.





	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
50 WATT MAX 220-240V 50-60HZ IP65 1.30 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	<div><div></div> TEXTURED GREY</div> <div><div></div> MATT WHITE (ON REQUEST)</div> <div><div></div> MATT BLACK (ON REQUEST)</div>

401002L HYDROTECH MINI 02 SQUARE GU10

Square up&down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. GU10 LED / halogen. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Double GU10 base, MAX 50W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.









	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
50 WATT MAX 220-240V 50-60HZ IP65 1.40 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	<div><div></div> TEXTURED GREY</div> <div><div></div> MATT WHITE (ON REQUEST)</div> <div><div></div> MATT BLACK (ON REQUEST)</div>

401003 HYDROTECH MEDIUM 02 ROUND G12

Round up&down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in electronic ballast 220-240V 50-60Hz, 1 x G12 35W or 70W metal halide. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT CRI 35W G12 or HIT CRI 70W G12.
- Electronic ballast 220/240V 50/60Hz included.
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M20 rubber grommet Rutaseal® in EPDM




	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT   70 WATT 220-240V 50-60HZ ELECTRONIC IP65 5.00 KG UNIT GROSS WEIGHT	 HIT-TC CRI 35W OR 70W G12	SEE BULB FEATURES	 40° FLOOD	 TEXTURED GREY  MATT WHITE (ON REQUEST)  MATT BLACK (ON REQUEST)





401013    HYDROTECH MEDIUM 01 ROUND G12

Round wall mounted luminaire for outdoor installation on a façade/wall, with light distribution downward only. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in electronic ballast 220-240V 50-60Hz, 1 x G12 35W or 70W metal halide. IP65 rating.

Energy Label    A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT CRI 35W G12 or HIT CRI 70W G12.
- Electronic ballast 220/240V 50/60Hz included.
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M20 rubber grommet Rutaseal® in EPDM





	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT   70 WATT 220-240V 50-60HZ ELECTRONIC IP65 5.00 KG UNIT GROSS WEIGHT	HIT-TC CRI 35W OR 70W G12	SEE BULB FEATURES	 40° FLOOD	 TEXTURED GREY  MATT WHITE (ON REQUEST)  MATT BLACK (ON REQUEST)

## 401004 HYDROTECH MEDIUM 02 ROUND LED

Round up&down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 5 CREE XP-G3 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 x 1.5W CREE "XP-G3" LED up and NR. 5 x 1.5W CREE "XP-G3" LED down.
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M20 rubber grommet Rutaseal® in EPDM
- Adjustable +/- 15 degrees.



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	2 X 720	90.00	<div> TEXTURED GREY</div> <div> MATT WHITE (ON REQUEST)</div> <div> MATT BLACK (ON REQUEST)</div>
		30°	2 X 684	85.50	
		45°	2 X 650	81.25	
	4.000°K NEUTRAL-WHITE	10°	2 X 750	93.75	
		30°	2 X 713	89.13	
		45°	2 X 677	84.63	

2X8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
3.00 KG UNIT GROSS WEIGHT




\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

401016 HYDROTECH MEDIUM 02 ROUND PRO LED

Round up&down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 5 CREE XP-L LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 CREE "XP-L" LED up and NR. 5 CREE "XP-L" LED down.
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M20 rubber grommet Rutaseal® in EPDM
- Adjustable +/- 15 degrees.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2X14 WATT 220-240V 50-60HZ ELECTRONIC IP65 3.00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	10°	2 X 1.300	92.86	TEXTURED GREY
			30°	2 X 1.230	87.86	MATT WHITE (ON REQUEST)
			45°	2 X 1.170	83.57	MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE


## 401012 HYDROTECH MEDIUM 01 ROUND LED

Round wall mounted luminaire for outdoor installation on a façade/wall, with light distribution downward only. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 x 1.5W CREE "XP-G3" LED down.
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M20 rubber grommet Rutaseal® in EPDM
- Adjustable +/- 15 degrees.

**FullRGB**  
AVAILABLE ON REQUEST



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	720	90.00	TEXTURED GREY
		30°	684	85.50	
		45°	650	81.25	MATT WHITE (ON REQUEST)
	4.000°K NEUTRAL-WHITE	10°	750	93.75	
		30°	713	89.13	
		45°	677	84.63	MATT BLACK (ON REQUEST)

8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
3.00 KG UNIT GROSS WEIGHT

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

401017 HYDROTECH MEDIUM 01 ROUND PRO LED


Round wall mounted luminaire for outdoor installation on a façade/wall, with light distribution downward only. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-L LED. IP65 rating.








Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 CREE "XP-L" LED down.
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M20 rubber grommet Rutaseal® in EPDM
- Adjustable +/- 15 degrees.



+70%  
LUMEN  
OUTPUT





	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
14 WATT 220-240V 50-60HZ ELECTRONIC IP65 3.00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 10°	1.300	92.86	 TEXTURED GREY
			 30°	1.230	87.86	 MATT WHITE (ON REQUEST)
			 45°	1.170	83.57	 MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE

401005 HYDROTECH MEDIUM 02 SQUARE G12

Square up&down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in electronic ballast 220-240V 50-60Hz, 1 x G12 35W or 70W metal halide. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT CRI 35W G12 or HIT CRI 70W G12.
- Electronic ballast 220/240V 50/60Hz included.
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M20 rubber grommet Rutaseal® in EPDM




	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT   70 WATT 220-240V 50-60HZ ELECTRONIC IP65 5.00 KG UNIT GROSS WEIGHT	 HIT-TC CRI 35W OR 70W G12	SEE BULB FEATURES	 40° FLOOD	<div><div>TEXTURED GREY</div><div>MATT WHITE (ON REQUEST)</div><div>MATT BLACK (ON REQUEST)</div></div>


401015    HYDROTECH MEDIUM 01 SQUARE G12

Square wall mounted luminaire for outdoor installation on a façade/wall, with light distribution downward only. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in electronic ballast 220-240V 50-60Hz, 1 x G12 35W or 70W metal halide. IP65 rating.

Energy Label    **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT CRI 35W G12 or HIT CRI 70W G12.
- Electronic ballast 220/240V 50/60Hz included.
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M20 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT   70 WATT 220-240V 50-60HZ ELECTRONIC IP65 5.00 KG UNIT GROSS WEIGHT	HIT-CRI – BASE G12	SEE BULB FEATURES	 40° FLOOD	<div><div></div> TEXTURED GREY</div> <div><div></div> MATT WHITE (ON REQUEST)</div> <div><div></div> MATT BLACK (ON REQUEST)</div>



## 401006 HYDROTECH MEDIUM 02 SQUARE LED

Square up&down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 5 CREE XP-G3 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 x 1.5W CREE "XP-G3" LED up and NR. 5 x 1.5W CREE "XP-G3" LED down.
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M20 rubber grommet Rutaseal® in EPDM
- Adjustable +/- 15 degrees.

**FullRGB**  
AVAILABLE ON REQUEST



LIGHT SOURCE		LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2X8 WATT 220-240V 50-60HZ ELECTRONIC IP65 3.00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	10°	2 X 720	90.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
			30°	2 X 684	85.50	
			45°	2 X 650	81.25	
		4.000°K NEUTRAL-WHITE	10°	2 X 750	93.75	
			30°	2 X 713	89.13	
			45°	2 X 677	84.63	


\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE








401018    HYDROTECH MEDIUM 02 SQUARE PRO LED

Square up&down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 5 CREE XP-L LED. IP65 rating.

Energy Label    A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 CREE "XP-L" LED up and NR. 5 CREE "XP-L" LED down.
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M20 rubber grommet Rutaseal® in EPDM
- Adjustable +/- 15 degrees.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2X14 WATT 220-240V 50-60HZ ELECTRONIC IP65 3.00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 10°	2 X 1.300	92.86	 TEXTURED GREY  MATT WHITE (ON REQUEST)  MATT BLACK (ON REQUEST)
			 30°	2 X 1.230	87.86	
			 45°	2 X 1.170	83.57	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE


## 401014 HYDROTECH MEDIUM 01 SQUARE LED

Square wall mounted luminaire for outdoor installation on a façade/wall, with light distribution downward only. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 x 1.5W CREE "XP-G3" LED down.
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M20 rubber grommet Rutaseal® in EPDM
- Adjustable +/- 15 degrees.

**FullRGB**  
AVAILABLE ON REQUEST



8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
3.00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	720	90.00	TEXTURED GREY
		30°	684	85.50	
		45°	650	81.25	MATT WHITE (ON REQUEST)
	4.000°K NEUTRAL-WHITE	10°	750	93.75	
		30°	713	89.13	
		45°	677	84.63	MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

401019    HYDROTECH MEDIUM 01 SQUARE PRO LED


Square wall mounted luminaire for outdoor installation on a façade/wall, with light distribution downward only. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-L LED. IP65 rating.








Energy Label    **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 CREE "XP-L" LED down.
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M20 rubber grommet Rutaseal® in EPDM
- Adjustable +/- 15 degrees.



**+70%**  
**LUMEN  
OUTPUT**



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
14 WATT 220-240V 50-60HZ ELECTRONIC IP65 3.00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 10°	1.300	92.86	 TEXTURED GREY  MATT WHITE (ON REQUEST)  MATT BLACK (ON REQUEST)
			 30°	1.230	87.86	
			 45°	1.170	83.57	



\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE




**401010 HYDROTECH MAXI 02 ROUND LED**

Round up&down luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 1 COB CREE "CXA2530" LED. IP65 rating.

**Energy Label** A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 39W COB CREE "CXA2530" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0,5 mt. neoprene power cable included




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2 X 39 WATT 220-240V 50-60HZ ELECTRONIC IP65 4,60 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 40°	2 X 4.000	102.56	 TEXTURED GREY




401011    HYDROTECH MAXI 02 SQUARE LED

Square up&down luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 1 COB CREE "CXA2530" LED. IP65 rating.

Energy Label    **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- NR. 2 x 39W COB CREE "CXA2530" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0,5 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2 X 39 WATT 220-240V 50-60HZ ELECTRONIC IP65 4,60 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 40°	2 X 4.000	102.56	 TEXTURED GREY



**401901 HYDROTECH MINI STEEL ROUND 01 LED**




**NEW**

Round wall mounted luminaire for outdoor installation on a façade/wall, with light distribution downward only. Luminaire completely made in mirrored stainless steel AISI 316L, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with nr. 1 CREE COB LED. IP65 rating.

**Energy Label** **A++**

- Material : mirrored stainless steel AISI 316L
- NR. 1 x 5W CREE COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
5 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,90 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 30°	480	96.00	 MIRRORED STAINLESS STEEL





**401902 HYDROTECH MINI STEEL ROUND 02 LED**



Round up&down luminaire for outdoor installation on a façade/wall. Luminaire completely made in mirrored stainless steel AISI 316L, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x CREE COB LED. IP65 rating.

**Energy Label** A++

- Material : mirrored stainless steel AISI 316L
- NR. 2 x 5W CREE COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.





	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2X5 WATT 220-240V 50-60HZ ELECTRONIC IP65 2,00 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	2 X 30°	2 X 480	96.00	MIRRORED STAINLESS STEEL




401903 HYDROTECH MEDIUM STEEL ROUND 01 LED NEW

Round wall mounted luminaire for outdoor installation on a façade/wall, with light distribution downward only. Luminaire completely made in mirrored stainless steel AISI 316L, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with nr. 1 CREE COB LED. IP65 rating.

Energy Label A++

- Material : mirrored stainless steel AISI 316L
- NR. 1 x 12W CREE COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
12 WATT 220-240V 50-60HZ ELECTRONIC IP65 4,90 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 30°	960	80.00	 MIRRORED STAINLESS STEEL



**401904 HYDROTECH MEDIUM STEEL ROUND 02 LED**



Round up&down luminaire for outdoor installation on a façade/wall. Luminaire completely made in mirrored stainless steel AISI 316L, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x CREE COB LED. IP65 rating.

**Energy Label** **A++**

- Material : mirrored stainless steel AISI 316L
- NR. 2 x 12W CREE COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2X12 WATT 220-240V 50-60HZ ELECTRONIC IP65 5,00 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	2 X 30°	2 X 960	80.00	MIRRORED STAINLESS STEEL



401701 HYDROECLIPSE MINI ROUND LED


NEW

Designed by **paolovilladesign**

Round wall surface-mounted luminaire creating a **diffused and discrete light through the fixture perimeter** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with low-power CREE LED. IP65 rating.

Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- M12 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
6 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,00 KG UNIT GROSS WEIGHT	LOW-POWER LED	3.000°K WARM-WHITE	360°	---	---	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE



401702 HYDROECLIPSE MINI SQUARE LED






Designed by paolovilladesign

Square wall surface-mounted luminaire creating a **diffused and discrete light through the fixture perimeter** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with low-power CREE LED. IP65 rating.

Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- M12 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
7 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,00 KG UNIT GROSS WEIGHT	LOW-POWER LED	3.000°K WARM-WHITE	360°	---	---	<div></div> TEXTURED GREY <div></div> MATT WHITE (ON REQUEST) <div></div> MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE


401703 HYDROECLIPSE MINI SQUARE 01 LED NEW






Designed by **paolovilla**design

Square wall surface-mounted luminaire creating a **mono-directional wall-washer lighting effect** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 6 mid-power CREE XH-G LED. IP65 rating.

Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- Electronic transformer 220/240V 50/60Hz included
- Nr. 6 mid-power CREE XH-G LED
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- M12 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
4 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,00 KG UNIT GROSS WEIGHT	MID-POWER LED	 3.000°K WARM-WHITE	 30°	350	87,50	 TEXTURED GREY  MATT WHITE (ON REQUEST)  MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE

401704 HYDROECLIPSE MINI SQUARE 02 LED


NEW

Designed by paolovilladesign

Square wall surface-mounted luminaire creating a **bi-directional (up&down) wall-washer lighting effect** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2x6 mid-power CREE XH-G LED. IP65 rating.

Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Electronic transformer 220/240V 50/60Hz included
- Nr. 2 x 6 mid-power CREE XH-G LED
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- M12 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
8 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,00 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	2 X 30°	2 X 350	87,50	<div></div> TEXTURED GREY <div></div> MATT WHITE (ON REQUEST) <div></div> MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL -WHITE

401705


HYDROECLIPSE MEDIUM ROUND LED

NEW

Round wall surface-mounted luminaire creating a **diffused and discrete light through the fixture perimeter** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with low-power CREE LED. IP65 rating.

Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- M16 rubber grommet Rutaseal® in EPDM



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
9 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,50 KG UNIT GROSS WEIGHT	LOW-POWER LED  3.000°K WARM-WHITE	 360°	---	---	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE



## 401706 HYDROECLIPSE MEDIUM SQUARE LED

NEW

Square wall surface-mounted luminaire creating a **diffused and discrete light through the fixture perimeter** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with low-power CREE LED. IP65 rating.

### Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- M16 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,50 KG UNIT GROSS WEIGHT	LOW-POWER LED	3.000°K WARM-WHITE	360°	---	---	<div></div> TEXTURED GREY <div></div> MATT WHITE (ON REQUEST) <div></div> MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE



401707 HYDROECLIPSE MEDIUM SQUARE 01 LED



Designed by **paolovilladesign**

Square wall surface-mounted luminaire creating a **mono-directional wall-washer lighting effect** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 14 mid-power CREE XH-G LED. IP65 rating.

**Energy Label** **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- Electronic transformer 220/240V 50/60Hz included
- Nr. 14 mid-power CREE XH-G LED
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- M16 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
8 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,50 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	30°	650	81.25	<div></div> TEXTURED GREY <div></div> MATT WHITE (ON REQUEST) <div></div> MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE

401708 HYDROECLIPSE MEDIUM SQUARE 02 LED





Designed by paolovilladesign

Square wall surface-mounted luminaire creating a **bi-directional (up&down) wall-washer lighting effect** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2x14 mid-power CREE XH-G LED. IP65 rating.

Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- Electronic transformer 220/240V 50/60Hz included
- Nr. 2 x 14 mid-power CREE XH-G LED
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- M16 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
16 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,50 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	2 X 30°	2 X 650	81.25	<div>■</div> TEXTURED GREY <div>□</div> MATT WHITE (ON REQUEST) <div>■</div> MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE





401709 HYDROECLIPSE LINEAR 350 LED




NEW

Designed by **paolovilladesign**

Rectangular wall surface-mounted luminaire creating a **diffused and discrete light through the fixture perimeter** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with low-power CREE LED. IP65 rating.

Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- M16 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
9 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,50 KG UNIT GROSS WEIGHT	LOW-POWER LED	3.000°K WARM-WHITE	360°	---	---	<div></div> TEXTURED GREY <div></div> MATT WHITE (ON REQUEST) <div></div> MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE

401710 HYDROECLIPSE LINEAR 600 LED






Designed by **paolovilla**design

Rectangular wall surface-mounted luminaire creating a **diffused and discrete light through the fixture perimeter** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with low-power CREE LED. IP65 rating.

Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- M16 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
18 WATT 220-240V 50-60HZ ELECTRONIC IP65 2,00 KG UNIT GROSS WEIGHT	LOW-POWER LED	3.000°K WARM-WHITE	360°	---	---	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: 4.000°K NEUTRAL-WHITE







## 401607 HYDROSURF MINI RECTANGULAR LED

NEW

Rectangular wall surface-mounted luminaire for outdoor installation on a wall, no recess needed. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 6 mid-power CREE XH-G LED. IP65 rating.

### Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 6 x CREE XH-G LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass
- M12 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
4 WATT 220-240V 50-60HZ ELECTRONIC IP65 0,60 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	FLOOR WASHER 180°	350	87.50	<div></div> TEXTURED GREY <div></div> MATT WHITE (ON REQUEST) <div></div> MATT BLACK (ON REQUEST)




## 401601 HYDROSURF MINI ROUND LED

Round wall surface-mounted luminaire for outdoor installation on a wall, no recess needed. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 6 mid-power CREE XH-G LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 6 x CREE XH-G LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass
- M12 rubber grommet Rutaseal® in EPDM




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
4 WATT 220-240V 50-60HZ ELECTRONIC IP65 0,60 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	FLOOR WASHER 180°	350	87.50	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>

## 401602 HYDROSURF MINI SQUARE LED


Square wall surface-mounted luminaire for outdoor installation on a wall, no recess needed. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 6 mid-power CREE XH-G LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 6 x CREE XH-G LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass
- M12 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
4 WATT 220-240V 50-60HZ ELECTRONIC IP65 0,60 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	FLOOR WASHER 180°	350	87.50	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>




401603 HYDROSURF MEDIUM ROUND LED

Round wall surface-mounted luminaire for outdoor installation on a wall, no recess needed. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 14 mid-power CREE XH-G LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 14 x CREE XH-G LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass
- M16 rubber grommet Rutaseal® in EPDM



35 mm



Ø 234 mm


	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
8 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,40 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	FLOOR WASHER 180°	650	81.25	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)

401604 HYDROSURF MEDIUM SQUARE LED

Square wall surface-mounted luminaire for outdoor installation on a wall, no recess needed. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 14 mid-power CREE XH-G LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 14 x CREE XH-G LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass
- M16 rubber grommet Rutaseal® in EPDM




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
8 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,40 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	FLOOR WASHER 180°	650	81.25	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)

401605 HYDROSURF MAXI ROUND LED

Round wall surface-mounted luminaire for outdoor installation on a wall, no recess needed. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 21 mid-power CREE XH-G LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 21 x CREE XH-G LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass
- M16 rubber grommet Rutaseal® in EPDM



40,5 mm

Ø 300 mm


	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
14 WATT 220-240V 50-60HZ ELECTRONIC IP65 2 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	FLOOR WASHER 180°	1.000	71.43	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)

401606    HYDROSURF MAXI SQUARE LED

Square wall surface-mounted luminaire for outdoor installation on a wall, no recess needed. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 21 mid-power CREE XH-G LED. IP65 rating.

Energy Label    A++

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 21 x CREE XH-G LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass
- M16 rubber grommet Rutaseal® in EPDM



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
14 WATT 220-240V 50-60HZ ELECTRONIC IP65 2 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	FLOOR WASHER 180°	1.000	71.43	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)


## 401608 HYDROSURF MAXI RECTANGULAR LED



Rectangular wall surface-mounted luminaire for outdoor installation on a wall, no recess needed. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 21 mid-power CREE XH-G LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 21 x CREE XH-G LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass
- M16 rubber grommet Rutaseal® in EPDM




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
14 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,70 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	FLOOR WASHER 180°	1.000	71.43	<div></div> TEXTURED GREY <div></div> MATT WHITE (ON REQUEST) <div></div> MATT BLACK (ON REQUEST)



## 401801-02-03 HYDROFLEX MINI LED




1.000 / 3.000 / 5.000 mm length,  
10mm x 10mm section, opal encapsulated  
flexible LED strip for linear lighting  
(straight or bended) outdoor  
and indoor wall-recessed installation;  
surface mounted version through installation  
accessories to be ordered separately.  
LED circuit completely encapsulated  
with UV and high-temperatures resistant  
Polyurethane sheath, with white (outside)  
and milky finish (over light emission),  
dot free and homogeneous light emission  
surface. Double power cable with male/  
female connectors included,  
suitable for in-line installation.  
Cutttable each 41,67 mm.  
Remote driver 24V DC needed.  
With low-power SMD3014 Lumileds LED.  
IP68 rating.



### Energy Label A++

- Material: high performances Polyurethane, UV resistant, saltwater resistant.
- No yellowish after years
- Dot-free and homogeneous light emission.
- 24V DC remote driver needed
- Supplied with Male/Female connectors for in-line installation.



## 401801 HYDROFLEX MINI 1000 LED



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 24V DC IP68	LOW-POWER LED	3.000°K WARM-WHITE	DIFFUSED	750	75.00	MILKY

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: 4.000°K NEUTRAL-WHITE

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	1
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 – MAX 2
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 – MAX 5
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 – MAX 9

**401802 HYDROFLEX MINI 3000 LED**



300 cm



AVAILABLE ON REQUEST

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
30 WATT 24V DC IP68	LOW-POWER LED	3.000°K WARM-WHITE	DIFFUSED	2.250	75.00	<input type="checkbox"/> MILKY

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ☐ 4.000°K NEUTRAL-WHITE

**REMOTE DRIVER SELECTION**

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	1
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 – MAX 3

**401803 HYDROFLEX MINI 5000 LED**



500 cm



AVAILABLE ON REQUEST

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
50 WATT 24V DC IP68	LOW-POWER LED	3.000°K WARM-WHITE	DIFFUSED	3.750	75.00	<input type="checkbox"/> MILKY

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ☐ 4.000°K NEUTRAL-WHITE

**REMOTE DRIVER SELECTION**

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	1

**AC028 MOUNTING CLIP FOR HYDROFLEX MINI**



Mounting clip for Hydroflex Mini, realized in Stainless steel, clip to be applied every 40 cm, to secure with screws. Ideal for bended installation on a wall or ceiling.



**AC029 ALUMINUM LINEAR PROFILE FOR HYDROFLEX MINI**



1.000 mm Linear profile for Hydroflex Mini, realized in Anodized aluminum, supplied with nr. 2 clips to be applied every 40 cm, to secure with screws. Ideal for straight installation on a wall or ceiling.



**AC030 END CAP FOR HYDROFLEX MINI**



End cap for Hydroflex Mini, realized in Polyurethane, to be applied at the end of the line, after Hydroflex cut.










**401804-05 HYDROFLEX SIDE LED**

**NEW**

1.000 / 4.000 mm length, 20mm x 12mm section, opal encapsulated flexible LED strip for linear lighting (straight or bended) outdoor and indoor wall-recessed installation; surface mounted version through installation accessories to be ordered separately. LED circuit completely encapsulated with UV and high-temperatures resistant Polyurethane sheath, with white (outside) and milky finish (over light emission), dot free and homogeneous light emission surface. Double power cable with male/female connectors included, suitable for in-line installation. Cuttable each 50 mm. Remote driver 24V DC needed. With low-power SMD3014 Lumileds LED. IP68 rating.

**Energy Label** **A++**


- Material: high performances Polyurethane, UV resistant, saltwater resistant.
- No yellowish after years
- Dot-free and homogeneous light emission.
- 24V DC remote driver needed
- Supplied with Male/Female connectors for in-line installation.






401804 HYDROFLEX SIDE 1000 LED







100 cm



AVAILABLE ON REQUEST

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 24V DC IP68	LOW-POWER LED	 3.000°K WARM-WHITE	DIFFUSED	750	75.00	 MILKY
* OTHER LIGHT COLORS AVAILABLE ON REQUEST:  4.000°K NEUTRAL WHITE, RGB						


REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
 MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	1
 MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 - MAX 2
 MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 5
 MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 - MAX 9




401805 HYDROFLEX SIDE 4000 LED





400 cm



AVAILABLE ON REQUEST

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
40 WATT 24V DC IP68	LOW-POWER LED	 3.000°K WARM-WHITE	DIFFUSED	2.250	75.00	 MILKY
* OTHER LIGHT COLORS AVAILABLE ON REQUEST:  4.000°K NEUTRAL WHITE						

REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
 MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	1
 MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 - MAX 2

AC031 MOUNTING CLIP FOR HYDROFLEX SIDE



Mounting clip for Hydroflex Side realized in Stainless steel, clip to be applied every 40 cm, to secure with screws. Ideal for bended installation on a wall or ceiling.



AC032 ALUMINUM LINEAR PROFILE FOR HYDROFLEX SIDE



1.000 mm Linear profile for Hydroflex Side, realized in Anodized aluminum, supplied with nr. 2 clips to be applied every 40 cm, to secure with screws. Ideal for straight installation on a wall or ceiling.



AC033 END CAP FOR HYDROFLEX SIDE



End cap for Hydroflex Side, realized in Polyurethane, to be applied at the end of the line, after Hydroflex cut.








**401806-07 HYDROFLEX TOP LED**

**NEW**

1.000 / 4.000 mm length, 16mm x 15 mm section, opal encapsulated flexible LED strip for linear lighting (straight or bended) outdoor and indoor wall-recessed installation; surface mounted version through installation accessories to be ordered separately. LED circuit completely encapsulated with UV and high-temperatures resistant Polyurethane sheath, with white (outside) and milky finish (over light emission), dot free and homogeneous light emission surface. Double power cable with male/female connectors included, suitable for in-line installation. Cuttable each 50 mm. Remote driver 24V DC needed. With low-power SMD3014 Lumileds LED. IP68 rating.

**Energy Label** **A++**

- Material: high performances Polyurethane, UV resistant, saltwater resistant.
- No yellowish after years
- Dot-free and homogeneous light emission.
- 24V DC remote driver needed
- Supplied with Male/Female connectors for in-line installation.



## 401806 HYDROFLEX TOP 1000 LED



100 cm



AVAILABLE ON REQUEST

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 24V DC IP68	LOW-POWER LED	3.000°K WARM-WHITE	DIFFUSED	750	75.00	<input type="checkbox"/> MILKY

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ☐ 4.000°K NEUTRAL-WHITE, RGB

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	1
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 – MAX 2
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 – MAX 5
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 – MAX 9

## 401807 HYDROFLEX TOP 4000 LED



300 cm



AVAILABLE ON REQUEST

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
40 WATT 24V DC IP68	LOW-POWER LED	3.000°K WARM-WHITE	DIFFUSED	2.250	75.00	<input type="checkbox"/> MILKY

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ☐ 4.000°K NEUTRAL-WHITE

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	1
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 – MAX 2

## AC034 MOUNTING CLIP FOR HYDROFLEX TOP



Mounting clip for Hydroflex Top, realized in Stainless steel, clip to be applied every 40 cm, to secure with screws. Ideal for bended installation on a wall or ceiling.



## AC035 ALUMINUM LINEAR PROFILE FOR HYDROFLEX TOPSIDE



1.000 mm Linear profile for Hydroflex Top, realized in Anodized aluminum, supplied with nr. 2 clips to be applied every 40 cm, to secure with screws. Ideal for straight installation on a wall or ceiling.



## AC036 END CAP FOR HYDROFLEX TOP



End cap for Hydroflex Top, realized in Polyurethane, to be applied at the end of the line, after Hydroflex cut.





## 402001 HYDROBRACKET MINI LED

Round up or down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 3 CREE XP-G3 LED. IP67 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 3 x 1W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection against impact IK09 (10 joule)
- M20 cable gland.
- Adjustable +/- 15 degrees.
- 3 mt. neoprene power cable included




3 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
1.25 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	346	115.33	<div>TEXTURED GREY</div> <div>MATT BLACK</div>
		30°	329	109.66	
		45°	312	104.00	
	4.000°K NEUTRAL-WHITE	10°	360	120.00	
		30°	342	114.00	
		45°	325	108.33	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ● BLUE

### 402003 HYDROBRACKET MINI LED - EXTENSIBLE BRACKET

- High corrosion resistance  
die-cast aluminum body  
and bracket
- Polyester painting  
with phosphocromating pre-finish



#### AVAILABLE COLOURS

- TEXTURE
- BLACK

### 402005 HYDROBRACKET MINI LED - VISOR

- High corrosion resistance  
die-cast aluminum  
body and bracket
- Polyester painting  
with phosphocromating pre-finish



#### AVAILABLE COLOURS

- TEXTURE
- BLACK

### 402007 HYDROBRACKET MINI LED - EARTH SPIKE

- High corrosion resistance  
die-cast aluminum body and bracket
- Polyester painting  
with phosphocromating pre-finish
- Earth Spike made in plastic material




#### AVAILABLE COLOURS




- TEXTURE
- BLACK

402002P HYDROBRACKET MINI GU10

Round up or down luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. GU10 LED / halogen. IP67 rating.


- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- GU10 base, MAX 50W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection against impact IK09 (10 joule)
- M20 cable gland.
- Adjustable +/- 15 degrees.



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
50 WATT MAX 220-240V 50-60HZ IP65 1.20 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	 TEXTURED GREY  MATT BLACK

### 402004P HYDROBRACKET MINI GU 10 - EXTENSIBLE BRACKET

- High corrosion resistance  
die-cast aluminum body  
and bracket
- Polyester painting  
with phosphocromating pre-finish



#### AVAILABLE COLOURS

- TEXTURE
- BLACK

### 402006P HYDROBRACKET MINI GU 10 - VISOR

- High corrosion resistance  
die-cast aluminum  
body and bracket
- Polyester painting  
with phosphocromating pre-finish



#### AVAILABLE COLOURS

- TEXTURE
- BLACK

### 402008P HYDROBRACKET MINI GU 10 - EARTH SPIKE

- High corrosion resistance  
die-cast aluminum body and bracket
- Polyester painting  
with phosphocromating pre-finish
- Earth Spike made in plastic material



#### AVAILABLE COLOURS

- TEXTURE
- BLACK

## 402009 HYDROBRACKET MEDIUM LED

Round up or down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP67 rating.

### Energy Label **A++**



- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- M20 cable gland.
- Adjustable +/- 15 degrees.
- 1 mt. neoprene power cable included



1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST



AVAILABLE ON REQUEST




LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	 3.000°K WARM-WHITE	10°	720	90.00	TEXTURED GREY MATT BLACK
		30°	684	85.50	
		45°	650	81.25	
	 4.000°K NEUTRAL-WHITE	10°	750	93.75	
		30°	713	89.13	
		45°	677	84.63	

8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
2.20 KG UNIT GROSS WEIGHT

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

## 402011 HYDROBRACKET MEDIUM LED - EXTENSIBLE BRACKET

- High corrosion resistance  
die-cast aluminum body  
and bracket
- Polyester painting  
with phosphochromating pre-finish



### AVAILABLE COLOURS

- TEXTURE
- BLACK

## 402013 HYDROBRACKET MEDIUM LED - VISOR

- High corrosion resistance  
die-cast aluminum  
body and bracket
- Polyester painting  
with phosphochromating pre-finish



### AVAILABLE COLOURS

- TEXTURE
- BLACK

## 402015 HYDROBRACKET MEDIUM LED - EARTH SPIKE

- High corrosion resistance  
die-cast aluminum body and bracket
- Polyester painting  
with phosphochromating pre-finish
- Earth Spike made in plastic material



### AVAILABLE COLOURS

- TEXTURE
- BLACK

## 402017 HYDROBRACKET MAXI LED

Round up or down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-G3 LED. IP67 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- M20 cable gland.
- Adjustable +/- 15 degrees.
- 1 mt. neoprene power cable included




1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST



AVAILABLE ON REQUEST



12 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
5.00 KG UNIT GROSS WEIGHT




LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	 3.000°K WARM-WHITE	10°	1.152	96.00	TEXTURED GREY MATT BLACK
		30°	1.095	91.25	
		45°	1.040	86.67	
	 4.000°K NEUTRAL-WHITE	10°	1.200	100.00	
		30°	1.140	95.00	
		45°	1.083	90.25	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

## 402019 HYDROBRACKET MAXI LED - EXTENSIBLE BRACKET

- High corrosion resistance  
die-cast aluminum body  
and bracket
- Polyester painting  
with phosphocromating pre-finish



### AVAILABLE COLOURS

- TEXTURE
- BLACK

## 402021 HYDROBRACKET MAXI LED - VISOR

- High corrosion resistance  
die-cast aluminum  
body and bracket
- Polyester painting  
with phosphocromating pre-finish



### AVAILABLE COLOURS

- TEXTURE
- BLACK

## 402023 HYDROBRACKET MAXI LED - EARTH SPIKE

- High corrosion resistance  
die-cast aluminum body and bracket
- Polyester painting  
with phosphocromating pre-finish
- Earth Spike made in plastic material



### AVAILABLE COLOURS

- TEXTURE
- BLACK

402018 HYDROBRACKET MAXI G12

Round up or down luminaire for outdoor installation on a façade/wall. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in ballast 230V 50Hz, G12 35W or 70W metal halide. IP67 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT CRI 35W G12 or HIT CRI 70W G12
- Conventional ballast 230V 50Hz
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- M20 cable gland.
- Adjustable +/- 15 degrees.



SPOT 10° REFLECTOR  
(STANDARD)



SUPERSPOT 4°  
REFLECTOR  
(OPTION)





FLOOD 23°  
REFLECTOR  
(OPTION)



AC004 - LIGHT GRID  
(ACCESSORY)




AC002 - DARK-LIGHT ATTACHMENT  
(ACCESSORY)



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT   70 WATT HIT-CRI – BASE G12 230V 50HZ IP65 6.00 KG UNIT GROSS WEIGHT	HIT-CRI – BASE G12	SEE BULB FEATURES	4° SUPER-NARROW (ON REQUEST)	TEXTURED GREY MATT BLACK
			10° NARROW	
			23° FLOOD (ON REQUEST)	

## 402020 HYDROBRACKET MAXI G12 - EXTENSIBLE BRACKET

- High corrosion resistance die-cast aluminum body and bracket
- Polyester painting with phosphocromating pre-finish



### AVAILABLE COLOURS


-  TEXTURE
-  BLACK

## 402022 HYDROBRACKET MAXI G12 - VISOR

- High corrosion resistance die-cast aluminum body and bracket
- Polyester painting with phosphocromating pre-finish



### AVAILABLE COLOURS


-  TEXTURE
-  BLACK

## 402024 HYDROBRACKET MAXI G12 - EARTH SPIKE

- High corrosion resistance die-cast aluminum body and bracket
- Polyester painting with phosphocromating pre-finish
- Earth Spike made in plastic material



### AVAILABLE COLOURS

-  TEXTURE
-  BLACK

## 403003 HYDROLINE-B 13 PERFORMANCE LED


Linear luminaire for outdoor installation on a façade/wall, length 610mm. Phospho-chromatised and polyester powder coated extruded copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 13 CREE XP-G3 LED. IP67 rating.

### Energy Label **A++**


- Material: high corrosion resistance extruded copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- NR. 13 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection against impact IK10 (20 joule)
- Double PG13.5 cable gland
- 1 mt. neoprene power cable included.



### STANDARD BRACKET (INCLUDED)





### AC003 EXTENSIBLE BRACKETS FOR HYDROLINE-B DIE-CAST ALUMINUM (OPTION TO BE ORDERED SEPARATELY)











**1...10 V** **DALI**  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST


**RGB**  
AVAILABLE ON REQUEST



19.5 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
4.30 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	 10°	1.872	96.00	 TEXTURED GREY  MATT BLACK (ON REQUEST)
		 30°	1.779	91.25	
		 45°	1.690	86.67	
	4.000°K NEUTRAL-WHITE	 10°	1.950	100.00	
		 30°	1.853	95.00	
		 45°	1.760	90.25	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST:  BLUE



## 403004 HYDROLINE-B 21 PERFORMANCE LED


Linear luminaire for outdoor installation on a façade/wall, length 910mm. Phospho-chromatised and polyester powder coated extruded copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 21 CREE XP-G3 LED. IP67 rating.

### Energy Label **A++**



- Material: high corrosion resistance extruded copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 21 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection against impact IK10 (20 joule)
- Double PG13.5 cable gland
- 1 mt. neoprene power cable included.



#### STANDARD BRACKET (INCLUDED)




#### AC003 EXTENSIBLE BRACKETS FOR HYDROLINE-B DIE-CAST ALUMINUM (OPTION TO BE ORDERED SEPARATELY)



**1...10 V** **DALI**  
1-10 V DIMMABLE / DALI VERSION  
AVAILABLE ON REQUEST

**RGB**  
AVAILABLE ON REQUEST



31.5 WATT  
220-240V 50-60HZ ELECTRONIC  
IP67  
6.50 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	3.024	96.00	TEXTURED GREY MATT BLACK (ON REQUEST)
		30°	2.873	91.25	
		45°	2.729	86.67	
	4.000°K NEUTRAL-WHITE	10°	3.150	100.00	
		30°	2.993	95.00	
		45°	2.843	90.25	


\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE



## 404005 HYDROSPLIT SQUARE 01 LED

Square up or down luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x 3 CREE XP-G3 LED. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 3 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- Cable gland PG11



4.5 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
3.80 KG UNIT GROSS WEIGHT



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	432	96.00	<div> TEXTURED GREY</div> <div> MATT WHITE (ON REQUEST)</div> <div> MATT BLACK (ON REQUEST)</div>
		30°	410	91.12	
		45°	390	18.06	
	4.000°K NEUTRAL-WHITE	10°	450	100.00	
		30°	428	95.12	
		45°	406	90.23	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE


404001P HYDROSPLIT SQUARE 01 G8.5






Square up or down luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in electronic ballast 220-240V 50-60Hz, 1 x G8.5 35W metal halide. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT-TC CRI G8.5 35W
- Built-in electronic ballast 220/240V 50/60Hz
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- Cable gland PG11



LIGHT UP OR DOWN




	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT 220-240V 50-60HZ ELECTRONIC IP65 6.40 KG UNIT GROSS WEIGHT	 HIT-TC CRI 35W G8.5	SEE BULB FEATURES	 45° FLOOD	 TEXTURED GREY  MATT WHITE (ON REQUEST)  MATT BLACK (ON REQUEST)

## 404006 HYDROSPLIT SQUARE 02 G8.5

Square up and down luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 3 CREE XP-G3 LED. IP65 rating.

### Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 3 x 1.5W CREE "XP-G3" LED up and NR. 3 x 1.5W CREE "XP-G3" LED down.
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- Cable gland PG11



9 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
3.90 KG UNIT GROSS WEIGHT



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	2 X 432	96.00	<div>  TEXTURED GREY </div> <div>  MATT WHITE (ON REQUEST) </div> <div>  MATT BLACK (ON REQUEST) </div>
		30°	2 X 410	91.12	
		45°	2 X 390	18.06	
	4.000°K NEUTRAL-WHITE	10°	2 X 450	100.00	
		30°	2 X 428	95.12	
		45°	2 X 406	90.23	




404002P HYDROSPLIT SQUARE 02 G8.5

Square up and down luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in electronic ballast 220-240V 50-60Hz, 1 x G8.5 35W metal halide. IP65 rating.






- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT-TC CRI G8.5 35W
- Built-in electronic ballast 220/240V 50/60Hz
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- Cable gland PG11



LIGHT UP AND DOWN



173 x 173 mm



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT 220-240V 50-60HZ ELECTRONIC IP65 6.40 KG UNIT GROSS WEIGHT	 HIT-TC CRI 35W G8.5	SEE BULB FEATURES	 45° FLOOD	 TEXTURED GREY  MATT WHITE (ON REQUEST)  MATT BLACK (ON REQUEST)

405002 HYDROLED 01


Square up or down luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 CREE XP-G3 LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 1W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M12 rubber grommet Rutaseal® in EPDM



COULD BE USED WITHOUT COVER TOO



1 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
1.00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	115	115.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		30°	110	110.00	
		45°	104	104.00	
	4.000°K NEUTRAL-WHITE	10°	120	120.00	
		30°	114	114.00	
		45°	109	109.00	


\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE

**405003 HYDROLED 02**

Square up and down luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 1 CREE XP-G3 LED. IP65 rating.

**Energy Label** **A++**


- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 1W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws.
- Silicone rubber gasket.
- Tempered safety glass.
- M12 rubber grommet Rutaseal® in EPDM



2 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
2.30 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	2 X 115	115.00	<div> TEXTURED GREY</div> <div> MATT WHITE (ON REQUEST)</div> <div> MATT BLACK (ON REQUEST)</div>
		30°	2 X 110	110.00	
		45°	2 X 104	104.00	
	4.000°K NEUTRAL-WHITE	10°	2 X 120	120.00	
		30°	2 X 114	114.00	
		45°	2 X 109	109.00	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: BLUE







## 401401 HYDROMASK 01 LED

Wall-mounting luminaire for outdoor installation, with 1 side 120° light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x 5W COB LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminium body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 5W COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered glass diffuser
- 1 mt. power cable included.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
5 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,00 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 120°	350	70.00	 TEXTURED GREY





## 401402 HYDROMASK 02 LED


Wall-mounting luminaire for outdoor installation, with 2 sides 120° light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 5W COB LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 5W COB CREE LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered glass diffuser



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,30 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	2 X 120°	2 X 350	70.00	TEXTURED GREY





## 406003 HYDROTARGET-3 LED

200 mm LED bar for outdoor installation on a wall; installation with two fixing holders, adjustable through 180°. Phospho-chromatised and polyester powder coated extruded aluminium body, tempered safety glass and stainless steel screws. Double power cable with male/female quick couplings included, suitable for in-line installation. Remote driver 24V DC needed. With nr. 15 low-power SMD5050 LED. IP65 rating.

### Energy Label **A++**


- Material: high corrosion resistance extruded aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 15 x 0.2W Epistar SMD5050 LED.
- Tempered safety glass, 3 mm thickness.
- Adjustable through 180 degrees.
- Double power cables included, supplied with male/female quick coupling for in-line installation



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
3 WATT 24V DC IP65 0.20 KG UNIT GROSS WEIGHT	SMD5050 LED	3.000°K WARM-WHITE	120°	90	30.00	TEXTURED GREY

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	MIN 1 - MAX 4
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 - MAX 5
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 9
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 - MAX 15





## 406004 HYDROTARGET-6 LED

500 mm LED bar for outdoor installation on a wall; installation with two fixing holders, adjustable through 180°. Phospho-chromatised and polyester powder coated extruded aluminium body, tempered safety glass and stainless steel screws. Double power cable with male/female quick couplings included, suitable for in-line installation. Remote driver 24V DC needed. With nr. 30 low-power SMD5050 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance extruded aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 30 x 0.2W Epistar SMD5050 LED.
- Tempered safety glass, 3 mm thickness.
- Adjustable through 180 degrees.
- Double power cables included, supplied with male/female quick coupling for in-line installation



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
6 WATT 24V DC IP65 0.30 KG UNIT GROSS WEIGHT	SMD5050 LED	3.000°K WARM-WHITE	120°	180	30.00	TEXTURED GREY

### REMOTE DRIVER SELECTION


BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	MIN 1 - MAX 3
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 - MAX 5
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 9

## 406005 HYDROTARGET-12 LED

1.000 mm LED bar for outdoor installation on a wall; installation with two fixing holders, adjustable through 180°. Phospho-chromatised and polyester powder coated extruded aluminium body, tempered safety glass and stainless steel screws. Double power cable with male/female quick couplings included, suitable for in-line installation. Remote driver 24V DC needed. With nr. 60 low-power SMD5050 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance extruded aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 60 x 0.2W Epistar SMD5050 LED.
- Tempered safety glass, 3 mm thickness.
- Adjustable through 180 degrees.
- Double power cables included, supplied with male/female quick coupling for in-line installation



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
12 WATT 24V DC IP65 0.55 KG UNIT GROSS WEIGHT	SMD5050 LED	3.000°K WARM-WHITE	120°	360	30.00	TEXTURED GREY

### REMOTE DRIVER SELECTION


BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	1
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 - MAX 2
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 4
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100W	IP67	MIN 1 - MAX 8

# 401301 HYDRODISK 02 LED

Round luminaire for outdoor installation on a façade/wall. "V-type" 2 ways light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, PMMA diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 1 high-power LED. IP65 rating.

## Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 1W LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- PMMA diffuser
- 1 mt. neoprene power cable included



V - LIGHTING DISTRIBUTION, LIGHT BEAMS POSITIONED AT 90 DEGREES

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2 WATT 220-240V 50-60HZ ELECTRONIC IP65 0,70 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	2 X 5°	2 X 80	80.00	MATT BLACK




401302 HYDRODISK 04 LED

Round luminaire for outdoor installation on a façade/wall. “X-type” 4 ways light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 4 x 1 high-power LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 4 x 1W LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- PMMA diffuser
- 1 mt. neoprene power cable included



X - LIGHTING DISTRIBUTION, LIGHT BEAMS POSITIONED AT 90 DEGREES



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
4 WATT 220-240V 50-60HZ ELECTRONIC IP65 0,80 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	4 X 5°	4 X 80	80.00	MATT BLACK

401303 HYDRODISK 08 LED

Round luminaire for outdoor installation on a façade/wall. “8-lights type” 8 ways light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 8 x 1 high-power LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 x 1W LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- PMMA diffuser
- 1 mt. neoprene power cable included



8-LIGHTS – LIGHTING DISTRIBUTION, LIGHT BEAMS POSITIONED AT 45 DEGREES

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
8 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	8 X 5°	8 X 80	80.00	MATT BLACK





# Wall Recessed



501000 HYDROBLADE

page. **226**



502000 HYDROSTEP

page. **227**




## 501001 HYDROBLADE COMPACT ROUND LED

Recessed round luminaire for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 high-power LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- Stainless steel AISI 304 trim.
- NR. 1 x 1W LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection against impact IK09 (10 joule)
- Double cable gland PG11
- Polypropylene recessing box included.
- 1 mt. neoprene power cable included

2 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
1.40 KG UNIT GROSS WEIGHT



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	SPOT DIRECTIONAL	96	48.00	STAINLESS STEEL
	4.000°K NEUTRAL-WHITE	SPOT DIRECTIONAL	100	50.00	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ● BLUE


## 501002 HYDROBLADE COMPACT SQUARE LED

Recessed square luminaire for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 high-power LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- Stainless steel AISI 304 trim.
- NR. 1 x 1W LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection against impact IK09 (10 joule)
- Double cable gland PG11
- Polypropylene recessing box included.
- 1 mt. neoprene power cable included

2 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
1.40 KG UNIT GROSS WEIGHT





LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	SPOT DIRECTIONAL	96	48.00	STAINLESS STEEL
	4.000°K NEUTRAL-WHITE	SPOT DIRECTIONAL	100	50.00	




502014 HYDROSTEP – TONDO – T 03 LED

Recessed round steplight for outdoor installation in the wall, stainless steel AISI 316 body and frame, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 high-power CREE LED. IP65 rating.

Energy Label A++

- Stainless Steel AISI 316 body and frame.
- NR. 1 x 1W CREE LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Protection against impact IK09 (10 joule)
- Polypropilene recessing box included.
- 0.2 mt. neoprene power cable included





	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
1 WATT 220-240V 50-60HZ ELECTRONIC IP65 0.60 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 80° ASYMMETRIC	60	60.00	 TEXTURED GREY




502015 HYDROSTEP – QUADRO – Q 03 LED

Recessed square steplight for outdoor installation in the wall, stainless steel AISI 316 body and frame, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 high-power CREE LED. IP65 rating.

Energy Label A++

- Stainless Steel AISI 316 body and frame.
- NR. 1 x 1W CREE LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Protection against impact IK09 (10 joule)
- Polypropilene recessing box included.
- 0.2 mt. neoprene power cable included







	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
1 WATT 220-240V 50-60HZ ELECTRONIC IP65 0.60 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 80° ASYMMETRIC	60	60.00	 TEXTURED GREY

## 502001P HYDROSTEP T/01 TONDO

Recessed round steplight for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered safety glass, moulded silicone gasket and stainless steel screws. Remote transformer needed, G4 20W LED / halogen. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- 2 pins G4 base, MAX 20W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety fully frosted glass.
- Protection against impact IK09 (10 joule)
- Polypropylene recessing box included.







	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20 WATT MAX 12V IP54 0.50 KG UNIT GROSS WEIGHT	 G4 LED / HALOGEN	SEE BULB FEATURES	 FLOOD	 TEXTURED GREY

## 502002P HYDROSTEP T/02 TONDO

Recessed round steplight for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered safety glass, moulded silicone gasket and stainless steel screws. Remote transformer needed, G4 20W LED / halogen. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- 2 pins G4 base, MAX 20W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety fully frosted glass.
- Protection against impact IK09 (10 joule)
- Polypropylene recessing box included.







	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20 WATT MAX 12V IP54 0.50 KG UNIT GROSS WEIGHT	 G4 LED / HALOGEN	SEE BULB FEATURES	 FLOOD	 TEXTURED GREY

502003P HYDROSTEP Q/05 QUADRO

Recessed square steplight for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered safety glass, moulded silicone gasket and stainless steel screws. Remote transformer needed, G4 20W LED / halogen. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- 2 pins G4 base, MAX 20W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety fully frosted glass.
- Protection against impact IK09 (10 joule)
- Polypropylene recessing box included.







	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20 WATT MAX 12V IP54 0.60 KG UNIT GROSS WEIGHT	 G4 LED / HALOGEN	SEE BULB FEATURES	 DIRECTIONAL	 TEXTURED GREY

502004P HYDROSTEP – ES/08 RETTANGOLO

Recessed rectangular steplight for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in transformer 230V 50Hz G24d-1 10W compact fluorescent. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety fully frosted glass.
- Protection against impact IK09 (10 joule)
- Polypropylene recessing box included.







	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
10 WATT 230V 50HZ IP54 1.30 KG UNIT GROSS WEIGHT	 ES TC-D – G24D-1	SEE BULB FEATURES	 DIRECTIONAL	 TEXTURED GREY

## 502007P HYDROSTEP – RETTANGOLO – GU10

Recessed rectangular steplight for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered safety glass, moulded silicone gasket and stainless steel screws. GU10 LED / halogen. IP65 rating.


- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection against impact IK09 (10 joule)
- Polypropylene recessing box included.



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT MAX 220-240V 50-60HZ IP55 1.20 KG UNIT GROSS WEIGHT	 GU10 LED / HALOGEN	SEE BULB FEATURES	 DIRECTIONAL	 DARK-GREY




## 502005 HYDROSTEP – QUADRO Q 01 LED

Square steplight for outdoor surface installation on the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 3 high-power LED. IP65 rating.



### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 3 x 1W CREE LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket


	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
3 WATT 220-240V 50-60HZ ELECTRONIC IP55 0.90 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 10°	240	80.00	 MATT BLACK




502006 HYDROSTEP – QUADRO Q 02 LED

Square steplight for outdoor surface installation on the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 3 high-power LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- NR. 3 x 1W CREE LED up and NR. 3 x 1W CREE LED down.
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
6 WATT 220-240V 50-60HZ ELECTRONIC IP55 1.00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 10°	2 X 240	80.00	 MATT BLACK




## 502018 HYDROSTEP – QUADRO – Q 04 LED




Recessed linear steplight for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered frosted glass diffuser, polypropilene housing for recess, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 24 low-power SMD3528 LED. IP65 rating.



### Energy Label **A++**



- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 24 x SMD3528 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.50 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
3 WATT 220-240V 50-60HZ ELECTRONIC IP65 0,85 KG UNIT GROSS WEIGHT	SMD3528	 3.000°K WARM-WHITE	 120°	70	23.33	 TEXTURED GREY




## 502019 HYDROSTEP – QUADRO – Q 06 LED

Recessed linear steplight for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered frosted glass diffuser, polypropilene housing for recess, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 18 low-power SMD3528 LED. IP65 rating.



### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 18 x SMD3528 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.50 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2 WATT 220-240V 50-60HZ ELECTRONIC IP65 0,90 KG UNIT GROSS WEIGHT	SMD3528	 3.000°K WARM-WHITE	 120°	50	25.00	 TEXTURED GREY

## 502010 HYDROSTEP - LINEAR 01 - LED

Recessed linear steplight for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, stainless steel frame, tempered frosted glass diffuser, polypropilene housing for recess, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 54 low-power SMD3528 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 frame.
- NR. 54 x SMD3528 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety fully frosted glass.
- Protection against impact IK09 (10 joule)
- Polypropilene recessing box included.
- 0.5 mt. neoprene power cable included





	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
7 WATT 220-240V 50-60HZ ELECTRONIC IP65 1.20 KG UNIT GROSS WEIGHT	SMD3528 LED	3.000°K WARM-WHITE	100°	140	20.00	STAINLESS STEEL

## 502011 HYDROSTEP - LINEAR 02 - LED

Recessed linear steplight for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, stainless steel frame and grid, tempered frosted glass diffuser, polypropilene housing for recess, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 54 low-power SMD3528 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 frame.
- NR. 54 x SMD3528 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety fully frosted glass.
- Protection against impact IK09 (10 joule)
- Polypropilene recessing box included.
- 0.5 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
7 WATT 220-240V 50-60HZ ELECTRONIC IP65 1.20 KG UNIT GROSS WEIGHT	SMD3528 LED	3.000°K WARM-WHITE	100°	80	11.43	STAINLESS STEEL


## 502012 HYDROSTEP – LINEAR 03 - LED

Recessed linear steplight for outdoor installation in the wall, asymmetrical light distribution, phosphochromatised and polyester powder coated die-cast copper-free aluminium body, stainless steel frame, tempered clear glass, polypropylene housing for recess, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 3 high-power OSRAM LED. IP65 rating.



### Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 frame.
- NR. 3 x OSRAM LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection against impact IK09 (10 joule)
- Polypropylene recessing box included.
- 0.5 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
3 WATT 220-240V 50-60HZ ELECTRONIC IP65 0.90 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	45°X 35° ASYMMETRIC	230	76.67	STAINLESS STEEL


## 502013 HYDROSTEP – LINEAR 04 - LED

Recessed linear steplight for outdoor installation in the wall, asymmetrical light distribution, phosphochromatised and polyester powder coated die-cast copper-free aluminium body, stainless steel frame, tempered clear glass, polypropylene housing for recess, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 6 high-power OSRAM LED. IP65 rating.



### Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel AISI 304 frame.
- NR. 6 x OSRAM LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Protection against impact IK09 (10 joule)
- Polypropylene recessing box included.
- 0.5 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
6 WATT 220-240V 50-60HZ ELECTRONIC IP65 1.30 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	45°X 35° ASYMMETRIC	410	68.34	STAINLESS STEEL


## 502016 HYDROSTEP – LINEAR – 05 LED

Recessed linear steplight for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered frosted glass diffuser, polypropylene housing for recess, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 54 low-power SMD3528 LED. IP65 rating.



### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 54 x SMD3528 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.50 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
7 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,05 KG UNIT GROSS WEIGHT	SMD3528	3.000°K WARM-WHITE	120°	140	20.00	TEXTURED GREY


## 502017 HYDROSTEP – LINEAR – 06 LED

Recessed linear steplight for outdoor installation in the wall, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered frosted glass diffuser, polypropylene housing for recess, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 15 low-power SMD5630 LED. IP65 rating.



### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 15 x SMD5630 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.50 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
7 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,00 KG UNIT GROSS WEIGHT	SMD5630	3.000°K WARM-WHITE	120°	180	25.71	TEXTURED GREY





# Bollards



609001 HYDROBOULEVARD

page. **238**



608001 HYDROSURF BOLLARD

page. **244**



601000 HYDROPHARO

page. **246**



603000 HYDROWAY

page. **252**



604000 HYDROLANE

page. **259**



605000 HYDROSIDE

page. **262**



606000 HYDROPLATE

page. **262**



601200 HYDROSTICK

page. **263**



601100 HYDROSWING

page. **264**





## 609001 HYDROBOULEVARD 01 180 LED



220mm height bollard, round shape, for outdoor surface installation, 180° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included- Built-in LED driver 220-240V 50-60Hz, with 6 CREE XP-G3 high-power LED. IP65 rating.

**Designed by MOMO DESIGN.**

DESIGNED BY  
**MOMODESIGN**



### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 6 CREE XP-G3 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- Anchorage unit included

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 220-240V 50-60HZ ELECTRONIC IP65 4,00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	180°	800	80.00	<div>TEXTURED GREY</div> <div>MATT BLACK (ON REQUEST)</div>



\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4000°K NEURAL WHITE

## 609002 HYDROBOULEVARD 01 360 LED



220mm height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included- Built-in LED driver 220-240V 50-60Hz, with 12 CREE XP-G3 high-power LED. IP65 rating. **Designed by MOMO DESIGN.**

DESIGNED BY  
**MOMODESIGN**



### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 12 CREE XP-G3 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- Anchorage unit included

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
20 WATT 220-240V 50-60HZ ELECTRONIC IP65 4,20 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	360°	1.600	80.00	<div>TEXTURED GREY</div> <div>MATT BLACK (ON REQUEST)</div>

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4000°K NEURAL WHITE



**609003 HYDROBOULEVARD 02 180 LED**




DESIGNED BY  
**MOMODESIGN**

600mm height bollard, round shape, for outdoor surface installation, 180° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included- Built-in LED driver 220-240V 50-60Hz, with 6 CREE XP-G3 high-power LED. IP65 rating.

**Designed by MOMO DESIGN.**

**Energy Label** **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 6 CREE XP-G3 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- Anchorage unit included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 220-240V 50-60HZ ELECTRONIC IP65 5,50 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	180°	800	80.00	<div>TEXTURED GREY</div> <div>MATT BLACK (ON REQUEST)</div>


\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4000°K NEURAL WHITE





609004 HYDROBOULEVARD 02 360 LED NEW

600mm height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included- Built-in LED driver 220-240V 50-60Hz, with 12 CREE XP-G3 high-power LED. IP65 rating.  
**Designed by MOMO DESIGN.**

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 12 CREE XP-G3 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- Anchorage unit included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
20 WATT 220-240V 50-60HZ ELECTRONIC IP65 5,70 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 360°	1.600	80.00	 TEXTURED GREY  MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4000°K NEURAL WHITE

**609005 HYDROBOULEVARD 03 180 LED**





DESIGNED BY  
**MOMODESIGN**

1000mm height bollard, round shape, for outdoor surface installation, 180° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included- Built-in LED driver 220-240V 50-60Hz, with 6 CREE XP-G3 high-power LED. IP65 rating.

**Designed by MOMO DESIGN.**

**Energy Label** **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 6 CREE XP-G3 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- Anchorage unit included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 220-240V 50-60HZ ELECTRONIC IP65 7,00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 180°	800	80.00	<div>  TEXTURED GREY                     </div> <div>  MATT BLACK (ON REQUEST)                     </div>

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4000°K NEURAL WHITE



**609006 HYDROBOULEVARD 03 360 LED**




DESIGNED BY  
**MOMODESIGN**

1000mm height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included- Built-in LED driver 220-240V 50-60Hz, with 12 CREE XP-G3 high-power LED. IP65 rating.

**Designed by MOMO DESIGN.**

**Energy Label** **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 12 CREE XP-G3 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- Anchorage unit included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
20 WATT 220-240V 50-60HZ ELECTRONIC IP65 7,20 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	360°	1.600	80.00	<div>TEXTURED GREY</div> <div>MATT BLACK (ON REQUEST)</div>

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4000°K NEURAL WHITE


608001 HYDROSURF BOLLARD 01 SQUARE LED



600 mm height bollard, square shape, for outdoor surface installation, 180° light distribution, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted glass diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 14 mid-power CREE XH-G LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 14 x CREE XH-G LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
8 WATT 220-240V 50-60HZ ELECTRONIC IP65 4,60 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	FLOOR WASHER 180°	650	81.25	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)



## 608002 HYDROSURF BOLLARD 02 SQUARE LED



600 mm height bollard, square shape, for outdoor surface installation, floor washer 2x180° light distribution, phosphochromatised and polyester powder coated die-cast copper-free aluminium body, frosted glass diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2x14 mid-power CREE XH-G LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 14 x CREE XH-G LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
16 WATT 220-240V 50-60HZ ELECTRONIC IP65 6 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	FLOOR WASHER 2X180°	2 X 650	81.25	<div></div> TEXTURED GREY <div></div> MATT WHITE (ON REQUEST) <div></div> MATT BLACK (ON REQUEST)



## 601007 HYDROPHARO 01 E27





Low height bollard, round shape, for outdoor surface installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, vandal-proof polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Single light emission 180°. E27 lamp-holder, 230V 50Hz. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser vandal-proof
- E27 lamp-holder
- Protection against impact IK09 (10 joule)
- Double PG 13.5 cable gland.



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
<b>E27</b> 220-240V 50-60 HZ IP65 3.50 KG UNIT GROSS WEIGHT	E27	SEE BULB FEATURES	 180° LIGHT DISTRIBUTION	 TEXTURED GREY



## 601008 HYDROPHARO 02 E27





Low height bollard, round shape, for outdoor surface installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, vandal-proof polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Double light emission 2 x 90°. E27 lamp-holder, 230V 50Hz. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser vandal-proof
- E27 lamp-holder
- Protection against impact IK09 (10 joule)
- Double PG 13.5 cable gland.



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
<b>E27</b> 220-240V 50-60 HZ IP65 3.50 KG UNIT GROSS WEIGHT	E27	SEE BULB FEATURES	 2 X 90° LIGHT DISTRIBUTION	 TEXTURED GREY


## 601009 HYDROPHARO 04 E27



**NEW**

Low height bollard, round shape, for outdoor surface installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, vandal-proof polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Full light emission 360°. E27 lamp-holder, 230V 50Hz. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser vandal-proof
- E27 lamp-holder
- Protection against impact IK09 (10 joule)
- Double PG 13.5 cable gland.







	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
<b>E27</b> 220-240V 50-60 HZ IP65 3.50 KG UNIT GROSS WEIGHT	E27	SEE BULB FEATURES	 360° LIGHT DISTRIBUTION	 TEXTURED GREY

## 601004 HYDROPHARO 01 G8.5

Low height bollard, round shape, for outdoor surface installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, vandal-proof polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Single light emission 180°. Built-in electronic ballast 220-240V 50-60Hz, G8.5 20W metal halide. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser vandal-proof
- HIT-TC CRI 20W G8.5
- Electronic ballast 220-240V 50-60Hz
- Protection against impact IK09 (10 joule)
- Double PG 13.5 cable gland.







	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
<b>20 WATT</b> 220-240V 50-60HZ IP65 3.50 KG UNIT GROSS WEIGHT	HIT-TC CRI 20W G8.5	SEE BULB FEATURES	 180° LIGHT DISTRIBUTION	 TEXTURED GREY

601005 HYDROPHARO 02 G8.5

Low height bollard, round shape, for outdoor surface installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body,vandal-proof polycarbonate diffuser,moulded silicone gasket and stainless steel screws. Double light emission 2 x 90°. Built-in electronic ballast 220-240V 50-60Hz, G8.5 20W metal halide. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser vandal-proof
- HIT-TC CRI 20W G8.5
- Electronic ballast 220-240V 50-60Hz
- Protection against impact IK09 (10 joule)
- Double PG 13.5 cable gland.







	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20 WATT 220-240V 50-60HZ IP65 3.50 KG UNIT GROSS WEIGHT	HIT-TC CRI 20W G8.5	SEE BULB FEATURES	 2 X 90° LIGHT DISTRIBUTION	 TEXTURED GREY

601006 HYDROPHARO 04 G8.5

Low height bollard, round shape, for outdoor surface installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body,vandal-proof polycarbonate diffuser,moulded silicone gasket and stainless steel screws. Full light emission 360°. Built-in electronic ballast 220-240V 50-60Hz, G8.5 20W metal halide. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser vandal-proof
- HIT-TC CRI 20W G8.5
- Electronic ballast 220-240V 50-60Hz
- Protection against impact IK09 (10 joule)
- Double PG 13.5 cable gland.



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20 WATT 220-240V 50-60HZ IP65 3.50 KG UNIT GROSS WEIGHT	HIT-TC CRI 20W G8.5	SEE BULB FEATURES	 360° LIGHT DISTRIBUTION	 TEXTURED GREY

## 603001 HYDROWAY MINI ROUND LED

680mm height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage unit included- Built-in LED driver 220-240V 50-60Hz, with 4 CREE XP-E high-power LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 4 x 2W CREE "XP-E" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser.
- Anchorage unit included.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 220-240V 50-60HZ ELECTRONIC IP65 2,80 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	360°	600	60.00	TEXTURED GREY

## 603002 HYDROWAY MINI SQUARE LED

680mm height bollard, square shape, for outdoor surface installation, 4x85° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage unit included- Built-in LED driver 220-240V 50-60Hz, with 4 CREE XP-E high-power LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 4 x 2W CREE "XP-E" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser.
- Anchorage unit included.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 220-240V 50-60HZ ELECTRONIC IP65 2,80 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	4 X 85°	600	60.00	TEXTURED GREY




**603003 HYDROWAY MEDIUM 01 ROUND LED**




**NEW**

380mm height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included- Built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-E high-power LED. IP65 rating.

**Energy Label** **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 x 2.5 W CREE XP-E LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- Anchorage unit included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
20 WATT 220-240V 50-60HZ ELECTRONIC IP65 4,30 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 360°	1.200	60.00	 TEXTURED GREY




## 603004 HYDROWAY MEDIUM 02 ROUND LED


680mm height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included- Built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-E high-power LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 x 2.5 W CREE XP-E LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- Anchorage unit included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
20 WATT 220-240V 50-60HZ ELECTRONIC IP65 5,20 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	360°	1.200	60.00	TEXTURED GREY





## 603005 HYDROWAY MEDIUM 01 SQUARE LED

380mm height bollard, square shape, for outdoor surface installation, 4x85° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included- Built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-E high-power LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 x 2.5 W CREE XP-E LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- Anchorage unit included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
20 WATT 220-240V 50-60HZ ELECTRONIC IP65 3,80 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	4 X 85°	1.200	60.00	TEXTURED GREY




## 603006 HYDROWAY MEDIUM 02 SQUARE LED

680mm height bollard, square shape, for outdoor surface installation, 4x85° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included- Built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-E high-power LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 x 2.5 W CREE XP-E LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Polycarbonate diffuser
- Anchorage unit included




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
20 WATT 220-240V 50-60HZ ELECTRONIC IP65 5,20 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	4 X 85°	1.200	60.00	TEXTURED GREY

## 604001 HYDROLANE ROUND 01 LED

600mm height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x COB LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 5W COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 220-240V 50-60HZ ELECTRONIC IP65 2,60 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	360°	700	70.00	TEXTURED GREY

## 604002 HYDROLANE ROUND 02 LED

800mm height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x COB LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 5W COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 220-240V 50-60HZ ELECTRONIC IP65 3,50 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	360°	700	70.00	TEXTURED GREY




### 604003 HYDROLANE SQUARE 01 LED

600mm height bollard, square shape, for outdoor surface installation, 80° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB LED. IP65 rating.

#### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 5W COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
5 WATT 220-240V 50-60HZ ELECTRONIC IP65 2,60 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 80°	350	70.00	 TEXTURED GREY




### 605001 HYDROSIDE 01 LED

400mm height bollard, square shape, for outdoor surface installation, 180° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB LED. IP65 rating.

#### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 5W COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
5 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,70 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 180°	350	70.00	 TEXTURED GREY




## 605002 HYDROSIDE 02 LED

600mm height bollard, square shape, for outdoor surface installation, 180° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 5W COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
5 WATT 220-240V 50-60HZ ELECTRONIC IP65 2,60 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	180°	350	70.00	TEXTURED GREY

## 606001 HYDROPLATE 01 LED

600mm height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x COB LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 5W COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
10 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,60 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	360°	700	70.00	TEXTURED GREY




601201 HYDROSTICK LED NEW

680mm height bollard, rectangular shape for outdoor surface installation, with 180° diffused light emission from one side , phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, opaline PMMA diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 48 low-power LED. Anchorage bolts included. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body.
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 48 x low-power SMD3528 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- PMMA diffuser
- Anchorage unit included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
6 WATT 220-240V 50-60HZ ELECTRONIC IP65 3,00 KG UNIT GROSS WEIGHT	LOW-POWER LED	 3.000°K WARM-WHITE	 180°	350	58.34	 TEXTURED GREY

## 601101 HYDROSWING 01 LED



750mm height bollard, cylindrical shape with single lighting head, for outdoor surface installation, 30° light emission, realized in hard anodized copper-free aluminum, tempered safety glass, moulded silicone gasket and stainless steel screws. With 1 x COB LED, 24V DC remote driver needed. IP65 rating.

### Energy Label A++

- Material: hard anodized copper-free aluminum.
- NR. 1 x COB LED
- 24V DC remote driver needed
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
9 WATT 24V DC IP65 2,00 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	M 30°	1.050	116.67	SILVER GREY

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	MIN 1 - MAX 2
MEANWELL	LPV-35-24	CONSTANT VOLTAGE 24V DC	35W	IP67	MIN 1 - MAX 3
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60W	IP67	MIN 1 - MAX 6


## 601102 HYDROSWING 02 LED



750mm height bollard, cylindrical shape with double lighting head, for outdoor surface installation, 2x30° light emission, realized in hard anodized copper-free aluminum, tempered safety glass, moulded silicone gasket and stainless steel screws. With 2 x COB LED, 24V DC remote driver needed. IP65 rating.

### Energy Label A++

- Material: hard anodized copper-free aluminum.
- NR. 2 x COB LED
- 24V DC remote driver needed
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2X9 WATT 24V DC IP65 2,50 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	M 2 X 30°	2 X 1.050	116.67	SILVER GREY

### REMOTE DRIVER SELECTION

BRAND	MANUFACTURER CODE	TYPE	WATT	IP RATE	NUMBERS OF FIXTURES
MEANWELL	LPV-20-24	CONSTANT VOLTAGE 24V DC	20W	IP67	1
MEANWELL	LPV-60-24	CONSTANT VOLTAGE 24V DC	60 W	IP67	MIN 1 - MAX 3
MEANWELL	LPV-100-24	CONSTANT VOLTAGE 24V DC	100 W	IP67	MIN 1 - MAX 5







# Downlights



701000 HYDROCEILING

page. **268**



706000 HYDROTECH 03

ppage. **273**



707000 HYDROTECH 03 STEEL

page. **276**



702000 HYDROSPOT

page. **277**



704000 ID SERIES

page. **279**



705000 OYSTER

page. **280**





## 701005 HYDROCEILING MINI LED

Recessed luminaire for outdoor ceiling installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 12W COB Bridgelux LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included





	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
12 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,25 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	25°	900	75.00	MATT BLACK

## 701001P HYDROCEILING MINI GU10

Recessed luminaire for outdoor ceiling installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered safety glass, moulded silicone gasket and stainless steel screws. GU10 LED / halogen. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminium body
- Coating: polyester powder coating with phosphochromating pre-finish
- GU10 base, MAX 50W
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- M16 x 1.5 cable gland.
- 0,5 mt neoprene power cable included.





	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT MAX 220-240V 50-60HZ IP65 1.50 KG UNIT GROSS WEIGHT	GU10 LED / HALOGEN	SEE BULB FEATURES	SEE BULB FEATURES	MATT BLACK




701006 HYDROCEILING MEDIUM LED

Recessed luminaire for outdoor ceiling installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 26W COB Bridgelux LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included





	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
26 WATT 220-240V 50-60HZ ELECTRONIC IP65 2,20 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 30°	2.745	105.58	 MATT BLACK




701002P HYDROCEILING MEDIUM G8.5

Recessed luminaire for outdoor ceiling installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in ballast 220-240V 50-60Hz, G8.5 20W metal halide. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT-TC CRI 20W G8.5
- Electronic ballast 220-240V 50-60Hz
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- M16 x 1.5 cable gland.
- 0,5 mt neoprene power cable included.



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20 WATT 220-240V 50-60HZ ELECTRONIC IP65 3.90 KG UNIT GROSS WEIGHT	 HIT-TC CRI 20W G8.5	SEE BULB FEATURES	 30°	 MATT BLACK



**701007 HYDROCEILING MAXI LED**

**NEW**


Recessed luminaire for outdoor ceiling installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB LED. IP65 rating.

**Energy Label** **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 50W COB Bridgelux LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 1 mt. neoprene power cable included





	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
50 WATT 220-240V 50-60HZ ELECTRONIC IP65 3,45 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	30°	4.240	84.80	MATT BLACK








701003 HYDROCEILING MAXI G12

Recessed luminaire for outdoor ceiling installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and frame, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in ballast 230V 50Hz, G12 35W or 70W metal halide. IP65 rating.

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- HIT CRI 35W G12 or HIT CRI 70W G12
- Conventional ballast 230V 50Hz
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- M16 x 1.5 cable gland.
- Adjustable +/- 15 degrees.
- 0,5 mt neoprene power cable included.



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
35 WATT   70 WATT HIT-CRI – BASE G12 230V 50HZ IP65 4.00 KG UNIT GROSS WEIGHT	 HIT-CRI – BASE G12	SEE BULB FEATURES	 4° SUPER-NARROW (ON REQUEST)	 MATT BLACK
			 10° NARROW	
			 23° FLOOD (ON REQUEST)	


706004 HYDROTECH MINI 03 ROUND LED






Round downlight for outdoor surface installation on the ceiling, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB "CXA 1512" CREE LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 13W COB CREE "CXA 1512" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.5 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
13 WATT 220-240V 50-60HZ ELECTRONIC IP65 0,95 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 30°	1.290	99.23	 TEXTURED GREY


706005 HYDROTECH MEDIUM 03 ROUND LED






Round downlight for outdoor surface installation on the ceiling, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB "CXA 2520" CREE LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 26W COB CREE "CXA 2520" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.5 mt. neoprene power cable included




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
26 WATT 220-240V 50-60HZ ELECTRONIC IP65 2,30 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 30°	2.500	96.15	 TEXTURED GREY




## 706006 HYDROTECH MINI 03 SQUARE LED

Square downlight for outdoor surface installation on the ceiling, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB "CXA 1512" CREE LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 13W COB CREE "CXA 1512" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.5 mt. neoprene power cable included




	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
13 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,15 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 30°	1.290	99.23	 TEXTURED GREY




## 706007 HYDROTECH MEDIUM 03 SQUARE LED

Square downlight for outdoor surface installation on the ceiling, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB "CXA 2520" CREE LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 x 26W COB CREE "CXA 2520" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.5 mt. neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
26 WATT 220-240V 50-60HZ ELECTRONIC IP65 2,50 KG UNIT GROSS WEIGHT	COB LED	 3.000°K WARM-WHITE	 30°	2.500	96.15	 TEXTURED GREY





**707001 HYDROTECH MINI STEEL ROUND 03 LED**


Round downlight for outdoor surface installation on the ceiling, luminaire body completely realized in mirrored stainless steel AISI 316L, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB CREE LED. IP65 rating.

**Energy Label** **A++**

- Mirrored stainless steel AISI 316L
- NR. 1 x 5W CREE COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.3 mt. neoprene power cable included



Ø100 mm



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
5 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,50 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	30°	480	96.00	MIRRORRED STAINLESS STEEL

**707002 HYDROTECH MEDIUM STEEL ROUND 03 LED**


Round downlight for outdoor surface installation on the ceiling, luminaire body completely realized in mirrored stainless steel AISI 316L, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB CREE LED. IP65 rating.

**Energy Label** **A++**

- Mirrored stainless steel AISI 316L
- NR. 1 x 12W CREE COB LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 0.3 mt. neoprene power cable included




Ø150 mm



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
12 WATT 220-240V 50-60HZ ELECTRONIC IP65 3,00 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	30°	960	80.00	MIRRORRED STAINLESS STEEL

702002 HYDROSPOT STEEL

Completely made of massive Stainless Steel.  
Ideal for use in Saunas, Spas Hammam,  
Swimming pool areas,  
Fitness Centers and all wet recreational areas  
both Indoor and Outdoor.


- Protection class IP66
- Stainless steel body
- Stainless steel ring
- Stainless steel bracket
- Silicon rubber gaskets
- Tempered safety glass
- Inox aisi 304










	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
MAX 50 WATT 220-240V 50-60HZ ELECTRONIC IP65 0,50 KG UNIT GROSS WEIGHT	 QPAR16 OR GU 10 L.E.D.	SEE BULB FEATURES	SEE BULB FEATURES	 STAINLESS STEEL AISI 304

702005 HYDROSPOT 01

- Die-cast aluminium
- Water-proof IP66
- Dust proof



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
MAX 50 WATT 220-240V 50-60HZ ELECTRONIC IP65 0,50 KG UNIT GROSS WEIGHT	 QPAR16 OR GU 10 L.E.D.	SEE BULB FEATURES	SEE BULB FEATURES	 CHROME  SATIN ZAPON  TEXTURE  GOLD  MATT WHITE  MATT BLACK

702004 HYDROSPOT OYSTER

- Die-cast aluminium
- Water-proof IP66
- Dust proof




EASY INSTALLATION










EASY RELAMPING AND MAINTENANCE




75 MM



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
MAX 50 WATT 220-240V 50-60HZ ELECTRONIC IP65 0,50 KG UNIT GROSS WEIGHT	 QPAR16 OR GU 10 L.E.D.	SEE BULB FEATURES	SEE BULB FEATURES	<div><div> CHROME</div><div> TEXTURE</div><div> MATT WHITE</div><div> MATT BLACK</div><div> SATIN ZAPON</div><div> GOLD</div></div>

704001 ID02 STANDARD


- Die-cast
- See bulb features




CHROME VERSION

AC020 - PUKSTOP

50 WATT MAX  
MR16 - BASE GU5,3  
12 VOLTS - IP20  
0,2 KG UNIT GROSS WEIGHT



LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
 MR16 - BASE GU5,3	SEE BULB FEATURES	SEE BULB FEATURES	<div><div></div> CHROME</div> <div><div></div> ZAPON SATIN</div> <div><div></div> TEXTURE</div> <div><div></div> MATT WHITE</div> <div><div></div> MATT BLACK</div>


704002 ID5 PLUS STANDARD

- Die-cast
- See bulb features



THE **DARK-LIGHT** TECHNIQUE IS RELATED TO THE CUT-OFF ANGLE OF THE LAMPS AND THE REFLECTOR. THIS METHOD PROVIDES HIGH VISUAL COMFORT BY DECREASING THE DIRECT GLARE ON OBJECTS AND INSTALLATIONS, THUS TAKING THE MAXIMUM RENDERING ADVANTAGE OF THE LIGHT. PRODUCING A RESULT ON WHICH IT IS POSSIBLE TO OBTAIN THE BEST LIGHTING OUTPUT WITHOUT SEEING THE ELEMENT THAT PRODUCES IT. CUT-OFF IS THE ANGLE FORMED BETWEEN THE CEILING (HORIZONTAL) AND AN IMAGINARY STRAIGHT LINE THAT IS TANGENT TO THE LAMP AND PASSES BY THE EDGE OF THE REFLECTOR. IF OUR VISUAL FIELD IS POSITIONED WITHIN THIS ANGLE, IT IS IMPOSSIBLE TO SEE THE LAMP IN FUNCTION. DOWN-LIGHTS SUPPLIED WITH INTEGRATED CELL-DIFFUSERS PRODUCE THE SAME EFFECT AS ANTIGLARE LOUVERS AND CAN HAVE AN IMPORTANT BEARING ON DIRECT GLARE. AS A RESULT OF THIS, THE VISUAL COMFORT INCREASES AND MAKES IT MOST SUITABLE TO USE IN WORK AREAS WITH COMPUTER-SCREENS, SUBSTANTIALLY REDUCING THE DISABILITY GLARE THAT USUALLY REFLECTS ON THE SAME.



LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
 MR16 - BASE GU5,3	SEE BULB FEATURES	SEE BULB FEATURES	<div><div></div> TEXTURED GREY</div> <div><div></div> MATT WHITE</div> <div><div></div> MATT BLACK</div>

20/35/50 WATT  
MR16 - BASE GU5,3  
12 VOLTS - IP44  
0,3 KG UNIT GROSS WEIGHT

## 705001 OYSTER 01


- Die-cast
- See bulb features









ZAPONATO SATIN VERSION



63 mm



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20/50 WATT MR16 - BASE GU5,3 12 VOLTS - IP20 0,2 KG UNIT GROSS WEIGHT	 MR16 - BASE GU5,3	SEE BULB FEATURES	SEE BULB FEATURES	<div>  CHROME            ZAPONATO SATIN            TEXTURE            MATT WHITE            MATT BLACK         </div>

## 705002 OSYTER 02

- Die-cast
- See bulb features




CHROME VERSION









75 mm





MOVABLE  
+15° ↔ -15°




	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20/35/50 WATT MR16 - BASE GU5,3 12 VOLTS - IP20 0,2 KG UNIT GROSS WEIGHT	 MR16 - BASE GU5,3	SEE BULB FEATURES	SEE BULB FEATURES	<div>  CHROME            ZAPONATO SATIN            TEXTURE            MATT WHITE            MATT BLACK         </div>

705005 OYSTER 05 PLUS

- Die-cast
- See bulb features



	LIGHT SOURCE	LIGHT COLOR	LIGHT BEAM OPTIONS	COLORS OPTIONS
20/35/50 WATT MR16 - BASE GU5,3 12 VOLTS - IP44 0,3 KG UNIT GROSS WEIGHT	 MR16 - BASE GU5,3	SEE BULB FEATURES	SEE BULB FEATURES	<div><div></div> TEXTURED GREY</div> <div><div></div> MATT WHITE</div> <div><div></div> MATT BLACK</div>





# Urban lights



802000 HYDROCITY

page. **284**



803000 HYDROBOOK POLE-TOP

page. **298**



804000 HYDROTECH POLE-TOP

page. **306**




805000 HYDROFLASH POLE-TOP

page. **310**



809900 POLES & ACCESSORIES

page. **332**





## 802001-02 HYDROCITY 01 LED

Round pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm, single supporting arm, with downward light distribution. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver/s, with number of LEDs from 24 to 48 CREE XP-G3 LED. IP66 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 24 -> 48 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



### AVAILABLE OPTICS:



ROTSYMMETRICAL



CYCLE ROUTE / PEDESTRIAN



STREET



802001 HYDROCITY 01 12+12	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
36 WATT 220-240V 50-60HZ ELECTRONIC IP66 6,10 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	ROSYMMETRICAL	3.456	96.00	TEXTURED GREY
			CYCLE ROUTE PEDESTRIAN			MATT WHITE (ON REQUEST)
			STREET			MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE





802002 HYDROCITY 01 24+24	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
72 WATT 220-240V 50-60HZ ELECTRONIC IP66 6,10 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	ROSYMMETRICAL	6.912	96.00	TEXTURED GREY
			CYCLE ROUTE PEDESTRIAN			MATT WHITE (ON REQUEST)
			STREET			MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE


## POLES & ACCESSORIES

### BURIED POLES



CODE	ARTICLE	HEIGHT MM.	DESCRIPTION
809901	CYLINDRICAL POLE 3,5 METERS TO BE BURIED	3.500	Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), diameter 76 mm, thickness 4 mm. Phospho-chromatised and polyester powder coated. Total height including 500 mm to be buried into the ground. Includes IP54 cover plate 132x38 mm and terminal block in double insulation.
809902	CYLINDRICAL POLE 4,5 METERS TO BE BURIED	4.500	
809903	CYLINDRICAL POLE 5,5 METERS TO BE BURIED	5.500	
809908	ADAPTER DIAM. 76MM → 60MM		Adapter for pole diam. 76 mm, allow the diameter reduction to 60 mm

### POLES WITH BASE-PLATE



CODE	ARTICLE	HEIGHT MM.	DESCRIPTION
809904	CYLINDRICAL POLE 3 METERS WITH BASE-PLATE	3.000	Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), diameter 76 mm, thickness 4 mm. Phospho-chromatised and polyester powder coated. With base plate dim. 250x250 mm, thickness 10 mm Includes IP54 cover plate 132x38 mm and terminal block in double insulation.
809905	CYLINDRICAL POLE 4 METERS WITH BASE-PLATE	4.000	
809906	CYLINDRICAL POLE 5 METERS WITH BASE-PLATE	5.000	
809907	ANCHORAGE UNIT FOR BASE-PLATE		Base plate dim. 250x250 mm, thickness 3 mm, made in galvanized steel complete of nr. 4 anchorage threaded bolts
809908	ADAPTER DIAM. 76MM → 60MM		Adapter for pole diam. 76 mm, allow the diameter reduction to 60 mm






## 802003..07 HYDROCITY 02 LED

Round pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm, double supporting arm, with downward light distribution. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver/s, with number of LEDs from 12 to 48 CREE XP-G3 LED. IP66 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 12 -> 48 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



Ø 390 mm

452 mm

58 mm



### AVAILABLE OPTICS:



ROTSYMMETRICAL



CYCLE ROUTE / PEDESTRIAN



STREET




**Energy Label** **A++**

802003 HYDROCITY 02 -12+0	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
18 WATT 220-240V 50-60HZ ELECTRONIC IP66 6,30 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	<div> <div>ROSYMMETRICAL</div> <div>CYCLE ROUTE PEDESTRIAN</div> <div>STREET</div> </div>	1.728	96.00	<div> <div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div> </div>

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE


**Energy Label** **A++**

802004 HYDROCITY 02 -12+12	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
36 WATT 220-240V 50-60HZ ELECTRONIC IP66 6,30 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	<div> <div>ROSYMMETRICAL</div> <div>CYCLE ROUTE PEDESTRIAN</div> <div>STREET</div> </div>	3.456	96.00	<div> <div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div> </div>

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE


**Energy Label** **A++**

802005 HYDROCITY 02 - 24+0	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
36 WATT 220-240V 50-60HZ ELECTRONIC IP66 6,30 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	<div> <div>ROSYMMETRICAL</div> <div>CYCLE ROUTE PEDESTRIAN</div> <div>STREET</div> </div>	3.456	96.00	<div> <div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div> </div>

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE


**Energy Label** **A++**

802006 HYDROCITY 02 - 24+12	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
54 WATT 220-240V 50-60HZ ELECTRONIC IP66 6,30 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	<div> <div>ROSYMMETRICAL</div> <div>CYCLE ROUTE PEDESTRIAN</div> <div>STREET</div> </div>	5.184	96.00	<div> <div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div> </div>

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE





802007	HYDROCITY 02 - 24+24	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
72 WATT 220-240V 50-60HZ ELECTRONIC IP66 6,30 KG UNIT GROSS WEIGHT		HIGH-POWER LED	3.000°K WARM-WHITE	ROSYMMETRICAL	6.912	96.00	TEXTURED GREY
				CYCLE ROUTE PEDESTRIAN			MATT WHITE (ON REQUEST)
				STREET			MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE


## POLES & ACCESSORIES

### BURIED POLES



CODE	ARTICLE	HEIGHT MM.	DESCRIPTION
809901	CYLINDRICAL POLE 3,5 METERS TO BE BURIED	3.500	Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), <b>diameter 76 mm, thickness 4 mm.</b> Phospho-chromatised and polyester powder coated. <b>Total height including 500 mm to be buried into the ground.</b> <b>Includes IP54 cover plate 132x38 mm and terminal block in double insulation.</b>
809902	CYLINDRICAL POLE 4,5 METERS TO BE BURIED	4.500	
809903	CYLINDRICAL POLE 5,5 METERS TO BE BURIED	5.500	
809908	ADAPTER DIAM. 76MM → 60MM		Adapter for pole diam. 76 mm, allow the diameter reduction to 60 mm

### POLES WITH BASE-PLATE



CODE	ARTICLE	HEIGHT MM.	DESCRIPTION
809904	CYLINDRICAL POLE 3 METERS WITH BASE-PLATE	3.000	Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), <b>diameter 76 mm, thickness 4 mm.</b> Phospho-chromatised and polyester powder coated. <b>With base plate dim. 250x250 mm, thickness 10 mm</b> <b>Includes IP54 cover plate 132x38 mm and terminal block in double insulation.</b>
809905	CYLINDRICAL POLE 4 METERS WITH BASE-PLATE	4.000	
809906	CYLINDRICAL POLE 5 METERS WITH BASE-PLATE	5.000	
809907	ANCHORAGE UNIT FOR BASE-PLATE		<b>Base plate dim. 250x250 mm, thickness 3 mm,</b> made in galvanized steel complete of nr. 4 anchorage threaded bolts
809908	ADAPTER DIAM. 76MM → 60MM		Adapter for pole diam. 76 mm, allow the diameter reduction to 60 mm



## 802008..12 HYDROCITY 03 LED



Round pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm, central supporting arm, with downward light distribution. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws Built-in LED driver/s, with 12 to 48 CREE XP-G3 LED. IP66 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 12 -> 48 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



Ø 390 mm



### AVAILABLE OPTICS:



ROTSYMMETRICAL



CYCLE ROUTE / PEDESTRIAN



STREET





		LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
<b>802008</b>	<b>HYDROCITY 03 12+0</b>						
18 WATT	220-240V 50-60HZ ELECTRONIC	HIGH-POWER LED	3.000°K WARM-WHITE	<input checked="" type="checkbox"/> ROTOSYMMETRICAL	1.728	96.00	<input type="checkbox"/> TEXTURED GREY <input type="checkbox"/> MATT WHITE (ON REQUEST) <input checked="" type="checkbox"/> MATT BLACK (ON REQUEST)
IP66	6,10 KG UNIT GROSS WEIGHT			<input type="checkbox"/> CYCLE ROUTE PEDESTRIAN			
				<input type="checkbox"/> STREET			

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE



		LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
<b>802009</b>	<b>HYDROCITY 03 -12+12</b>						
36 WATT	220-240V 50-60HZ ELECTRONIC	HIGH-POWER LED	3.000°K WARM-WHITE	<input checked="" type="checkbox"/> ROTOSYMMETRICAL	3.456	96.00	<input type="checkbox"/> TEXTURED GREY <input type="checkbox"/> MATT WHITE (ON REQUEST) <input checked="" type="checkbox"/> MATT BLACK (ON REQUEST)
IP66	6,10 KG UNIT GROSS WEIGHT			<input type="checkbox"/> CYCLE ROUTE PEDESTRIAN			
				<input type="checkbox"/> STREET			

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE



		LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
<b>802010</b>	<b>HYDROCITY 03 - 24+0</b>						
36 WATT	220-240V 50-60HZ ELECTRONIC	HIGH-POWER LED	3.000°K WARM-WHITE	<input checked="" type="checkbox"/> ROTOSYMMETRICAL	3.456	96.00	<input type="checkbox"/> TEXTURED GREY <input type="checkbox"/> MATT WHITE (ON REQUEST) <input checked="" type="checkbox"/> MATT BLACK (ON REQUEST)
IP66	6,10 KG UNIT GROSS WEIGHT			<input type="checkbox"/> CYCLE ROUTE PEDESTRIAN			
				<input type="checkbox"/> STREET			








\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE



		LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
<b>802011</b>	<b>HYDROCITY 03 - 24+12</b>						
54 WATT	220-240V 50-60HZ ELECTRONIC	HIGH-POWER LED	3.000°K WARM-WHITE	<input checked="" type="checkbox"/> ROTOSYMMETRICAL	5.184	96.00	<input type="checkbox"/> TEXTURED GREY <input type="checkbox"/> MATT WHITE (ON REQUEST) <input checked="" type="checkbox"/> MATT BLACK (ON REQUEST)
IP66	6,10 KG UNIT GROSS WEIGHT			<input type="checkbox"/> CYCLE ROUTE PEDESTRIAN			
				<input type="checkbox"/> STREET			

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE





802012    HYDROCITY 03 - 24+24		LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
72 WATT 220-240V 50-60HZ ELECTRONIC IP66 6,10 KG UNIT GROSS WEIGHT		HIGH-POWER LED	 3.000°K WARM-WHITE	 ROTOSYMMETRICAL	6.912	96.00	 TEXTURED GREY
				 CYCLE ROUTE PEDESTRIAN			 MATT WHITE <i>(ON REQUEST)</i>
				 STREET			 MATT BLACK <i>(ON REQUEST)</i>

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE


## POLES & ACCESSORIES

### BURIED POLES



CODE	ARTICLE	HEIGHT MM.	DESCRIPTION
809901	CYLINDRICAL POLE 3,5 METERS TO BE BURIED	3.500	Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), <b>diameter 76 mm, thickness 4 mm.</b> Phospho-chromatised and polyester powder coated. <b>Total height including 500 mm to be buried into the ground.</b> Includes IP54 cover plate 132x38 mm and terminal block in double insulation.
809902	CYLINDRICAL POLE 4,5 METERS TO BE BURIED	4.500	
809903	CYLINDRICAL POLE 5,5 METERS TO BE BURIED	5.500	
809908	ADAPTER DIAM. 76MM → 60MM		Adapter for pole diam. 76 mm, allow the diameter reduction to 60 mm

### POLES WITH BASE-PLATE



CODE	ARTICLE	HEIGHT MM.	DESCRIPTION
809904	CYLINDRICAL POLE 3 METERS WITH BASE-PLATE	3.000	Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), <b>diameter 76 mm, thickness 4 mm.</b> Phospho-chromatised and polyester powder coated. <b>With base plate dim. 250x250 mm, thickness 10 mm</b> Includes IP54 cover plate 132x38 mm and terminal block in double insulation.
809905	CYLINDRICAL POLE 4 METERS WITH BASE-PLATE	4.000	
809906	CYLINDRICAL POLE 5 METERS WITH BASE-PLATE	5.000	
809907	ANCHORAGE UNIT FOR BASE-PLATE		<b>Base plate dim. 250x250 mm, thickness 3 mm,</b> made in galvanized steel complete of nr. 4 anchorage threaded bolts
809908	ADAPTER DIAM. 76MM → 60MM		Adapter for pole diam. 76 mm, allow the diameter reduction to 60 mm






## 803001 - 803002 SINGLE HYDROBOOK POLE-TOP MAXI LED

Square pole-top mounted floodlight for outdoor installation on a pole diam. 60 mm or 76 mm. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Flange for pole diam. 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 12 or 24 CREE XP-G3 LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 12 -> 24 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG9
- 3 m neoprene power cable included



### AVAILABLE OPTICS:



CYCLE ROUTE / PEDESTRIAN



STREET



**Energy Label** **A++**

803001	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
<b>HYDROBOOK POLE-TOP MAXI 12 LED</b>	HIGH-POWER LED	3.000°K WARM-WHITE	CYCLE ROUTE PEDESTRIAN	1.728	96.00	<input type="checkbox"/> TEXTURED GREY <input type="checkbox"/> MATT WHITE (ON REQUEST) <input type="checkbox"/> MATT BLACK (ON REQUEST)
18 WATT 220-240V 50-60HZ ELECTRONIC IP65 3,00 KG UNIT GROSS WEIGHT			STREET			

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE





**Energy Label** **A++**

803002	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
<b>HYDROBOOK POLE-TOP MAXI 24 LED</b>	HIGH-POWER LED	3.000°K WARM-WHITE	CYCLE ROUTE PEDESTRIAN	3.456	96.00	<input type="checkbox"/> TEXTURED GREY <input type="checkbox"/> MATT WHITE (ON REQUEST) <input type="checkbox"/> MATT BLACK (ON REQUEST)
36 WATT 220-240V 50-60HZ ELECTRONIC IP65 3,00 KG UNIT GROSS WEIGHT			STREET			

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE


## POLES & ACCESSORIES

### BURIED POLES



CODE	ARTICLE	HEIGHT MM.	DESCRIPTION
<b>809901</b>	CYLINDRICAL POLE 3,5 METERS TO BE BURIED	3.500	Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), diameter 76 mm, thickness 4 mm. Phospho-chromatised and polyester powder coated. Total height including 500 mm to be buried into the ground. Includes IP54 cover plate 132x38 mm and terminal block in double insulation.
<b>809902</b>	CYLINDRICAL POLE 4,5 METERS TO BE BURIED	4.500	
<b>809903</b>	CYLINDRICAL POLE 5,5 METERS TO BE BURIED	5.500	
<b>809908</b>	ADAPTER DIAM. 76MM → 60MM		Adapter for pole diam. 76 mm, allow the diameter reduction to 60 mm

### POLES WITH BASE-PLATE



CODE	ARTICLE	HEIGHT MM.	DESCRIPTION
<b>809904</b>	CYLINDRICAL POLE 3 METERS WITH BASE-PLATE	3.000	Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), diameter 76 mm, thickness 4 mm. Phospho-chromatised and polyester powder coated. With base plate dim. 250x250 mm, thickness 10 mm Includes IP54 cover plate 132x38 mm and terminal block in double insulation.
<b>809905</b>	CYLINDRICAL POLE 4 METERS WITH BASE-PLATE	4.000	
<b>809906</b>	CYLINDRICAL POLE 5 METERS WITH BASE-PLATE	5.000	
<b>809907</b>	ANCHORAGE UNIT FOR BASE-PLATE		Base plate dim. 250x250 mm, thickness 3 mm, made in galvanized steel complete of nr. 4 anchorage threaded bolts
<b>809908</b>	ADAPTER DIAM. 76MM → 60MM		Adapter for pole diam. 76 mm, allow the diameter reduction to 60 mm

**803003 - 803004 DOUBLE HYDROBOOK POLE-TOP MAXI LED**




2 x square pole-top mounted floodlight for outdoor installation on a pole diam. 60 mm or 76 mm. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Flange for pole diam. 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 2 x 12 or 24 CREE XP-G3 LED. IP65 rating.

**Energy Label A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 12 → 24 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG9
- 3 m neoprene power cable included



ADJUSTABLE  
+28°  
-28°  
ADJUSTABLE  
-33°  
+33°



**AVAILABLE OPTICS:**



CYCLE ROUTE / PEDESTRIAN



STREET



Energy Label **A++**

803003	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
<b>DOUBLE HYDROBOOK POLE-TOP MAXI 12 LED</b>	HIGH-POWER LED	3.000°K WARM-WHITE	CYCLE ROUTE PEDESTRIAN	2 X 1.728	96.00	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)
<b>2X18 WATT</b> 220-240V 50-60HZ ELECTRONIC IP65 5,80 KG UNIT GROSS WEIGHT			STREET			

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE





Energy Label **A++**

803004	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
<b>DOUBLE HYDROBOOK POLE-TOP MAXI 24 LED</b>	HIGH-POWER LED	3.000°K WARM-WHITE	CYCLE ROUTE PEDESTRIAN	2 X 3.456	96.00	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)
<b>2X36 WATT</b> 220-240V 50-60HZ ELECTRONIC IP65 5,80 KG UNIT GROSS WEIGHT			STREET			

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE, ● BLUE


## POLES & ACCESSORIES

### BURIED POLES



CODE	ARTICLE	HEIGHT MM.	DESCRIPTION
<b>809901</b>	CYLINDRICAL POLE 3,5 METERS TO BE BURIED	3.500	Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), <b>diameter 76 mm, thickness 4 mm.</b> Phospho-chromatised and polyester powder coated. <b>Total height including 500 mm to be buried into the ground.</b> <b>Includes IP54 cover plate 132x38 mm and terminal block in double insulation.</b>
<b>809902</b>	CYLINDRICAL POLE 4,5 METERS TO BE BURIED	4.500	
<b>809903</b>	CYLINDRICAL POLE 5,5 METERS TO BE BURIED	5.500	
<b>809908</b>	ADAPTER DIAM. 76MM → 60MM		Adapter for pole diam. 76 mm, allow the diameter reduction to 60 mm

### POLES WITH BASE-PLATE



CODE	ARTICLE	HEIGHT MM.	DESCRIPTION
<b>809904</b>	CYLINDRICAL POLE 3 METERS WITH BASE-PLATE	3.000	Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), <b>diameter 76 mm, thickness 4 mm.</b> Phospho-chromatised and polyester powder coated. <b>With base plate dim. 250x250 mm, thickness 10 mm</b> <b>Includes IP54 cover plate 132x38 mm and terminal block in double insulation.</b>
<b>809905</b>	CYLINDRICAL POLE 4 METERS WITH BASE-PLATE	4.000	
<b>809906</b>	CYLINDRICAL POLE 5 METERS WITH BASE-PLATE	5.000	
<b>809907</b>	ANCHORAGE UNIT FOR BASE-PLATE		<b>Base plate dim. 250x250 mm, thickness 3 mm,</b> made in galvanized steel complete of nr. 4 anchorage threaded bolts
<b>809908</b>	ADAPTER DIAM. 76MM → 60MM		Adapter for pole diam. 76 mm, allow the diameter reduction to 60 mm






**803005 -803006 HYDROBOOK ARM POLE-TOP MAXI LED**

Square pole-top mounted floodlight for outdoor installation on a pole diam. 60 mm with single supporting arm. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 12 or 24 CREE XP-G3 LED. IP65 rating.

**Energy Label** **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 12 -> 24 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double M20 rubber grommet Rutaseal® in EPDM
- 3 m neoprene power cable included

+20°  
ADJUSTABLE  
-20°




**AVAILABLE OPTICS:**



CYCLE ROUTE / PEDESTRIAN










STREET



		LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
803005	HYDROBOOK ARM POLE-TOP MAXI 12 LED	HIGH-POWER LED	<div><div></div><div>3.000°K WARM-WHITE</div></div>	<div><div></div><div>CYCLE ROUTE PEDESTRIAN</div></div>	1.728	96.00	<div><div></div><div>TEXTURED GREY</div></div>
18 WATT 220-240V 50-60HZ ELECTRONIC IP65 3,60 KG UNIT GROSS WEIGHT				<div><div></div><div>STREET</div></div>			<div><div></div><div>MATT WHITE (ON REQUEST)</div></div> <div><div></div><div>MATT BLACK (ON REQUEST)</div></div>

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE




		LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
803006	HYDROBOOK ARM POLE-TOP MAXI 24 LED	HIGH-POWER LED	 3.000°K WARM-WHITE	 CYCLE ROUTE PEDESTRIAN	3.456	96.00	 TEXTURED GREY
				 STREET			 MATT WHITE <i>(ON REQUEST)</i>
							 MATT BLACK <i>(ON REQUEST)</i>


\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE

## POLES & ACCESSORIES


### BURIED POLES



CODE	ARTICLE	HEIGHT MM.	DESCRIPTION
809901	CYLINDRICAL POLE 3,5 METERS TO BE BURIED	3.500	Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), <b>diameter 76 mm, thickness 4 mm.</b> Phospho-chromatised and polyester powder coated. <b>Total height including 500 mm to be buried into the ground.</b> Includes IP54 cover plate 132x38 mm and terminal block in double insulation.
809902	CYLINDRICAL POLE 4,5 METERS TO BE BURIED	4.500	
809903	CYLINDRICAL POLE 5,5 METERS TO BE BURIED	5.500	
809908	ADAPTER DIAM. 76MM → 60MM		Adapter for pole diam. 76 mm, allow the diameter reduction to 60 mm



### POLES WITH BASE-PLATE



CODE	ARTICLE	HEIGHT MM.	DESCRIPTION
809904	CYLINDRICAL POLE 3 METERS WITH BASE-PLATE	3.000	Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), <b>diameter 76 mm, thickness 4 mm.</b> Phospho-chromatised and polyester powder coated. <b>With base plate dim. 250x250 mm, thickness 10 mm</b> Includes IP54 cover plate 132x38 mm and terminal block in double insulation.
809905	CYLINDRICAL POLE 4 METERS WITH BASE-PLATE	4.000	
809906	CYLINDRICAL POLE 5 METERS WITH BASE-PLATE	5.000	
809907	ANCHORAGE UNIT FOR BASE-PLATE		Base plate dim. 250x250 mm, thickness 3 mm, made in galvanized steel complete of nr. 4 anchorage threaded bolts
809908	ADAPTER DIAM. 76MM → 60MM		Adapter for pole diam. 76 mm, allow the diameter reduction to 60 mm

## 804001 SINGLE HYDROTECH POLE-TOP MEDIUM 01 ROUND LED




Round pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm or 76 mm, with downward light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws.












Clamp for pole diam 60 mm or 76 mm included.

Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP65 rating.


### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	 3.000°K WARM-WHITE	 10°	720	90.00	 TEXTURED GREY  MATT WHITE (ON REQUEST)  MATT BLACK (ON REQUEST)
		 30°	684	85.50	
		 45°	650	81.25	
	 4.000°K NEUTRAL-WHITE	 10°	750	93.75	
		 30°	713	89.13	
		 45°	677	84.63	

8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
3,80 KG UNIT GROSS WEIGHT













## 804005 SINGLE HYDROTECH POLE-TOP MEDIUM 01 ROUND PRO LED

Round pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm or 76 mm, with downward light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-L LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 CREE "XP-L" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
14 WATT 220-240V 50-60HZ ELECTRONIC IP65 3,80 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	 10°	1.300	92.86	 TEXTURED GREY  MATT WHITE (ON REQUEST)  MATT BLACK (ON REQUEST)
			 30°	1.230	87.86	
			 45°	1.170	83.57	


\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE

804002 DOUBLE HYDROTECH POLE-TOP MEDIUM 01 ROUND LED

2 x round pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm or 76 mm, with downward light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 2 x 5 CREE XP-G3 LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 5 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



2X8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
7,00 KG UNIT GROSS WEIGHT


LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	2 X 720	90.00	<div><div></div> TEXTURED GREY</div> <div><div></div> MATT WHITE (ON REQUEST)</div> <div><div></div> MATT BLACK (ON REQUEST)</div>
		30°	2 X 684	85.50	
		45°	2 X 650	81.25	
	4.000°K NEUTRAL-WHITE	10°	2 X 750	93.75	
		30°	2 X 713	89.13	
		45°	2 X 677	84.63	

## 804006 DOUBLE HYDROTECH POLE-TOP MEDIUM 01 ROUND PRO LED

2 x round pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm or 76 mm, with downward light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 2 x 5 CREE XP-L LED. IP65 rating.


### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 5 CREE "XP-L" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2X14 WATT 220-240V 50-60HZ ELECTRONIC IP65 7,00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	10°	2 X 1.300	92.86	TEXTURED GREY
			30°	2 X 1.230	87.86	MATT WHITE (ON REQUEST)
			45°	2 X 1.170	83.57	MATT BLACK (ON REQUEST)

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE




## 804003 SINGLE HYDROTECH POLE-TOP MEDIUM 01 SQUARE LED












Square pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm or 76 mm, with downward light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP65 rating.


### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
3,80 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	 3.000°K WARM-WHITE	 10°	720	90.00	 TEXTURED GREY  MATT WHITE (ON REQUEST)  MATT BLACK (ON REQUEST)
		 30°	684	85.50	
		 45°	650	81.25	
	 4.000°K NEUTRAL-WHITE	 10°	750	93.75	
		 30°	713	89.13	
		 45°	677	84.63	




## 804007 SINGLE HYDROTECH POLE-TOP MEDIUM 01 SQUARE PRO LED

Square pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm or 76 mm, with downward light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-L LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 CREE "XP-L" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
14 WATT 220-240V 50-60HZ ELECTRONIC IP65 3,80 KG UNIT GROSS WEIGHT	HIGH-POWER LED	 3.000°K WARM-WHITE	10°	1.300	92.86	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)
			30°	1.230	87.86	
			45°	1.170	83.57	


\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE

804004 DOUBLE HYDROTECH POLE-TOP MEDIUM 01 SQUARE LED

2 x square pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm or 76 mm, with downward light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 2 x 5 CREE XP-G3 LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphocromating pre-finish
- NR. 2 x 5 x 1.5W CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



2X8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
7,00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	2 X 720	90.00	<div><div></div> TEXTURED GREY</div> <div><div></div> MATT WHITE (ON REQUEST)</div> <div><div></div> MATT BLACK (ON REQUEST)</div>
		30°	2 X 684	85.50	
		45°	2 X 650	81.25	
	4.000°K NEUTRAL-WHITE	10°	2 X 750	93.75	
		30°	2 X 713	89.13	
		45°	2 X 677	84.63	


**804008 DOUBLE HYDROTECH POLE-TOP MEDIUM 01 SQUARE PRO LED**



2 x square pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm or 76 mm, with downward light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 2 x 5 CREE XP-L LED. IP65 rating.


**Energy Label** **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 5 CREE "XP-L" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- 3 m neoprene power cable included



	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2X14 WATT 220-240V 50-60HZ ELECTRONIC IP65 7,00 KG UNIT GROSS WEIGHT	HIGH-POWER LED	3.000°K WARM-WHITE	10°	2 X 1.300	92.86	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)
			30°	2 X 1.230	87.86	
			45°	2 X 1.170	83.57	

\* OTHER LIGHT COLORS AVAILABLE ON REQUEST: ○ 4.000°K NEUTRAL-WHITE




## 805001 SINGLE HYDROFLASH POLE MEDIUM LED



Round pole-mounted floodlight for outdoor installation on a pole diam. 60 mm or 76 mm. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 high-power LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 5 CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 3 mt. neoprene power cable included



AC-026 - ANTI-GLARE VISOR FOR HYDROFLASH MEDIUM

GRADUATED STAINLESS STEEL INSERT


8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
3,00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	720	90.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		30°	684	85.50	
		45°	650	81.25	
	4.000°K NEUTRAL-WHITE	10°	750	93.75	
		30°	713	89.13	
		45°	677	84.63	

### POLES & ACCESSORIES


Full technical details of poles and accessories for poles are available at the end of the catalogue

#### BURIED POLES



CODE	HEIGHT MM.
809901	3.500
809902	4.500
809903	5.500
809908	ACC.

#### POLES WITH BASE-PLATE



CODE	HEIGHT MM.
809904	3.000
809905	4.000
809906	5.000
809907	ACC.
809908	ACC.




## 805002 SINGLE HYDROFLASH POLE MEDIUM COB LED

**NEW**

Round pole-mounted floodlight for outdoor installation on a pole diam. 60 mm or 76 mm. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 1 CREE CXA 1512 COB LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 CREE CXA 1512 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 3 mt. neoprene power cable included



AC-026 - ANTI-GLARE VISOR FOR HYDROFLASH MEDIUM


GRADUATED STAINLESS STEEL INSERT

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
18 WATT 220-240V 50-60HZ ELECTRONIC IP65 3,00 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	35°	1.530	85.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>

### POLES & ACCESSORIES


Full technical details of poles and accessories for poles are available at the end of the catalogue

#### BURIED POLES



CODE	HEIGHT MM.
809901	3.500
809902	4.500
809903	5.500
809908	ACC.

#### POLES WITH BASE-PLATE



CODE	HEIGHT MM.
809904	3.000
809905	4.000
809906	5.000
809907	ACC.
809908	ACC.


805003 SINGLE HYDROFLASH POLE MAXI LED



Round pole-mounted floodlight for outdoor installation on a pole diam. 60 mm or 76 mm. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-G3 high-power LED. IP65 rating.

Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 8 CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 3 mt. neoprene power cable included



AC-027 - ANTI-GLARE VISOR FOR HYDROFLASH MEDIUM

GRADUATED STAINLESS STEEL INSERT


12 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
4,00 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	1.152	96.00	TEXTURED GREY
		30°	1.095	91.25	
		45°	1.040	86.67	MATT WHITE (ON REQUEST)
	4.000°K NEUTRAL-WHITE	10°	1.200	100.00	
		30°	1.140	95.00	
		45°	1.083	90.25	MATT BLACK (ON REQUEST)

POLES & ACCESSORIES


Full technical details of poles and accessories for poles are available at the end of the catalogue

BURIED POLES



CODE	HEIGHT MM.
809901	3.500
809902	4.500
809903	5.500
809908	ACC.

POLES WITH BASE-PLATE



CODE	HEIGHT MM.
809904	3.000
809905	4.000
809906	5.000
809907	ACC.
809908	ACC.


## 805004 SINGLE HYDROFLASH POLE MAXI COB LED



Round pole-mounted floodlight for outdoor installation on a pole diam. 60 mm or 76 mm. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 1 CREE CXB 2530 COB LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 1 CREE CXB 2530 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 3 mt. neoprene power cable included



AC-027 - ANTI-GLARE VISOR FOR HYDROFLASH MEDIUM


GRADUATED STAINLESS STEEL INSERT

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
36 WATT 220-240V 50-60HZ ELECTRONIC IP65 4,00 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	35°	3.100	86.10	<div>■</div> TEXTURED GREY <div>□</div> MATT WHITE (ON REQUEST) <div>■</div> MATT BLACK (ON REQUEST)

### POLES & ACCESSORIES


Full technical details of poles and accessories for poles are available at the end of the catalogue

#### BURIED POLES



CODE	HEIGHT MM.
809901	3.500
809902	4.500
809903	5.500
809908	ACC.

#### POLES WITH BASE-PLATE



CODE	HEIGHT MM.
809904	3.000
809905	4.000
809906	5.000
809907	ACC.
809908	ACC.

805005 DOUBLE HYDROFLASH POLE MEDIUM LED



2 x Round pole-mounted floodlight for outdoor installation on a pole diam. 60 mm or 76 mm. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 1 CREE CXA 1512 COB LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 5 CREE "XP-G2" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 3 mt. neoprene power cable included



AC-026 - ANTI-GLARE VISOR FOR HYDROFLASH MEDIUM

GRADUATED STAINLESS STEEL INSERT


2 X 8 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
5,60 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	10°	2 X 720	90.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		30°	2 X 684	85.50	
		45°	2 X 650	81.25	
	4.000°K NEUTRAL-WHITE	10°	2 X 750	93.75	
		30°	2 X 713	89.13	
		45°	2 X 677	84.63	

POLES & ACCESSORIES


Full technical details of poles and accessories for poles are available at the end of the catalogue

BURIED POLES



CODE	HEIGHT MM.
809901	3.500
809902	4.500
809903	5.500
809908	ACC.

POLES WITH BASE-PLATE



CODE	HEIGHT MM.
809904	3.000
809905	4.000
809906	5.000
809907	ACC.
809908	ACC.







## 805006 DOUBLE HYDROFLASH POLE MEDIUM COB LED



2 x Round pole-mounted floodlight for outdoor installation on a pole diam. 60 mm or 76 mm. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 1 CREE CXA 1512 COB LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 1 CREE CXA 1512 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 3 mt. neoprene power cable included



AC-026 - ANTI-GLARE VISOR FOR HYDROFLASH MEDIUM


GRADUATED STAINLESS STEEL INSERT

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2 X 18 WATT 220-240V 50-60HZ ELECTRONIC IP65 5,60 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	35°	2 X 1.530	85.00	<div></div> TEXTURED GREY <div></div> MATT WHITE (ON REQUEST) <div></div> MATT BLACK (ON REQUEST)

### POLES & ACCESSORIES


Full technical details of poles and accessories for poles are available at the end of the catalogue

#### BURIED POLES



CODE	HEIGHT MM.
809901	3.500
809902	4.500
809903	5.500
809908	ACC.

#### POLES WITH BASE-PLATE



CODE	HEIGHT MM.
809904	3.000
809905	4.000
809906	5.000
809907	ACC.
809908	ACC.





## 805007 DOUBLE HYDROFLASH POLE MAXI LED



2 x Round pole-mounted floodlight for outdoor installation on a pole diam. 60 mm or 76 mm. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 8 CREE XP-G3 high-power LED. IP65 rating.

### Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 8 CREE "XP-G3" LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 3 mt. neoprene power cable included



AC-027 - ANTI-GLARE VISOR FOR HYDROFLASH MEDIUM



GRADUATED STAINLESS STEEL INSERT


2 X 12 WATT  
220-240V 50-60HZ ELECTRONIC  
IP65  
7,50 KG UNIT GROSS WEIGHT

LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
HIGH-POWER LED	3.000°K WARM-WHITE	M 10°	2 X 1.152	96.00	<div>TEXTURED GREY</div> <div>MATT WHITE (ON REQUEST)</div> <div>MATT BLACK (ON REQUEST)</div>
		M 30°	2 X 1.095	91.25	
		M 45°	2 X 1.040	86.67	
	4.000°K NEUTRAL-WHITE	M 10°	2 X 1.200	100.00	
		M 30°	2 X 1.140	95.00	
		M 45°	2 X 1.083	90.25	

### POLES & ACCESSORIES


Full technical details of poles and accessories for poles are available at the end of the catalogue

### BURIED POLES



CODE	HEIGHT MM.
809901	3.500
809902	4.500
809903	5.500
809908	ACC.

### POLES WITH BASE-PLATE



CODE	HEIGHT MM.
809904	3.000
809905	4.000
809906	5.000
809907	ACC.
809908	ACC.


## 805008 DOUBLE HYDROFLASH POLE MAXI COB LED



2 x Round pole-mounted floodlight for outdoor installation on a pole diam. 60 mm or 76 mm. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 1 CREE CXB 2530 COB LED. IP65 rating.

### Energy Label **A++**

- Material: high corrosion resistance die-cast copper-free aluminum body
- Coating: polyester powder coating with phosphochromating pre-finish
- NR. 2 x 1 CREE CXb 2530 LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass.
- Double nickel-plated brass cable gland PG11
- 3 mt. neoprene power cable included



AC-027 - ANTI-GLARE VISOR FOR HYDROFLASH MEDIUM




GRADUATED STAINLESS STEEL INSERT

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
2 X 36 WATT 220-240V 50-60HZ ELECTRONIC IP65 7,50 KG UNIT GROSS WEIGHT	COB LED	3.000°K WARM-WHITE	35°	2 X 3.100	86.10	<div></div> TEXTURED GREY <div></div> MATT WHITE (ON REQUEST) <div></div> MATT BLACK (ON REQUEST)

### POLES & ACCESSORIES


Full technical details of poles and accessories for poles are available at the end of the catalogue

#### BURIED POLES




CODE	HEIGHT MM.
809901	3.500
809902	4.500
809903	5.500
809908	ACC.

#### POLES WITH BASE-PLATE



CODE	HEIGHT MM.
809904	3.000
809905	4.000
809906	5.000
809907	ACC.
809908	ACC.

**POLES BURIED POLES**



**809901 CYLINDRICAL POLE 3,5 M.  
TO BE BURIED**

Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), **diameter 76 mm, thickness 4 mm.**

Phospho-chromatised and polyester powder coated.

**Total height 3.500 mm, including 500 mm** to be buried into the ground. Includes IP54 cover plate 132x38 mm and terminal block in double insulation.

**809902 CYLINDRICAL POLE 4,5M.  
TO BE BURIED**

Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), **diameter 76 mm, thickness 4 mm.**

Phospho-chromatised and polyester powder coated.


**Total height 4.500 mm, including 500 mm** to be buried into the ground. Includes IP54 cover plate 132x38 mm and terminal block in double insulation.

**809903 CYLINDRICAL POLE 5,5 M.  
TO BE BURIED**


Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), **diameter 76 mm, thickness 4 mm.**

Phospho-chromatised and polyester powder coated.


**Total height 5.500 mm, including 500 mm** to be buried into the ground. Includes IP54 cover plate 132x38 mm and terminal block in double insulation.



T= GROUNDING, THREADHD GALVANIZED INSERT  
POLE THICKNESS= 4MM




T= GROUNDING, THREADHD GALVANIZED INSERT  
POLE THICKNESS= 4MM



T= GROUNDING, THREADHD GALVANIZED INSERT  
POLE THICKNESS= 4MM


**POLES POLES WITH BASE-PLATE**



**809904**

**CYLINDRICAL POLE 3 M.  
WITH BASE-PLATE**

Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), **diameter 76 mm, thickness 4 mm.** Phospho-chromatised and polyester powder coated. **Total height 3.000 mm, with base plate dim. 250x250 mm, thickness 10 mm.** Includes IP54 cover plate 132x38 mm and terminal block in double insulation.




T= GROUNDING, THREADHD GALVANIZED INSERT  
POLE THICKNESS= 4MM

**809905**

**CYLINDRICAL POLE 4 M.  
WITH BASE-PLATE**

Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), **diameter 76 mm, thickness 4 mm.** Phospho-chromatised and polyester powder coated. **Total height 4.000 mm, with base plate dim. 250x250 mm, thickness 10 mm.** Includes IP54 cover plate 132x38 mm and terminal block in double insulation.




T= GROUNDING, THREADHD GALVANIZED INSERT  
POLE THICKNESS= 4MM


**809906**

**CYLINDRICAL POLE 5 M.  
WITH BASE-PLATE**

Cylindrical pole made in steel S235JR (UNI EN 10219) hot galvanized (UNI EN 1461), **diameter 76 mm, thickness 4 mm.** Phospho-chromatised and polyester powder coated. **Total height 5.000 mm, with base plate dim. 250x250 mm, thickness 10 mm.** Includes IP54 cover plate 132x38 mm and terminal block in double insulation.









T= GROUNDING, THREADHD GALVANIZED INSERT  
POLE THICKNESS= 4MM





## ELEMENTS TO CONSIDER IN A NEW (OR EXISTING) LIGHTING PROJECT

### IP protective degree (IEC 529 & EN 60529 norms)


IP 1...	Protected against the entry of solid bodies with dimensions of more than 50 mm.	IP ...0	Unprotected.
IP 2...	Protected against the entry of solid bodies with dimensions of more than 12 mm.	IP ...1	Protected against the vertical falling of water drops.
IP 3...	Protected against the entry of solid bodies with dimensions of more than 2,5 mm.	IP ...2	Protected against the falling of water with a maximum inclination of 15°.
IP 4...	Protected against the entry of solid bodies with dimensions of more than 1 mm.	IP ...3 	Protected against rain.
IP 5... 	Protected against entry of dust.	IP ...4 	Protected against sprinklings.
IP 6... 	Completeley protected against entry of dust.	IP ...5 	Protected against water jets.
		IP ...6	Protected against heavy waves.
		IP ...7 	Temporary immersion proof.
		IP ...8	Immersions.

### WARNING. UNLESS OTHERWISE SPECIFIED ARTICLES IN THIS CATALOGUE ARE NOT FOR PERMANENT AND CONTINUOUS IMMERSION IN WATER.

Some fittings, although classified and tested IP 68 cannot be installed permanently in water according to international norms IEC364-7-702 (max 12 V A.C. or 30 V D.C. in water). They can only withstand (resist) accidental immersion of 1,3 m depth due to temporary flooding.

**WARNING:** in all ground lighting fittings installation, at least a 20 cm depth drain hole filled by gravel must be made to prevent flooding.

**Use H07RN-F cables only. Other kind of cables may not be conformed to assure the IP 67 or IP 68 rating.**



### Mechanical shock (CEI EN 50102 norms)

Protection of the hardware against the mechanical shocks.  
Test: shock resistance from a hammer of 5 kg falling from 0,40 m.  
Intensity of shock: 20 Joules = IK 10.

### Shock resistance CEI EN 50102

IK00	
IK01	0,15 J
IK02	0,2 J
IK03	0,35 J
IK04	0,5 J
IK05	0,7 J
IK06	1 J
IK07	2 J
IK08	5 J
IK09	10 J
IK10	20 J

### WARNING!

SOME CHEMICAL SUBSTANCES, LIQUIDS OR VAPOUR, MAY CAUSE CORROSION/ DAMAGES ON METAL PARTS OF THE FITTINGS.  
VERIFY THE PRESENCE OF THESE SUBSTANCES WHEN INSTALLING THE PRODUCTS AND THE COMPATIBILITY WITH SUCH SUBSTANCES.  
STAINLESS STEEL SURFACES COULD BE DAMAGED BY: SODIUM HYDROXIDE (SODA), LIQUID CHLORINE OR VAPOUR, HYDROCHLORIC ACID, NITRIC ACID (20%), SULPHURIC ACID (30%).

DIE-CAST ALUMINIUM COULD BE DAMAGED BY: ARSENIC ACID (20%), ACETIC ACID, HYDROCHLORIC ACID, FORMIC ACID, NITRIC ACID (20%), SULPHURIC ACID (30%), QUICKLIME, SODIUM HYDROXIDE (SODA).  
SUGGESTION: VERY IMPORTANT IS TO REGULARLY CLEAN THE FITTING SURFACES. AT LEAST ONCE A YEAR OR DURING BULB REPLACEMENT. CLEANING COULD BE MADE WITH DILUTED SOAP OR DETERGENT. IN ANY CASE DO NOT USE SOLVENT OR ETHYLENE BASE PRODUCTS.

**TUPexElektriska Guarantee terms**

**Tupex AB** guarantees the performance of its products only and exclusively in relation to how they are used, their destination and application as explicitly specified.

**THE GUARANTEE OF THE PRODUCTS HAS A 5 YEAR VALIDITY STARTING FROM THE DATE OF DELIVERY TO THE PURCHASER.**

Any claims must be forwarded in writing to **Tupex AB** together with a copy of the purchase invoice complete with delivery date, description of the fault and number of products that are faulty.

**Tupex AB** according to its indisputable choice will arrange either to repair or replace them within a reasonable period of time from the claim. Returned faulty goods will be accepted by **Tupex AB** only if previously authorized in writing, correctly forwarded suitably packed and with transport prepaid.

This guarantee does not cover further expenses sustained by the Purchaser consequent to the faulty condition of the products; in particular **Tupex AB** will not bear the cost of collecting the faulty products from customers (including cost of dismantling) and forwarding of replacement products to them.

Any responsibility on the part of **Tupex AB** is explicitly excluded in the following cases:

- Use, assembly and/or improper or unreasonable maintenance of the products, and/or their correct preservation
- If damage or bad functioning is caused by work carried out on products without prior written authorization from **Tupex AB** [e.g. disassembly, alterations, substitutions, etc.]
- If the quality and performance have been compromised by the addition of accessories not approved by **Tupex AB**.

This guarantee includes and replaces every other possible responsibility stemming from the products supplied, no matter how it originated: in particular the Purchaser cannot claim damages, reduction in prices or cancellation of the contract. In no case will **Tupex AB** be responsible for indirect damage or loss of profit. The Law Court in Monza is the sole competent Court for any disputes.

**TUPexElektriska Garantivillkor**

**Tupex AB** garanterar prestandan av sina produkter endast och uteslutande i relation till hur de används, sin destination och tillämpning som uttryckligen anges.

**GARANTIN AV PRODUKTERNA HAR EN 5 ÅRS GILTIGHET MED START FRÅN LEVERANSDATUM TILL KÖPAREN**

Alla anspråk skall skickas skriftligen till **Tupex AB** tillsammans med en kopia av fakturan komplett med leveransdatum, beskrivning av felet samt antalet produkter som är felaktiga.

**Tupex AB** enligt dess odiskutabla val ordnar antingen att reparera eller byta ut dem inom en rimlig tid från anspråket. Returnerade felaktiga varor kommer att accepteras av **Tupex AB** endast om tidigare godkänts skriftligen, korrekt vidarelämnat och lämpligt förpackat med transport förbetalt.

Denna garanti täcker inte ytterligare oavbrutna slutföranden av köparen till en följd av det felaktiga tillståndet av produkterna; **Tupex AB** kommer i synnerhet inte att bära kostnaderna för att samla in felaktiga produkter från kunder (inklusive kostnader för demontering) samt vidarebefordran av ersättningsprodukter för dem.

Något ansvar för **Tupex AB** uttryckligen utesluts i följande fall:

- Användning, montering och / eller felaktig eller orimlig underhåll av produkter och / eller deras rätt bevarande
- Om skada eller dålig funktion är orsakat av arbete som utförs på produkter utan skriftligt tillstånd från **Tupex AB** [t.ex. demontering, ändringar, substitutioner, etc.]
- Om kvaliteten och prestandan har äventyrats genom tillsats av tillbehör som inte godkänts av **Tupex AB**.

Denna garanti omfattar och ersätter alla andra möjliga ansvar som härrör från de produkter som levereras, oavsett hur det har sitt ursprung: I synnerhet kan köparen inte kräva skadestånd, sänkning av priserna eller uppsägning av avtalet. I inget fall kommer **Tupex AB** att ansvara för indirekt skada eller förlust av vinst. Domstolen i Monza är den enda behöriga domstol för alla tvister.

**TUPex** Elektriska**TUPex**Group




**NOVOSIBIRSK MARRIOT HOTEL**  
Location: Novosibirsk, Russia



**105003**  
**Hydroscape LED**



**201034**  
**Hydrofloor**  
**Maxi Performance LED**





TUPEX AB  
GROSSIST INOM EL-BELYSNING & VVS  
Tel: +46 08 544 011 11  
[www.tupex.se](http://www.tupex.se)    [sales@tupex.se](mailto:sales@tupex.se)  
Stockholm - Sweden