
Technical features






108004

Skyscraper projector for outdoor installation to wall wash a building façade. Anodized extruded aluminium body, phosphochromatised and polyester powder coated die-cast copper-free aluminium closing caps, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 24 CREE LED. IP66 rating.



Technical data

| Wattage | 55 WATT |
|--------------|--|
| IP Rating | IP66 |
| IK Rating | IK07 |
| Material | High corrosion resistance anodized extruded aluminum body, die-cast copper-free aluminum closing caps |
| Coating | Polyester powder coating with phosphocromating pre-finish |
| Light source | NR. 24 x 2W CREE LED |
| Screws | Stainless steel |
| Transformer | Electronic transformer 220/240V 50/60Hz included |
| Gasket | Silicone rubber |
| Glass | Tempered |
| Power cable | 0,5 mt. neoprene power cable included |
| Gross weight | 4.60 Kg |



| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) | |
|-------------------|-----------------------|----------------------|---------------------------|---|
| 3000°K warm-white | | | | |
| high-power led | 5° | 4.800 | 87.27 | _ |

Finish color options:

Silver