




202010

HYDROQUADRO MAXI PRO

Square ground-recessed luminaire for outdoor installation, Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 16 CREE XP-L LED. IP67 rating.



| light source* | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|--------------------------|--------------------|-------------------|------------------------|
| 3000°K warm-white | | | |
| high-power led | 10° | 3.920 | 89.10 |
| high-power led | 30° | 3.720 | 84.55 |
| high-power led | 45° | 3.540 | 80.45 |

* Other light colors available on request: Neutral-white

Finish color options:

Stainless Steel

Technical features



Technical data

| | |
|--------------------------|--|
| Wattage | 44 WATT |
| IP Rating | IP67 |
| IK Rating | IK10 |
| Material | High corrosion resistance die-cast copper-free aluminum body |
| Trim | Stainless steel AISI 304 |
| Coating | Polyester powder coating with phosphocromating pre-finish |
| Light source | NR. 16 CREE "XP-L" LED |
| Screws | Stainless steel |
| Transformer | Electronic power supply 220/240V 50/60Hz built-in |
| Static weight resistance | Max 5000 Kg |
| Gasket | Silicone rubber |
| Glass | Tempered |
| Cable gland | Double M20 |
| Adjustable | +/- 15 degrees |
| Power cable | 1 mt. neoprene power cable included |
| Gross weight | 5,70 Kg |
| Included | Polypropilene recessing box included |

