




204005


## LINE VETRO SLIM 500

Linear slim ground-recessed luminaire for outdoor installation, length 500 mm, anodized extruded aluminum body, opal resin diffuser, anodized aluminum housing for recess.

24V DC remote driver needed, Low power 36 Epistar SMD5050 LED.

IP67 rating.



| light source             | light beam options  | lumen output (lm) | lumin. efficacy (lm/w) |
|--------------------------|---|-------------------|------------------------|
| <b>3000°K warm-white</b> |   |                   |                        |
| SMD 5050 LED             |  90° | 150               | 21.43                  |

### Finish color options:

☐ Opal

### Technical features



NEW

### Technical data

|                          |  |
|--------------------------|--|
| Wattage                  | 7 WATT   |
| IP Rating                | IP67   |
| IK Rating                | IK09   |
| Material                 | High corrosion resistance extruded copper-free aluminum body   |
| Light source             | NR. 36 x Epistar SMD5050 LED   |
| Screws                   | Stainless steel  |
| Housing                  | Anodized aluminum  |
| Remote driver            | 24V DC Needed  |
| Static weight resistance | Max 3000 Kg  |
| Diffuser                 | Opal resin   |
| Power cable              | Double 0.5 mt. neoprene power cable included, supplied with male/female quick coupling for in-line installation. |
| Gross weight             | 2,10 Kg  |

### remote driver selection

| brand    | manufacturer code | type                    | watt | IP rate | numbers of fixtures |
|----------|-------------------|-------------------------|------|---------|---------------------|
| Meanwell | LPV-20-24         | constant voltage 24V DC | 20W  | IP67    | min 1 - max 2       |
| Meanwell | LPV-35-24         | constant voltage 24V DC | 35W  | IP67    | min 1 - max 3       |
| Meanwell | LPV-60-24         | constant voltage 24V DC | 60W  | IP67    | min 1 - max 7       |

