


## 401706 ECLIPSE MEDIUM SQUARE Designed by PAOLO VILLA

Square wall surface-mounted luminaire creating a **diffused and discrete light through the fixture perimeter** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with low-power CREE LED. IP65 rating.





light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)	
3000°K warm-white				
low power led	<b>3</b> 60°	636	45.42	

\* Other light colors available on request: Neutral-white

Finish color options:

Textured Grey RAL 9006





## **Technical features**



## Technical data

Wattage	14 WATT	
IP Rating	IP65	
IK Rating	IK08	
Material	High corrosion resistance die-cast copper-free aluminum body	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	Low-power CREE LED	
Screws	Stainless steel	
Transformer	Electronic power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Rubber grommet	M16 Rutaseal® in EPDM	
Diffuser	Polycarbonate	
Gross weight	1,50 Kg	

