





## **Technical features**





EXTERNAL TRIM REALIZED IN STAINLESS STEEL AISI 316L

NO VISIBLE SCREWS ONCE THE PRODUCT IS INSTALLED

Technical data		
IP Rating	IP67	
IK Rating	10	
Material	High corrosion resistance die-cast copper-free aluminum body	
Trim	Stainless steel AISI 316	
Coating	Polyester powder coating with phosphocromating pre-finish	
Screws	Stainless steel	
Gasket	Silicone rubber	
Glass	Tempered	
Power cable	1 mt. power cable included	



16 mm

REDUCED WIDTH AT 16 MM FOR BETTER AESTHETIC IMPACT









VERY NARROW 10° MEDIUM 28°

NARROW

SPOT 18°

MEDIUM WIDE 36°

FLOOD 60°

WIDE

ASYMMETRIC WALL-WASHER

DIFFUSED

8°x170°



## 207002

# **TERRA MINI HP**

Diameter 140mm ground-recessed luminaire for outdoor installation, phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 316L frame, tempered safety glass, moulded silicone gasket. Light source tilt system +/- 15deg from outside. Built-in LED driver 220-240V 50-60Hz, with 1 CREE "XHP35" LED. IP67 rating.

light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white				
high-power led		4°	670	83.75
high-power led		10°	642	80.25
high-power led	V	28°	622	77.75
3000°K warm-white	_			
high-power led		4°	690	86.25
high-power led		10°	662	82.75
high-power led	V	28°	642	80.25
4000°K neutral-white	_			
high-power led		4°	703	87.88
high-power led		10°	676	84.50
high-power led	V	28°	656	82.00
Finish color options:				

Stainless Steel

# ACCESSORIES

AC116 - HONEYCOMB LOUVER FOR TERRA MINI



AC117 - GLARE SHIELD FOR TERRA MINI



#### **Technical features**



## Available on request





### **Technical data**

Wattage	8 WATT
IP Rating	IP67
IK Rating	IK10
Material	high corrosion resistance die-cast copper-free aluminum
Trim	Stainless steel AISI 316L
Coating	polyester powder coating with phosphocromating pre-finish
Light Source	Nr. 1 CREE XHP35 LED
Screws	Stainless steel
Transformer	Electrical power supply 220/240V 50/60Hz built in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	M20
Power cable	
Power cable	1 mt. neoprene power cable included
Gross weight	included



Glare shield accessory made in hard anodized black aluminum, for applications requiring very reduced glaring; minimal light loss on the light surface but overall lumen output typically reduced by 50%.