TERRA MINI




Technical features












EXTERNAL TRIM REALIZED IN STAINLESS STEEL AISI 316L

NO VISIBLE SCREWS ONCE THE PRODUCT IS INSTALLED

Technical data

IP Rating	IP67	
IK Rating	10	
Material	High corrosion resistance die-cast copper-free aluminum body	
Trim	Stainless steel AISI 316	
Coating	Polyester powder coating with phosphocromating pre-finish	
Screws	Stainless steel	
Gasket	Silicone rubber	
Glass	Tempered	
Power cable	1 mt. power cable included	



REDUCED WIDTH AT 16 MM FOR BETTER AESTHETIC IMPACT







LIGHT BEAM OPTIONS





VERY NARROW 10°



NARROW

SPOT 18°







WIDE

FLOOD 60°









MEDIUM 28°

MEDIUM WIDE 36°

ASYMMETRIC WALL-WASHER

DIFFUSED

8°x170°



207005

TERRA MINI WALL-WASHER

Diameter 140mm ground-recessed luminaire for outdoor installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 316L frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, , with 16 x mid-power SAMSUNG 2835 LED. IP67 rating.

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white			
mid-power led	WALL-WASHER	450	75.00
3000°K warm-white			
mid-power led	WALL-WASHER	470	78.34
4000°K neutral-white	•		
mid-power led	WALL-WASHER	490	81.67

Finish color options:



Stainless Steel

Technical features














Available on request







Technical data

Wattage	6 WATT
IP Rating	IP67
IK Rating	IK10
Material	high corrosion resistance die-cast copper-free aluminum
Trim	Stainless steel AISI 316L
Coating	polyester powder coating with phosphocromating pre-finish
Light Source	Nr. 16 x mid-power SAMSUNG 2835 LED
Screws	Stainless steel
Transformer	Electrical power supply 220/240V 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Cable gland	M20
Power cable	1 mt. neoprene power cable included
Gross weight	2,60 Kg

