


207007-08-09-10

TERRA MINI TRIMLESS



Technical features



Technical data

| | |
|-------------|--|
| IP Rating | IP67 |
| IK Rating | 10 |
| Material | High corrosion resistance die-cast copper-free aluminum body |
| Coating | Polyester powder coating with phosphochromating pre-finish |
| Screws | Stainless steel |
| Gasket | Silicone rubber |
| Glass | Tempered |
| Power cable | 1 mt. power cable included |



SPECIAL TILT SYSTEM INTEGRATED ALLOWING ON SITE ADJUSTMENT +/- 20 DEG. WITHOUT OPENING THE LUMINAIRE

LIGHT BEAM OPTIONS



EXTRA NARROW 4°

VERY NARROW 10°

NARROW SPOT 18°

MEDIUM 28°

MEDIUM WIDE 36°

WIDE FLOOD 60°

ASYMMETRIC WALL-WASHER

DIFFUSED

8°x170°



207007

TERRA MINI TRIMLESS COB


Diameter 130mm ground-recessed luminaire for outdoor installation, phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket. Light source tilt system +/- 15deg from outside. Built-in LED driver 220-240V 50-60Hz, with 1 CREE CXB1304 LED. IP67 rating.

| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|-----------------------------|--------------------|-------------------|------------------------|
| 2700°K warm-white | | | |
| cob led | 18° | 600 | 75.00 |
| cob led | 36° | 580 | 72.50 |
| cob led | 60° | 560 | 70.00 |
| 3000°K warm-white | | | |
| cob led | 18° | 620 | 77.50 |
| cob led | 36° | 600 | 75.00 |
| cob led | 60° | 580 | 72.50 |
| 4000°K neutral-white | | | |
| cob led | 18° | 640 | 80.00 |
| cob led | 36° | 620 | 77.50 |
| cob led | 60° | 600 | 75.00 |

Technical features



Available on request



Technical data

| | |
|--------------|---|
| Wattage | 8 WATT |
| IP Rating | IP67 |
| IK Rating | IK10 |
| Material | high corrosion resistance die-cast copper-free aluminum |
| Coating | polyester powder coating with phosphocromating pre-finish |
| Light Source | Nr. 1 CREE CXB1304 COB LED |
| Screws | Stainless steel |
| Transformer | Electrical power supply 220/240V 50/60Hz built in |
| Gasket | Silicone rubber |
| Glass | Tempered |
| Cable gland | M20 |
| Power cable | 1 mt. neoprene power cable included |
| Gross weight | 2,60 Kg |



ACCESSORIES

AC116 - HONEYCOMB LOUVER FOR TERRA MINI



AC117 - GLARE SHIELD FOR TERRA MINI



Glare shield accessory made in hard anodized black aluminum, for applications requiring very reduced glaring; minimal light loss on the light surface but overall lumen output typically reduced by 50%.