

207015

TERRA MAXI COB

Diameter 240mm ground-recessed luminaire for outdoor installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 316L frame, tempered safety glass, moulded silicone gasket. Light source tilt system +/- 15deg from outside. Built-in LED driver 220-240V 50-60Hz, with 1 CREE CXB2540 LED. IP67 rating.

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white			
cob led	14°	2.960	92.50
cob led	35°	2.940	91.88
cob led	55°	2.920	91.25
3000°K warm-white			
cob led	14°	2.970	92.81
cob led	35°	2.950	92.19
cob led	55°	2.930	91.56
4000°K neutral-white			
cob led	14°	2.990	93.44
cob led	35°	2.970	92.81
cob led	55°	2.950	92.19

Finish color options:

Stainless Steel

ACCESSORIES




AC119 HONEYCOMB LOUVER FOR TERRA MAXI

Technical features



Available on request





Technical data

reennear aat	u	
Wattage	32 WATT	
IP Rating	IP67	
IK Rating	IK10	
Material	high corrosion resistance die-cast copper-free aluminum	
Trim	Stainless steel AISI 316L	
Coating	polyester powder coating with phosphocromating pre-finish	
Light Source	Nr. 1 CREE CXB2540 LED	
Screws	Stainless steel	
Transformer	Electrical power supply 220/240V 50/60Hz built in	
Gasket	Silicone rubber	
Glass	Tempered	
Cable gland	M20	
Power cable	1 mt. neoprene power cable included	
Gross weight	6,00 Kg	

