

Technical features














402601

TECH EVO MINI 01

Designed by MOMO DESIGN

Wall applique, to be mounted on an outdoor façade/wall, with one side light distribution. Phospho-chromatised and polyester powder coated copper-free extruded aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 3 CREE XP-G2 LED. IP 65 rating.



light source	light beam options		lumen output (In	lumin. efficacy n) (lm/w)
3000°K warm-white				
high-power led		12°	550	100
high-power led	Y	30°	520	94.54
high-power led	V	45°	495	90.00
4000°K neutral-white				
high-power led		12°	600	109.09
high-power led	Y	30°	570	103.63
high-power led		45°	540	98.18

Finish color options:







Technical data

Wattage	5.5 WATT		
IP Rating	IP65		
IK Rating	IK09		
Material	High corrosion resistance extruded copper-free aluminum body		
Coating	Polyester powder coating with phosphocromating pre-finish		
Light source	NR. 3 CREE XP-G2 LED		
Screws	Stainless steel		
Transformer	Electronic power supply 220/240V 50/60Hz built-in		
Cable gland	M16 rubber grommet		
Gasket	Silicone rubber		
Glass	Tempered		
Power cable	1 mt. neoprene power cable included		
Gross weight	2,00 Kg		





