


# 402602

# **ECH EVO MINI 02**

### **Designed by** MOMO DESIGN

Up & down wall applique for outdoor installation. Phosphochromatised and polyester powder coated copper-free extruded aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 3 CREE XP-G2 LED. IP 65 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
high-power led	10°	2 x 550	100.00
high-power led	30°	2 x 520	94.54
high-power led	45°	2 x 495	90.00
4000°K neutral-white			
high-power led	10°	2 x 600	109.09
high-power led	30°	2 x 570	103.63
high-power led	45°	2 x 540	98.18

## Finish color options:







### **Technical features**











**Technical data** 

Wattage	11 WATT	
IP Rating	IP65	
IK Rating	IK09	
Material	High corrosion resistance extruded copper-free aluminum body	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	NR. 2 x 3 CREE XP-G2 LED	
Screws	Stainless steel	
Transformer	Electronic power supply 220/240V 50/60Hz built-in	
Cable gland	M16 rubber grommet	
Gasket	Silicone rubber	
Glass	Tempered	
Power cable	1 mt. neoprene power cable included	
Gross weight	2,00 Kg	



