

## **Technical features**



**Technical data** 














## 402603

# Designed by MOMO DESIGN

Wall applique, to be mounted on an outdoor façade/wall, with one side light distribution. Phospho-chromatised and polyester powder coated copper-free extruded aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 COB CREE "CXB 1512" LED. IP 65 rating.




Wattage	15 WATT
IP Rating	IP65
IK Rating	IK09
Material	High corrosion resistance extruded copper-free aluminum body
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	NR. 1 COB CREE "CXB 1512" LED
Screws	Stainless steel
Transformer	Electronic power supply 220/240V 50/60Hz built-in
Cable gland	M16 rubber grommet
Gasket	Silicone rubber
Glass	Tempered
Power cable	1 mt. neoprene power cable included

### light beam lumin. efficacy light source lumen options output (lm) (lm/w) 3000°K warm-white cob led 14° 1.951 130.06 cob led 35° 1.850 123.33 cob led 55° 1.800 120.00 4000°K neutral-white 14° 2.240 149.33 cob led cob led 35° 2.131 142.06 cob led 55° 2.046 136.40

## Finish color options:









Gross weight 3,50 Kg



