

601504 PROMENADE SQUARE 02

1000mm height bollard, square shape, for outdoor surface installation, 360° downward light emission, phospho-chromatised and polyester powder coated extruded aluminum body and die-cast aluminium cover. Polycarbonate Fresnel diffuser, moulded silicone gasket and stainless steel screws. Anchorage flange with threaded bolts included. B uilt-in LED driver 220-240V 50-60Hz, with 1 x COB CREE "CXB 1520" LED. IP66 rating.

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
cob led	3 60°	2.900	111.54
4000°K neutral-white			
cob led	360°	3.100	119.23

Finish color options:

Textured Grey RAL 9006 Anthracite Grey RAL 7016






Technical features



Technical data

	-	
Wattage	26 WATT	
IP Rating	IP66	
IK Rating	IK10	
Material	High corrosion resistance die-cast copper-free aluminum body	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	NR. 1 COB CREE "CXB 1520" LED	
Screws	Stainless steel	
Transformer	Electronic power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Glass	Tempered	
Cable gland	M16 rubber grommet	
Power cable:	not included	
Gross weight	7,30 Kg	

AC053 - Base Plate





140x140 mm