


602202

ER 800

Designed by NAVA + AROSIO

800mm height bollard, for outdoor installation, 360° light distribution, phospho-chromatised and polyester powder coated die-cast aluminum head and extruded pole. Tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 24 x CREE "XH-G" LED. IP66 rating.





light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid-power led	• radial 360°	1.600	80.00
4000°K neutral-white			,
mid-power led	• radial 360°	1.650	82.50

Finish color options:

Textured Grey RAL 9006

Anthracite Grey RAL 7016



Technical features











Technical data

Wattage	20 WATT	
IP Rating	IP66	
IK Rating	IKO9	
Material	High corrosion resistance extruded copper-free aluminum head and extruded pole	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light Source	NR. 24 x CREE "XH-G" LED	
Screws	Stainless steel	
Transformer	Electronic power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Glass	Tempered	
Cable gland	PG11	
Power cable	1,5 meters power cable included	
Gross weight	4,30 Kg	





AC065 ANCHORAGE UNIT FOR ALDER SERIES

