

Technical features














701106

QUBO MEDIUM HP DOWNLIGHT

Surface mounted luminaire for outdoor ceiling installation. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium base and head, tempered safety glass, moulded silicone gaskets, with screws in stainless steel. Built-in LED driver, with 3 x CREE "XHP35" LED. IP66 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white	,		,
high-power led	4°	2.050	102.50
high-power led	10°	2.000	100.00
high-power led	28°	1.950	97.50
4000°K neutral-white			,
high-power led	4°	2.100	105.00
high-power led	10°	2.050	102.50
high-power led	28°	2.000	100.00

Finish color options:







Technical data

Wattage	20 WATT	
IP Rating	IP66	
IK Rating	IK10	
Material	High corrosion resistance die-cast copper-free aluminum body	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	3 x CREE "XHP35" LED	
Screws	Stainless steel	
Transformer	Electrical power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Glass	Tempered	
Power cable	1 mt. power cable included	
Gross weight	3,10 Kg	

AC073 HONEYCOMB LOUVER

