

Technical features














701107

Surface mounted luminaire for outdoor ceiling installation. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium base and head, tempered safety glass, moulded silicone gaskets, with screws in stainless steel. Built-in LED driver, with 6 x CREE "XHP35" LED. IP66 rating.



light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white				
high-power led		4°	4.300	113.15
high-power led	1	0°	4.260	112.10
high-power led	Y 2	28°	4.210	110.79
4000°K neutral-white			'	
high-power led		4°	4.400	115.79
high-power led	1	10°	4.360	114.74
high-power led	7 2	28°	4.310	113.42

Finish color options:







Technical data

Wattage	38 WATT	
IP Rating	IP66	
IK Rating	IK10	
Material	High corrosion resistance die-cast copper-free aluminum body	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	6 x CREE "XHP35" LED	
Screws	Stainless steel	
Transformer	Electrical power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Glass	Tempered	
Power cable	1 mt. power cable included	
Gross weight	4,50 Kg	

AC074 HONEYCOMB LOUVER

