





701207

CYLINDER MAXI HP

Surface mounted luminaire for outdoor ceiling installation. Phospho-chromatised and polyester powder coated extruded copper-free aluminium body, tempered safety glass, moulded silicone gaskets, with screws in stainless steel. Built-in LED driver, with 6 x CREE "XHP35" LED. IP66 rating.



| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|-----------------------------|--------------------|-------------------|------------------------|
| 3000°K warm-white | | | |
| high-power led | 4° | 4.300 | 113.15 |
| high-power led | 10° | 4.260 | 112.10 |
| high-power led | 28° | 4.210 | 110.79 |
| 4000°K neutral-white | | | |
| high-power led | 4° | 4.400 | 115.79 |
| high-power led | 10° | 4.360 | 114.74 |
| high-power led | 28° | 4.310 | 113.42 |

Finish color options:

Textured Grey
RAL 9006

Anthracite Grey
RAL 7016

Matt Black
(on request)

Technical features



Technical data

| | |
|--------------|--|
| Wattage | 38 WATT |
| IP Rating | IP66 |
| IK Rating | IK09 |
| Material | Phospho-chromatised and polyester powder coated extruded copper-free aluminium |
| Coating | Polyester powder coating with phosphocromating pre-finish |
| Light source | 6 x CREE "XHP35" LED |
| Screws | Stainless steel |
| Transformer | Electrical power supply 220/240V 50/60Hz built-in |
| Gasket | Silicone rubber |
| Glass | Tempered |
| Power cable | 1 mt. power cable included |
| Gross weight | 5,00 Kg |

AC093
HONEYCOMB LOUVER

