

701311

CIELO MAXI COB

Diameter 254mm ceiling-recessed luminaire for outdoor installation, phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 316L frame, tempered safety glass, moulded silicone gasket. Light source tilt system +/- 15deg from outside. Built-in LED driver 220-240V 50-60Hz, with 1 CREE CXB2540 LED. IP67 rating.

light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
2700°K warm-white				
cob led		14°	2.960	92.50
cob led	V	35°	2.940	91.88
cob led	V	55°	2.920	91.25
3000°K warm-white				
cob led	V	14°	2.970	92.81
cob led	V	35°	2.950	92.19
cob led	V	55°	2.930	91.56
4000°K neutral-white				
cob led	V	14°	2.990	93.44
cob led	V	35°	2.970	92.81
cob led	V	55°	2.950	92.19

Finish color options:



Stainless Steel

ACCESSORIES



AC119 HONEYCOMB LOUVER FOR CIELO MAXI

Technical features












Available on request







Technical data

Wattage	32 WATT	
IP Rating	IP67	
IK Rating	IK10	
Material	high corrosion resistance die-cast copper-free aluminum	
Trim	Stainless steel AISI 316L	
Coating	polyester powder coating with phosphocromating pre-finish	
Light Source	Nr. 1 CREE CXB2540 COB LED	
Screws	Stainless steel	
Transformer	Electrical power supply 220/240V 50/60Hz built in	
Gasket	Silicone rubber	
Glass	Tempered	
Cable gland	M20	
Power cable	1 mt. neoprene power cable included	
Gross weight	5,70 Kg	
	- 5,7 5 1 tg	

