

CIELO MAXI HP DMX RGBW

Diameter 254mm ceiling-recessed luminaire for outdoor installation, phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 316L frame, tempered safety glass, moulded silicone gasket. Light source tilt system +/- 15deg from outside. Built-in LED driver, DMX interface integrated; with 6 x CREE "XML" RGBW LED. IP67 rating.

light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
RGBW				
high-power led	Y	12°	1.000	35.71
high-power led	V	25°	992	35.43
high-power led	V	35°	981	35.04

Finish color options:



Stainless Steel

ACCESSORIES



AC119 HONEYCOMB LOUVER FOR CIELO MAXI

Technical features














Available on request







HOLE FOR RECESS

Technical data

	-	
Wattage	28 WATT	
IP Rating	IP67	
IK Rating	IK10	
Material	high corrosion resistance die-cast copper-free aluminum	
Trim	Stainless steel AISI 316L	
Coating	polyester powder coating with phosphocromating pre-finish	
Light Source	Nr. 6 CREE "XML" RGBW LED	
Screws	Stainless steel	
Remote driver	Constant voltage 24V DC remote driver needed	
DMX	DMX interface integrated	
Gasket	Silicone rubber	
Glass	Tempered	
Cable gland	M20 + PG9	
Power cable	1 mt. neoprene power cable included	
DMX cable	DMX IN cable included	
Gross weight	5,70 Kg	

