

Technical features














Available on request







HOLE FOR RECESS

Diameter 254mm ceiling-recessed luminaire for outdoor installation, phosphochromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 316L frame, tempered safety glass, moulded silicone gasket. Built-in LED driver 220-240V 50-60Hz, with 66 x mid-power SAMSUNG 2835 LED. IP67 rating.

ecnn	ıcaı	data	

Wattage	24 WATT	
IP Rating	IP67	
IK Rating	IK10	
Material	high corrosion resistance die-cast copper-free aluminum	
Trim	Stainless steel AISI 316L	
Coating	polyester powder coating with phosphocromating pre-finish	
Light Source	Nr. 66 x mid-power SAMSUNG 2835 LED	
Screws	Stainless steel	
Transformer	Electrical power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Glass	Tempered	
Cable gland	M20	
Power cable	1 mt. neoprene power cable included	
Gross weight	5,70 Kg	

light source light beam options lumin. efficacy lumen output (lm) (lm/w) 2700°K warm-white WALL-WASHER 75.00 1800 mid-power led 3000°K warm-white WALL-WASHER mid-power led 1880 78.33 4000°K neutral-white WALL-WASHER mid-power led 1960 81.67

Finish color options:



Stainless Steel

