

Technical features


















201034RGBW

DROFLOOR MAXI

Ground-recessed luminaire in round shape for outdoor installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver, DMX driver integrated; with 6 x CREE "XML" RGBW LED. IP67 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
RGBW			
high-power led	12°	1.000	35.71
high-power led	25°	992	35.43
high-power led	35°	981	35.04

Finish color options:



Stainless Steel

DMX ACCESSORIES

CONTROLLERS, SPLITTERS, ETC...

To be defined together with puk technical department, according to project specifications and after providing installation details.

Technical data

Wattage	28 WATT	
IP Rating	IP67	
IK Rating	IK10	
Material	High corrosion resistance die-cast copper-free aluminum body	
Trim	Stainless steel AISI 304	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	6 x CREE "XML" COLOR RGBW LED	
Screws	Stainless steel	
DMX	DMX interface integrated	
Transformer	Electronic power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Glass	Tempered	
Power cable	1 mt. neoprene power cable included	
DMX cable	DMX IN cable included	
Gross weight	5,10 Kg	