

Technical features














Technical data


201078

HYDROFLOOR MINI 01

Round ground-recessed luminaire diam. 138 mm for outdoor installation, Phosphochromatised and polyester powder coated die-cast copper-free aluminium body and top cover with one window (single light emission 1 x 90°), polycarbonate diffuser, moulded silicone gasket.

Built-in LED driver 220-240V 50-60Hz, with 1 CREE XHP-35 LED. IP67 rating.





Wattage	9 WATT		
IP Rating	IP67		
IK Rating	IK10		
Material	High corrosion resistance die-cast copper-free aluminum		
Trim	High corrosion resistance die-cast copper-free aluminum		
Coating	Polyester powder coating with phosphocromating pre-finish		
Light source	NR. 1 CREE XHP35 LED		
Screws	Stainless steel		
Transformer	Electrical power supply 220/240V 50/60Hz built-in		
Gasket	Silicone rubber		
Diffuser	Polycarbonate		
Cable gland	M20		
Power cable	1 mt. neoprene power cable included		
Gross weight	2,00 Kg		

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
high-power led	1 x 90°	220	24,45
4000°K neutral-white			
high-power led	1 x 90°	240	26,67

Finish color options:













