

### **Technical features**












DALI

### 402802

# FRAME MEDIUM SQUARE

## Designed by NAVA + AROSIO

Square 200x200mm surface mounted luminaire for outdoor installation on a façade/wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, acid-etched tempered glass diffuser white painted internally, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 36 x mid-power SAMSUNG 2835 LED. IP65 rating.



200 mm



73 mm



light source	light beam options		lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white				
high-power led		diffused	808	50.50
4000°K neutral-white				
high-power led		diffused	844	52.75

### Finish color options:







### **Technical data**

Wattage	16 WATT	
IP Rating	IP65	
IK Rating	IK09	
Material	High corrosion resistance extruded copper-free aluminum body	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	36 x mid-power SAMSUNG 2835 LED	
Screws	Stainless steel	
Transformer	Electronic power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Glass	Acid-etched tempered glass diffuser white painted internally	
Power cable	0,3 mt. power cable included	
Gross weight	3,50 Kg	



