


601801

BOULEVARD MINI 180

600mm height bollard, round shape, for outdoor surface installation, 180° light emission, phospho-chromatised and polyester powder coated extruded copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included. Built-in LED driver 220-240V 50-60Hz, with 8 CREE JK3030 mid-power LED. IP65 rating.



Ø 110 mm

light beam options	lumen output (lm)	lumin. efficacy (lm/w)				
3000°K warm-white						
• 180°	400	61.53				
4000°K neutral-white						
• 180°	410	63.08				
	• 180°	• 180° 400				

Finish color options:

Textured Grey RAL 9006

276 | tupex.se

Anthracite Grey RAL 7016 Matt Black (on request) **Technical features**



Тес	hni	ical	dat	ta

Wattage	6.5 WATT
IP Rating	IP65
IK Rating	IK10
Material	High corrosion resistance extruded copper-free aluminum body
Coating	Polyester powder coating with phosphocromating pre-finish
Light source	NR. 8 x CREE JK3030 LED
Screws	Stainless steel
Transformer	Electrical power supply 220/240V 50/60Hz built-in
Gasket	Silicone rubber
Diffuser	Polycarbonate diffuser
Gross weight	4,00 Kg

