

### Technical features



DALI












### 609002

# **BOULEVARD 01360**

## Designed by MOMO DESIGN

220mm height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included. Built-in LED driver 220-240V 50-60Hz, with 24 CREE XH-G mid-power LED. IP65 rating.



light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid power led	• 360°	1.600	84.21

<sup>\*</sup> Other light colors available on request: Neutral-white

### Finish color options:







#### Technical data

Wattage	18 WATT	
IP Rating	IP65	
IK Rating	IK10	
Material	High corrosion resistance die-cast copper-free aluminum body and frame.	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	NR. 24 CREE XH-G mid-power LED	
Screws	Stainless steel	
Transformer	Electronic power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Diffuser	Polycarbonate diffuser	
	Anchorage unit included	
Gross weight	4,20 Kg	

